2019 Snowrator®



Sidewalk Snow & Ice System



11 ich

THE ULTIMATE SIDEWALK SOLUTION

Any snow and ice contractor will tell you, managing sidewalks has its own set of challenges. The BOSS Snowrator® is a patented, right-size solution designed to make quick work of snow- and ice-covered sidewalks, and brings a maneuverable, multi-tasking, labor-saving solution to your fleet. Snowrator® reduces the need for shovelers, maximizing productivity and efficiency–whether in metro, commercial or residential environments–where clean and clear walking surfaces are always the top priority.

STANDARD FEATURES

- Four-Wheel Drive With Zero Turn Radius Capabilities provides maneuverability and traction in any condition.
- BOSS-Designed 4' Hydraulic Snowplow with 20" polyethylene skin improves reliability and maximizes productivity in light and heavy snow.
- BOSS Hydraulic Cylinders and Trip Springs maximize plow performance.
- Honda[®] GX390 Engine provides proven, turnkey power and performance in extreme cold.
- BOSS-Engineered Electrical System delivers weatherresistant performance and enhanced reliability.
- Float and Active Down Force increases productivity by maximizing scraping of plowing surfaces.
- Coated Hydraulic Hose Ends provide 7x greater corrosion resistance and increased reliability over previous designs.
- 20-Gallon Anti-Icing/Deicing Brine System quickly and efficiently controls surface area ice.
- LED Work Lights provide better and more reliable visibility on the job.

CONTRACTOR EFFICIENCY



LABOR SAVER

Snowrator® Quickly Deploys to plow and deice surface areas–effectively reducing the need for shovelers.

TIME SAVER

Brine, Spread and Plow at the same time to maximize on-the-job productivity and profitability.

BOSS stands behind every Snowrator[®] vehicle with improved parts availability and expanded dealer support nationwide. If you have questions or concerns or need additional support, contact BOSS customer service at 800-286-4155 or email sales@bossplow.com.

OPTIONAL SPREADER EQUIPMENT



EXACT PATH® 1.5 Cubic Foot drop spreader was designed exclusively for the Snowrator® to distribute salt at the optimum width while reducing contact with the plow attachment system and minimizing damage to turf.

FEATURES

- Variable Speed Control and Adjustable Feed Gate easily adjust material flow rate without tools.
- Conveniently Located on top of the base unit, the EXACT PATH[®] 1.5 spreader features a solid, poly hopper cover to keep material dry and free-flowing and flips back to block salt from falling into engine components while loading.
- Stainless Steel Hopper and Frame are built to outlast the elements.
- Top Screen With Bag Splitter allows for quick and easy opening and filtering of materials when filling.
- Enclosed, High-Torque Motor is weather- and dust-resistant to ensure performance, durability and reliability.



*All images shown may include standard/ optional equipment. Please consult your local BOSS Dealer for more information.



1.8 Cubic Foot Broadcast Spreader provides a wider-casting spreading option for larger areas and wider sidewalks.

FEATURES

BOSS

EXACT PRESE

- Adjustable Feed Gate maximizes efficiency and ease of operation.
- Vibrator reduces material bridging for increased spreading performance and ease of operation.
- BOSS Deflector and Spinner System is proven to perform with maximum spreading performance and easier operation.
- Stainless Steel Hopper and Frame are built to outlast the elements.



TO FIND A BOSS SNOWRATOR® DEALER, VISIT: **BOSSPLOW.COM**

ALL-NEW AND FULLY FEATURED



THE BOSS DIFFERENCE

With more than 30 years of snow and ice experience, BOSS re-engineered the Snowrator® to maximize performance and reliability. BOSS stands behind every Snowrator® vehicle with improved parts availability and expanded dealer and service locations across the country. Phone: 800-286-4155 or Email: sales@bossplow.com

BOSS PERFORMANCE & RELIABLILTY ENHANCEMENTS

- (B) Added rear fenders and splash guards to keep operators clean of snow, slush and water.
- (R) Upgraded hydraulic hose ends feature a coating that offers 7x greater corrosion resistance than the previous model.
- (B) Upgraded to nylon locking nuts to keep hardware from loosening during operation and continued vibration.

11

(R) Increased gauge of power and ground cable for greater power, performance and reliability.

- (B) Replaced terminal block with a weather-resistant electrical harness for added corrosion protection and plug-and-play functionality with optional equipment.
- Added rear reference bar for additional hand support and ease of operation.

STANDARD & OPTIONAL FEATURES,

- EXACT PATH® 1.5 DROP SPREADER (OPTIONAL EQUIPMENT)
- 2 REAR AND FRONT REFERENCE BARS
- **3** SNOWPLOW JOYSTICK CONTROLLER
- 4 4' FULLY HYDRAULIC BOSS SNOWPLOW WITH 20" TALL BLADE
- 5 BOSS SNOWRATOR[®] SNOWPLOW ATTACHMENT SYSTEM
- 6 HEAVY-DUTY SNOWPLOW TRIP SPRINGS
- 7 SNOWPLOW CROSSOVER RELIEF VALVE (NOT VISIBLE)
- 8 BOSS HYDRAULIC CYLINDERS
- 9 HONDA® GX390 ENGINE
- 10 LED WORKLIGHTS
- II STAINLESS STEEL PAINTED CHASSIS
- 12 5-GALLON BUCKET MOUNTS (OPTIONAL EQUIPMENT)
- 13 BRINE SYSTEM HAND WAND



An exclusive salt chute for the EXACT PATH® spreader precisely distributes salt at the optimum width, reduces salt contact with the plow attachment system and minimizes damage to turf.



SEE THE SNOWRATOR® IN ACTION **BOSSPLOW.COM**

(B) Upgraded to a new, 100% BOSS-designed snowplow (plow, trip springs, mounts, hydraulics) that is proven to perform.



(Reference) Upgraded to a new, fully potted spreader control that is weather-resistant and easy to operate and offers onboard diagnostics for troubleshooting.

STOURATOR ENHANCE THE PERFORMANCE OF YOUR BOSS SNOWRATOR® WITH GENUINE, FACTORY-BACKED Accessories from Boss.



5-GALLON BUCKET MOUNTS Optional 5-gallon bucket mounts attach quickly and simply to Snowrator® and give an operator easy access to additional deicing materials on the back of the unit.



20-GALLON AUXILIARY TANK

The auxiliary tank adds an additional 20 gallons of brine carrying capacity, doubling the overall liquid volume the machine can carry. The tank integrates with existing pump, nozzles and wand and cuts return trips to refill by half.



BOX WING KIT

Carry more snow with your BOSS Snowrator[®] plow by adding a box wing kit. These wings easily bolt to the Snowrator® snowplow, providing a box-plow effect.



The Snowrator[®] is designed to use all BOSS ATV plow accessories and shares common parts with BOSS ATV plows-providing expanded parts availability and service nationwide.



MATERIAL HOLDING TRAYS Additional gear, fuel and deicing materials are in easy reach when material holding trays are added, saving time and money on the job by helping operators beat the clock.



URETHANE CUTTING EDGES Urethane cutting edges offer optimum scraping performance and are easier on sensitive surfaces.



BLADE EXTENSIONS

Extend the width of your BOSS Snowrator® plow by 12" overall (6" on each side) with the blade extension kit. This kit allows the operator to quickly change the plow's capabilities based on the job type.



BOSS SNOWRATOR®

SpinolEquipoEquipoGapina ManufacturerMode"Fed TaysenSacolineEquipo ManufacturerMode"Fed EquiportySacolineSalaceSalaceSalaceSalaceSpinoleneSalaceSalaceSalaceS		· · · · · · · ·		
Tanjan MaditatureHords*Fel TypeBasic MariaEngine MadidationCalls of Calls of	Specifications		Specifications	
Engine Model FoxOpent/ Page Source FoxOpent/ Engine Model FoxOpent/ Page Source Fo	Engine		Engine	
DisplacementJale cJeiner Oli CapacityJournal CapacityJournal CapacityCylindersSingleSingle CalibacySingle CalibacySingle CalibacyDimensionZaS CalibacyMarine CalibacySingle CalibacyMerchandSingle CalibacyHeightSingle CalibacyMerchandZaS CalibacyHeightSingle CalibacyLightinLightinLightinHeight CalibacyMore Light CalibacyMy CalibacyMarine CalibacyHeight CalibacyOrbertainHy CalibacyMy CalibacySingle CalibacyParadoHy CalibacyMy CalibacySingle CalibacyParadoHy CalibacyMy CalibacySingle CalibacyParado CalibacyHy CalibacySingle CalibacySingle CalibacyParado CalibacySingle CalibacySingle CalibacySingle CalibacySingle CalibacyCalibacy CalibacySingle CalibacySingle CalibacySingle CalibacyCalibacy Calibacy <td< td=""><td>Engine Manufacturer</td><td>Honda®</td><td>Fuel Type</td><td>Gasoline</td></td<>	Engine Manufacturer	Honda®	Fuel Type	Gasoline
CyloarsBineEnden Old Space (Normal Spa	Engine Model	GX390	Fuel Capacity	6.4 US qt
Dimensions Dimensions Empty Weight 8781b Width 885* tyehckiek, 46* (plow) Minecilase 24.5* Height 81.5* Length 24.5* Turning Redius 2.0* Withelbace 24.5* Turning Redius 2.0* Withelbace 2.5* Turning Redius 2.0* Weik Light Oly 3 Otiversion 1440 lunees, P67-rating Driversion Meric Light Oly Oly 1440 lunees, P67-rating 2.5* Driversion Meric Light Oly 2.5* 2.5* Page Hydrostaic Hydrostaic Plaid 9.4* Page Hydrostaic Search 2.5* 2.5* Forward Reverse Hydraulic log search 2.5* 2.5* Forward Reverse Hydraulic All Gastaic State 2.5* 2.5* State Oly Hydraulic State 2.5* 2.5* State Oly Hydraulic State 2.5* 3.5* State Oly Hydraulic State 2.5* 3.5* State Oly <td< td=""><td>Displacement</td><td>389 cc</td><td>Engine Oil</td><td>10w-30</td></td<>	Displacement	389 cc	Engine Oil	10w-30
Empty WeightS28 loWirkihS85 (vehicle), 49 (plow)Winde Abase24 5'Height51 5'LeghtYa25'Texing AddrsZeroLightingLightingLightingJaluanen, JPS7-ratingWork Light OdyNerk Light OdyAluanen, JPS7-ratingPorterialPorterialOrientalJaluanen, JPS7-ratingProtectingHydrostaticMydrastic Oli Filter (Section)Sindern replaceable filterParapHydrostaticHydrastic Oli Filter (Section)Sindern replaceable filterProtectingHydrastic Oli Filter (Section)Sindern replaceable filterProtectingHydrastic PercectingCastradSindern replaceable filterProtectingHydrastic PercectingFastradSindern replaceable filterProtectingSinder StategeSinder replaceableSinder replaceable filterProtecting Edge MaterialSinder StategeSinder replaceableSinder replaceableBade WitchSinder StategeSinder stategeSinder replaceableCastrad Edge MaterialSinder stategeSinder stategeSinder stategeSinder Edge MaterialSinder stategeSinder stategeSinder statege	Cylinders	Single	Engine Oil Capacity	1.16 US qt
WieleaseJ45°HeipitJ5°Lapita742°Turing RadiusZorLapitaLightingLightingSorWork Light Oxy3York Light OxyMed Humen, PES-ratingBriteratinNetwork Social	Dimensions		Dimensions	
LeginYara's Arian RadiusZeroLightingLightingLightingWork Light Output3Work Light OutputL440 Jamens, JPS7-ratingDrivertainDrivertainDrivertainSemicron replaceable filterParageHydrestlerHydrestlerHydralice Harlan Karlan KarlanSemicron replaceable filterParageHydrestlerHydrestlerHydralice Harlan KarlanSemicron replaceable filterParageHydrestlerHydralice Harlan KarlanSemicron replaceable filterParageHydrestlerHydralice Harlan KarlanSemicron replaceable filterParageHydralice Lever controlCastrostlerIssee genotorIssee genotorFraverd/BeerseHydralice Lever controlFraverd Semich config Carlan KarlanIssee genotorIssee genotorFraverd/BeerseHydralice Lever controlHydralice Lever ControlIssee genotorIssee genotorFraverd/BeerseHydralice Lever controlFraverd Semich config Carlan Karlan K	Empty Weight	828 lb	Width	38.5" (vehicle), 48" (plow)
Lighting Lighting Work Light Quay 3 400 Work Light Quaya 1440 Jummes, IPS / rating Priversin Priversin Priversin Type Hydro Gas ^{an} tandem, variable displacement pistom // Bydraile Fluid Diversin Pamp Hydro Gas ^{an} tandem, variable displacement pistom // Bydraile Fluid Diversin Diversin Pamp Hydro Gas ^{an} tandem, variable displacement pistom // Bydraile Fluid Diversin Diversin Pamp Andrea Hydro Gas ^{an} tandem, variable displacement pistom // Bydraile Fluid Diversin Diversin Control Hydro Gas ^{an} tandem, variable displacement pistom // Bydraile Fluid Diversin Diversin Forward/Reverse Hydradic lever control Torxtot Eversin Spany Diversing Andrea Forward Type Control Snaph Control Snaph Control Snaph Control Straight Bade Snaph Control Find Modioard trip Snaph Control Snaph Control Straight Bade Snaph Control Trip Modioard trip Snaph Control Snaph Control Straight Bade Snaph Control Snaph Control Snaph Control Snaph Control Find Contr	Wheelbase	24.5"	Height	51.5"
Work Light Otype 3 Work Light Otype 1440 lumenet, JPE3-rating Driveratin Driveratin Driveratin 25-micron replaceable filter Type Hydroslic Oti Filter (Soction) 25-micron replaceable filter Pamp Hydroslic Oti Filter (Soction) 25-micron replaceable filter Wheel Motors Parker* T8 Saries gerotor WW-40 synthetic Controls Controls Lever on desh Forward/Reverse Hydraulic levar control Torol Sarcer Forward Speed Hydraulic levar control Forward Speed Pamp switch, anylof control levalve, pressure regulating valve Forward Speed Mydraulic levar control Forward Speed Synapswitch, anylof control levalve, pressure regulating valve Forward Speed Mydraulic levar control Reserve Synapswitch, anylof control levalve, pressure regulating valve Forward Speed Toph Reserve Synapswitch, anylof control levalve, pressure regulating valve Forward Speed Toph Schone Synapswitch, anylof control levalve, pressure regulating valve Forward Speed Stell (urchane available) Plow Operation Sound contrecont float Cott	Length	74.25"	Turning Radius	Zero
Driversin Driversin Type Hydrostatic Hydrostatic 01 Filter (Suction) 25-micron replaceable filter Pamp Hydrostatic 02 Filter (Suction) 55-micron replaceable filter Pamp Hydrostatic 01 Filter (Suction) 55-micron replaceable filter Wheat Mators Parker* T8 Sarios gurator 55-micron replaceable filter Controls Controls Controls Lever on dash Forward (Reverse) Hydraulic lever control Travel Speed Pump switch, on/off control valve, pressure repulating valve Forward Speed Travel Speed Smplo Smplo Forward Speed Statight-Blade Figit Mechanism Full moldboard trip Statight Blade Statight-Blade Figit Mechanism Full moldboard trip Statight Blade Statight Blade Figit Mechanism Full moldboard trip Statight Blade Statight Blade Figit Mechanism Full moldboard trip Statight Blade Statight Blade Figit Mechanism Full moldboard trip Statight Blade Statight Blade Figit Mechanism Full moldboard trip S	Lighting		Lighting	
TypeHydrostaticHydraulic Oil Filter (Suction)25-micron replaceable filterPunpHydro-Gear* tandem, variable displacement piston yeHydraulic FluidW-40 syntheticWetel MatorsParker* TB Series genotorControlsControlsForward/ReverseHydraulic lover controlThrottleLever on dashPlow ControlHydraulic joystickLiquid System ControlPung switch, on/off control valve, pressure regulating valveForward/ReverseHydraulic joystickTravel SpeedSmpstich, on/off control valve, pressure regulating valveForwardMythaulic joystickSnavplowSnavplowTravel SpeedTravel SpeedSmphStoapt-bladeTrip MechanismFull moldboard tripBlade Width64°ControlControlCatting Edge MaterialSteel (urethane available)Pole OperationBlade Width0 gol q - optional 20-gal auxiliary tankNazZesLiquid Dicting SystemJog Qal + optional 20-gal auxiliary tankNazZesRating Edge MaterialSteel (urethane available)Spay WadaStendardSpaying VolumeSoug Qal + optional 20-gal auxiliary tankNazZesTriple-beam nozzes (4)Spaying VolumeSteel Materian gaugeSpayu MadaStendardFore ControlMythane Lever adjustment on the control parameter (4)StendardSpaying VolumeSpay MadaStendardMaterianFore ControlMythane Lever adjustment on the control parameter (4)StendardSpaying VolumeStendard Stendard<	Work Light Qty	3	Work Light Output	1440 lumens, IP67-rating
Parige Hydro-Gear ⁴ tandem, variable displacement pistor typ. Hydra-Ulic Fluid 5000000000000000000000000000000000000	Drivetrain		Drivetrain	
Wheel Motors Parker ^{an} TB Series gerotor Controls Controls Enveroid Reverse Hydraulic lever control Throttle Lever on dash Plow Control Hydraulic joystick Liguid System Control Pump switch, or off Control valve, pressure regulating valve Prove Control Hydraulic joystick Liguid System Control Pump switch, or off Control valve, pressure regulating valve Travel Speed Travel Speed Smowplow Snowplow Snowplow Type Straight-blade Control Lift, lower, angle left, angle right Blade Width Gere (urethane available) Plow Operation Down force or float Catting Edge Dimensions X ^a thick, reversible Lifuid Deloing System Lifuid Deloing System Lifuid Capacity 20 gel + optional 20-gel availiary tank Nozzles Trigle-beam nozzles (4) Spraying Volume 5 GPM direct-drive disphragm pump Spray Wand Standard Provide Control Driver Control spare Velticle Velticle Frame Stainless steel Wiring Harness Loomed, weather resistant connectors fores Tres	Туре	Hydrostatic	Hydraulic Oil Filter (Suction)	25-micron replaceable filter
Controls Controls Forward/Reverse Hydraulic lever control Throtte Lever on dash Plow Control Hydraulic lever control Liquid System Control Pump switch, en/off control valve, pressure regulating valve Forward Reverse Liquid System Control Pump switch, en/off control valve, pressure regulating valve Travel Speed Travel Speed Smowplow Travel Speed Straight-blade Beverse Smowplow Simplow Type Straight-blade Trip Mechanism Full moldboard trip Blade Width 48° Control Lift, lower, angle left, angle right Catting Edge Material Steel (urethane available) Plow Operation Down force or float Catting Edge Dimensions Withick, reversible Lift I doet of System Triple-beam nozzles (4) Spraying Volume SGPM direct-drive diaphragm pump Spray Wand Standard Spray Goutrol David games Travel Speed Triple-beam nozzles (4) Spray Goutrol David game gamput Vahicle Standard Flew Control On/off control valve, pressure adjustment on the control panel Standard<	Pump	Hydro-Gear® tandem, variable displacement pis	ton type Hydraulic Fluid	5W-40 synthetic
Forward/Reverse Hydraulic lever control Throttie Lever on dash Plow Control Hydraulic joystick Liquid System Control Pump switch, on/off control valve, pressure regulating valve Forward Spead Travel Spead Travel Spead Somplow Forward Mode 7 mph Reverse Smowplow Type Straight-blade Trip Mechanism Full moldboard trip Blade Width 48° Control Lift, lower, angle left, angle right Cutting Edge Material Steel (urethane available) Plow Operation Down force or float Spraying Volume 20 gal + optional 20-gal auxiliary tank Nozzles Triple-beam nozzles (4) Spraying Volume 0n/off sortrol valve, pressure adjustment on the control panel Straider adjustment on the control panel Triple-beam nozzles (4) Volice Volice Volice Interverse Triple-beam nozzles (4) Triple Spraying Volume Stainless steel Wiring Harness Loomed, weather-resistant connectors Volice Volice Interverse Stainless steel Wiring Harness Loomed, weather-resistant connectors	Wheel Motors	Parker® TB Series gerotor		
Plow Control Hydraulic joystick Liquid System Control Pump switch, on/off control valve, pressure regulating valve Travel Speed Travel Speed Smowplow Smowplow Smowplow Showplow Snowplow Snowplow Snowplow Snowplow Snowplow Full moldboard trip Blade Width 48° Control Ontrol Lift, lower, angle left, angle right Cutting Edge Material Steel (ure thane available) Operation Down force or float Cutting Edge Otionensions M* thick, reversible Liquid Decing System Triple-beam nozzles (4) Speed Control On/off control valve, pressure adjustment on the control valve,	Controls		Controls	
Prove Control Pydradule joystatic Pupersoure regulating value Travel Speed Travel Speed Smowplow Smowplow Snowplow Snowplow Snowplow Full moldboard trip Type Straight-blade Trip Mechanism Full moldboard trip Blade Width 48° Control Lift, lower, angle left, angle right Cutting Edge Material Steel (urethane available) Plow Operation Down force or float Cutting Edge Dimensions V* thick, reversible Ingle Dejeting System Triple-beam nozzles (4) Staight-Charled Sop gl + optional 20-gal auxiliary tank Nozzles Standard Speed Control On/off switch for the pump Spray Wand Standard Speed Control On/off control valve, pressure adjustment on the control panel Standard Control control valve, pressure adjustment on the control panel Vehicle Vehicle Vehicle Insert System Loomed, weather-resistant connectors on the control panel Tires Stainless steel Wiring Harness Loomed, weather-resistant connectors on the control system control system control system Stainless steel Wiring Harness Loomed, weather-resistant connectors on the control syst	Forward/Reverse	Hydraulic lever control	Throttle	Lever on dash
Forward 7 mph Reverse 5 mph Snowplow Snowplow Snowplow Snowplow Snowplow Full moldboard trip Type Straight-blade Trip Mechanism Full moldboard trip Blade Width 48° Control Lift, lower, angle left, angle right Cutting Edge Material Steel (urethane available) Plow Operation Down force or float Cutting Edge Dimensions %" thick, reversible Liquid Decing System Liquid Decing System Liquid Capacity 20 gal + optional 20-gal auxiliary tank Nozzles Triple-beam nozzles (4) Spraying Volume 5 GPM direct-drive diaphragm pump Spray Wand Standard Speed Control On/off switch for the pump Tank One-piece rotomolded Frame Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires Stainless steel Wiring Harness Loomed, weather-resistant connectors Battery 350 CCA at 0" Fahrenheit Fuses 100 A main fuse, individual accessory fuse	Plow Control	Hydraulic joystick	Liquid System Control	
Snowplow Snowplow Type Straight-blade Trip Mechanism Full moldboard trip Blade Width 48° Control Lift, lower, angle left, angle right Cutting Edge Material Steel (urethane available) Plow Operation Down force or float Cutting Edge Dimensions N* thick, reversible Liquid Deicing System Down force or float Liquid Capacity 20 gal + optional 20-gal auxiliary tank Nozzles Triple-beam nozzles (A) Spraying Volume 5 GPM direct-drive diaphragm pump Spray Wand Standard Spread Control On/off switch for the pump Tank One-piece rotomolded Vehicle Vehicle Trips Assime Stand Reset Loomed, weather-resistant connectors Tres It's x8.5'x 10° all terrain Wiring Harness Loomed, weather-resistant connectors Electrical Standers Steel Wiring Marness Loomed, weather-resistant connectors	Travel Speed		Travel Speed	
Type Straight-blade Trip Mechanism Full moldboard trip Blade Width 48° Control Control Lift, lower, angle left, angle right Cutting Edge Material Steel (urethane available) Plow Operation Down force or float Cutting Edge Dimensions V* thick, reversible Liquid Deicing System Liquid Deicing System Triple-beam nozzles (4) Liquid Capacity 20 gal + optional 20-gal auxiliary tank Nozzles Triple-beam nozzles (4) Spraying Volume 5 GPM direct-drive diaphragm pump Spray Wand Standard Spred Control On/off fort the pump Tank One-piece rotomolded Flow Control On/off control valve, pressure adjustment on the control panel Vehicle Loomed, weather-resistant connectors Frame Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires Is' x 8.5' x 10° all terrain Electrical Io0 A main fuse, individual accessory fuse Battery 30 0CA at 0° Fhrenheit Fuses 100 A main fuse, individual accessory fuse	Forward	7 mph	Reverse	5 mph
Blade Width 48° Control Lift, lower, angle left, angle right Cutting Edge Material Steel (urethane available) Plow Operation Down force or float Cutting Edge Dimensions ¼* thick, reversible Liquid Deicing System Liquid Deicing System Liquid Deicing System Edgi Jeinensions Nozzles Triple-beam nozzles (4) Spraying Volume 20 gal + optional 20-gal auxiliary tank Nozzles Standard Standard Spread Control On/off switch for the pump Spray Wand One-piece rotomolded Material Flow Control On/off control valve, pressure adjustment on the control panel Vehicle Vehicle Loomed, weather-resistant connectors Tripes Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires Isiness steel Eletrical Loomed, weather-resistant connectors Blatery Sto CCA at 0' Fahrenheit Fuese 100 A main fuse, individual accessory fuse	Snowplow		Snowplow	
Cutting Edge Material Steel (urethane available) Plow Operation Down force or float Cutting Edge Dimensions ¼" thick, reversible Liquid Deicing System Liquid Deicing System Liquid Deicing System Liquid Capacity 20 gal + optional 20-gal auxiliary tank Nozzles Triple-beam nozzles (4) Spraying Volume 5 GPM direct-drive diaphragm pump Spray Wand Standard Speed Control On/off switch for the pump Tank One-piece rotomolded Flow Control On/off control valve, pressure adjustment on the control panel Vehicle Vehicle Frame Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires 18" x 8.5" x 10" all terrain Electrical Loomed, weather-resistant connectors Battery 350 CCA at 0" Fahrenheit Fuses 100 A main fuse, individual accessory fuse	Туре	Straight-blade	Trip Mechanism	Full moldboard trip
Cutting Edge Dimensions M* thick, reversible Liquid Deicing System Liquid Deicing System Liquid Capacity 20 gal + optional 20-gal auxiliary tank Nozzles Triple-beam nozzles (4) Spraying Volume 5 GPM direct-drive diaphragm pump Spray Wand Standard Speed Control On/off switch for the pump Tank One-piece rotomolded Flow Control On/off control valve, pressure adjustment on the control panel Vehicle Vehicle Loomed, weather-resistant connectors Frame Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires Stainless steel Electrical Electrical Iou Amain fuse, individual accessory fuse Battery Sto CCA at 0° Fahrenheit Fuses 100 A main fuse, individual accessory fuse	Blade Width	48"	Control	Lift, lower, angle left, angle right
Liquid Deicing System Liquid Deicing System Liquid Capacity 20 gal + optional 20-gal auxiliary tank Nozzles Triple-beam nozzles (4) Spraying Volume 5 GPM direct-drive diaphragm pump Spray Wand Standard Speed Control On/off switch for the pump Tank One-piece rotomolded Flow Control On/off control valve, pressure adjustment on the control panel Vehicle Vehicle Frame Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires 18" x 8.5" x 10" all terrain Electrical IoO A main fuse, individual accessory fuse	Cutting Edge Material	Steel (urethane available)	Plow Operation	Down force or float
Liquid Capacity 20 gal + optional 20-gal auxiliary tank Nozzles Triple-beam nozzles (4) Spraying Volume 5 GPM direct-drive diaphragm pump Spray Wand Standard Speed Control 0n/off switch for the pump Tank One-piece rotomolded Flow Control 0n/off control valve, pressure adjustment on the control panel Vehicle Vehicle Frame Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires 18* x 8.5* x 10° all terrain Electrical Io0 A main fuse, individual accessory fuse	Cutting Edge Dimensions	¼" thick, reversible		
Spray ing Volume 5 GPM direct-drive diaphragm pump Spray Wand Standard Speed Control On/off switch for the pump Tank One-piece rotomolded Flow Control On/off control valve, pressure adjustment on the control panel Vehicle Vehicle Frame Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires 18* x 8.5* x 10° all terrain Electrical Battery 350 CCA at 0* Fahrenheit Fuses 100 A main fuse, individual accessory fuses	Liquid Deicing System		Liquid Deicing System	
Speed Control On/off switch for the pump Tank One-piece rotomolded Flow Control On/off control valve, pressure adjustment on the control panel Vehicle Vehicle Yehicle Vehicle Loomed, weather-resistant connectors Frame Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires 18" x 8.5" x 10" all terrain Electrical Battery 350 CCA at 0" Fahrenheit Fuses 100 A main fuse, individual accessory fuses	Liquid Capacity	20 gal + optional 20-gal auxiliary tank	Nozzles	Triple-beam nozzles (4)
Flow Control On/off control valve, pressure adjustment on the control panel Vehicle Vehicle Frame Stainless steel Wiring Harness Iters 18" x 8.5" x 10" all terrain Electrical Electrical Battery 350 CCA at 0" Fahrenheit	Spraying Volume	5 GPM direct-drive diaphragm pump	Spray Wand	Standard
Vehicle Vehicle Frame Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires 18" x 8.5" x 10" all terrain Electrical Electrical Battery 350 CCA at 0" Fahrenheit Fuses 100 A main fuse, individual accessory fuses	Speed Control	On/off switch for the pump	Tank	One-piece rotomolded
Frame Stainless steel Wiring Harness Loomed, weather-resistant connectors Tires 18" x 8.5" x 10" all terrain Electrical Electrical Electrical 100 A main fuse, individual accessory fuses	Flow Control		3	
Tires 18" x 8.5" x 10" all terrain Electrical Electrical Battery 350 CCA at 0" Fahrenheit Fuses 100 A main fuse, individual accessory fuses	Vehicle		Vehicle	
Electrical Electrical Battery 350 CCA at 0° Fahrenheit Fuses 100 A main fuse, individual accessory fuses	Frame	Stainless steel	Wiring Harness	Loomed, weather-resistant connectors
Battery 350 CCA at 0° Fahrenheit Fuses 100 A main fuse, individual accessory fuses	Tires	18" x 8.5" x 10" all terrain		
	Electrical		Electrical	
Voltage 12v DC Charging System 17 A	Battery	350 CCA at 0° Fahrenheit	Fuses	100 A main fuse, individual accessory fuses
	Voltage	12v DC	Charging System	17 A

TWO-YEAR LIMITED WARRANTY All BOSS snowplows and equipment are guaranteed to be free from defects in material and workmanship for two full years from the date of purchase. Stop by any authorized BOSS Dealer to receive complete details on our two-year parts and labor warranty. Please visit bossplow.com for more details.

Vehicles intended to be equipped with a spreader and/or snowplow must comply with the vehicle manufacturers' specifications for equipment application. BOSS Products reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein. BOSS Products may be protected by one or more patents; please see bossplow.com for more details.

To comply with federal regulations and to ensure a safe vehicle, do not exceed the front gross axle weight rating (FGAWR), rear gross axle weight rating (RGAWR), gross vehicle weight rating (GVWR) or maximum vehicle payload ratings at any time. Combinations of equipment such as snowplows and spreaders, density of material being spread and the number of vehicle occupants should be taken into consideration. Ensuring these limitations are not exceeded may require weighing the vehicle and adding ballast as necessary. For receiver hitch-mounted products, do not exceed hitch rating at any time. Completed vehicle must not exceed front GAWR or GVWR.





All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.

LEGAL STATEMENT



BOSSPLOW.COM

See how BOSS continues to BACK YOU UP. Get more info, watch videos, find a dealer or chat live.

Call 800-286-4155 Email sales@bossplow.com





Ask your dealer or visit bossplow.com to explore the complete lineup of BOSS products, including Truck Equipment, Compact Vehicle Equipment, Heavy Equipment, Ice Control Equipment, Snowrator[®] and Accessories. **Ask your local dealer about financing options!**



With quality and reliability at the forefront, BOSS Genuine Parts are designed, built and tested to fit your BOSS product.



Exclusive to BOSS Owners, joining this community gives you a profile page, a free gift and access to special offers and information on BOSS products and services.



SnowCare for Troops is a nationwide outreach program that performs free snow removal for active military families.





BOSS PRODUCTS 2010 THE BOSS WAY P.O. BOX 787 IRON MOUNTAIN. MI 49801-0787

Patents: www.ttcopats.com ©2019 BOSS PRODUCTS. ALL RIGHTS RESERVED. PRINTED IN U.S.A. FORM #SLS-SNR02019

Honda is a registered trademark of Honda Motor Co., Ltd. Hydro-Gear is a registered trademark of Hydro-Gear Limited Partnership AF Holding Company, a Delaware Corporation, and Danfoss Power Solutions (US) Company, a Delaware Corporation. Parker is a registered trademark of Parker Intangibles LLC. The "i" fogo is a registered trademark/service mark of Facebook, Inc. The Twitter logo is a registered trademark/service mark of Twitter, Inc. The YouTube logo is a registered trademark/service mark of Google Inc. The "in" logo is a registered service mark of LinkedIn Corporation. The Instagram logo is a registered trademark/service mark of Instagram, LLC. The Blogger logo is a registered service mark of Google Inc. The Omnia Partners logo is a service mark of Omnia Partners, Inc. The Sourcewell logo is a service mark of National Joint Powers Alliance. All other trademarks belong to BOSS Snowplow.