

## STANDARD-DUTY STRAIGHT-BLADE

ADVANTAGE INTERNATIONAL REGISTRAR ISO 9001:2008
Registered

APPLICATIONS: 4X4s, 1/2-TON TO 3/4-TON TRUCKS AND SUVS





| SPECIFICATIONS                  | 7'6" Standard-Duty<br>(Steel)           |
|---------------------------------|---|
| Blade Width (Straight)          | 90" (229 cm)                            |
| Plowing Width @ 30° Angle       | 78" (198 cm)                            |
| Blade Height                    | 27-1/2" (70 cm)                         |
| Blade Thickness                 | 14-ga steel                             |
| Cutting Edge (High Performance) | 3/8" x 6" (1 cm x 15 cm)                |
| Reinforcement Ribs              | 7 vertical                              |
| Plow Shoes                      | Cast Iron                               |
| Trip Springs                    | 3                                       |
| Angle Cylinders                 | 1-1/2" x 10" (4 cm x 25 cm)             |
| Lift Cylinder                   | 2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm) |
| Shock Absorber                  | 1                                       |
| Attachment System               | SmartHitch 2                            |
| Plow Weight*                    | 597 lb (271 kg)                         |
| Plow Lights                     | SL3 L.E.D. with Ice Shield Technology   |

<sup>\*</sup>Plow weight does not include vehicle mount weight. Vehicle mount weight range: 75-105 lb (34-48 kg).