



TAILGATE SPREADERS

APPLICATIONS: 4X4s, SUVs AND 1/2-TON TO 1-TON TRUCKS



SPECIFICATIONS	TGS 300*	TGS 600*	TGS 800**	TGS 1100*
Hopper Design	Low-Profile	Low-Profile	Low-Profile	Low-Profile
Hopper Construction	Polyethylene	Polyethylene	Polyethylene	Polyethylene
Hopper Capacity	3 cu ft/200 lbs (.08 cu m/91 kg)	6 cu ft/400 lbs (.2 cu m/181 kg)	8 cu ft/780 lbs (.2 cu m/354 kg)	11 cu ft/800 lbs (.3 cu m/363 kg)
Hopper Dimensions	21-7/8"H x 29"W x 15"D (53cm x 74cm x 38cm)	25-3/4"H x 38"W x 21"D (65cm x 97cm x 53cm)	48"H x 36"W x 21"D (122cm x 91cm x 53cm)	34"H x 44"W x 24"D (86cm x 112cm x 61cm)
Spreader Weight	70 lb (31 kg) plus mount	101 lb (46 kg) plus mount	220 lb (160 kg) plus mount	152 lb (69 kg) plus mount
Hopper Cover	Solid poly	Solid poly	Solid poly	Solid poly
Feed Mechanism	Internal auger w/material saving brush and adjustable drop-feed gate	Internal auger w/cable-link agitator and adjustable feed gate	Feed paddle	Internal auger w/cable-link agitator and adjustable feed gate
Vibrator Kit	Not recommended	Optional	Optional	Optional
Top Screen with Bag Opener	Not available	Standard	Standard	Standard
Motor	High-torque/12-volt DC	High-torque/12-volt DC	High-torque/12-volt DC	High-torque/12-volt DC
Spinner	12" (31 cm) poly	12" (31 cm) poly	12" (31 cm) poly	12" (31 cm) poly
Spread Width	4-30 feet (1-9 meters)	4-30 feet (1-9 meters)	4-20 feet (1-6 meters)	4-30 feet (1-9 meters)
Material Deflector	Adjustable poly deflector	Adjustable poly deflector	Adjustable poly deflector	Adjustable poly deflector
Receiver Hitch	1-1/4 class 22", Class 2 and up	Class 3 or 4	Class 4	Class 4
Control	Variable speed control with blast feature and overload protection	Variable speed control with blast feature and overload protection	Variable speed control with blast feature and overload protection	Variable speed control with blast feature and overload protection
Vehicle Applications	SUV, light truck and up	3/4 and 1-ton trucks	3/4 and 1-ton trucks	3/4 and 1-ton trucks

*Designed to spread dry, free-flowing material (i.e., salt, deicers, etc.). **Designed to spread sand, salt or a combination of both.