



TRIP-EDGE SKID-STEER STRAIGHT-BLADE

APPLICATIONS: SKID STEERS



SPECIFICATIONS	7'6" Trip-Edge Skid Steer (Steel Stainless Steel)	8' Trip-Edge Skid Steer (Steel Stainless Steel)	9' Trip-Edge Skid Steer (Steel Stainless Steel)
Blade Width (Straight)	90" (229 cm)	96" (244 cm)	108" (274 cm)
Plowing Width @ 30° Angle	78" (198 cm)	83" (211 cm)	93-1/2" (238 cm)
Blade Height	31" (79 cm)	31" (79 cm)	31" (79 cm)
Blade Thickness	11-ga Steel 14-ga 304 Stainless	11-ga Steel 14-ga 304 Stainless	11-ga Steel 14-ga 304 Stainless
Base Angle	1/2" x 3-1/2" x 3-1/2" (1.3 cm x 9 cm x 9 cm)	1/2" x 3-1/2" x 3-1/2" (1.3 cm x 9 cm x 9 cm)	1/2" x 3-1/2" x 3-1/2" (1.3 cm x 9 cm x 9 cm)
Cutting Edge	1/2" x 6" (1.3 cm x 15 cm)	1/2" x 6" (1.3 cm x 15 cm)	1/2" x 6" (1.3 cm x 15 cm)
Reinforcement Ribs	6 vertical, 2 diagonal	6 vertical, 2 diagonal	6 vertical, 2 diagonal
Plow Shoes	Cast Iron	Cast Iron	Cast Iron
Trip Springs	4	4	4
Trip Pivot Pin Diameter	1 (3 cm)	1 (3 cm)	1 (3 cm)
Trip Spring Type	3/8" (1 cm) hooked extension spring	3/8" (1 cm) hooked extension spring	3/8" (1 cm) hooked extension spring
Trip-Edge Adjustable	Standard	Standard	Standard
Angle Cylinders	1-1/2" x 10" (4 cm x 25 cm)	1-1/2" x 10" (4 cm x 25 cm)	1-1/2" x 10" (4 cm x 25 cm)
Lift Cylinder	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)
Attachment System	Universal tool carrier	Universal tool carrier	Universal tool carrier
Plow Weight*	812 lb (368 kg) 862 lb (391 kg)	829 lb (376 kg) 881 lb (400 kg)	882 lb (400 kg) 939 lb (426 kg)
Plow Lights	N/A	N/A	N/A

*Plow weight does not include vehicle mount weight. Vehicle mount weight range: 75-105 lb (34-48 kg).

BOSS Products, a division of The Toro Company, reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

©2016 BOSS Products/The Toro Company. All rights reserved. Patents: www.ttcopats.com