



S N O W P L O W

# VBX SPREADERS

APPLICATIONS: 1/2 TON TRUCKS & 3/4 TO 1-TON TRUCKS



SPECIFICATIONS	VBX6500   VBX8000   VBX9000 Auger Spreader	VBX6500   VBX8000   VBX9000 Pintle Chain Spreader
Hopper Capacity	1.5 Yards   2 Yards   3 Yards	1.5 Yards   2 Yards   3 Yards
Hopper Length	78" (198 cm)   96" (244 cm)   107" (272 cm)	78" (198 cm)   96" (244 cm)   107" (272 cm)
Hopper Overall Length	93-1/2" (238 cm)   115" (292 cm)   122" (309 cm)	93-1/2" (238 cm)   115" (292 cm)   122" (309 cm)
Hopper Height	38-3/16" (97 cm)   38" (97 cm)   49" (125 cm)	38-3/16" (97 cm)   38" (97 cm)   49" (125 cm)
Hopper Width	48 -1/4" (123 cm)   48 -1/4" (123 cm)   48" (122 cm)	48 -1/4" (123 cm)   48 -1/4" (123 cm)   48" (122 cm)
Unit Weight (Empty)	550 lb (249 kg)   600 lb (272 kg)   710 lb (322 kg)	600 lb (272 kg)   650 lb (295 kg)   760 lb (345 kg)
Hopper Construction	3/16" (0.5 cm) Double Wall Polyethylene Hopper	3/16" (0.5 cm) Double Wall Polyethylene Hopper
Spreading Width	2 ft-40 ft (0.6 m - 12 m) Dry free-flowing material	2 ft-40 ft (0.6 m - 12 m) Dry free-flowing material
Max Feed Rate	2.3 cu ft (0.06 cu m) per minute	4 cu ft (0.11 cu m) per minute
Lighting	Dual 55 watt halogen variable output work lights (Standard)	Dual 55 watt halogen variable output work lights (Standard)
Cover	VCP Tarp with integral tie-downs	VCP Tarp with integral tie-downs
Top Screen	Standard	Standard
Gearbox	Planetary Gearbox	Planetary Gearbox
Motor	1/2 HP SS Feed Motor   3/4 HP SS Feed Motor	1/2 HP SS Feed Motor   3/4 HP SS Feed Motor
Trough	304 Stainless Steel	304 Stainless Steel
Cab Controller	LCD Display Controller	LCD Display Controller
Dual Variable Speed Control	Standard	Standard
Dual Variable Speed Vibrators	Standard	Optional
Inverted V Baffle	Standard	Optional
Selectable Drive	6" (15 cm) OD x 9" (23 cm) pitch full length auger	14" (36 cm) wide pintle chain
LED CHMSL	Standard	Standard
Adjustable Deflector	Standard	Standard
Spinner Assembly	Easily removable and height adjustable	Easily removable and height adjustable
Hopper Tie-Down Kit	Standard	Standard
Spinner	14.5" (36.8 cm) Diameter Urethane Spinner	14.5" (36.8 cm) Diameter Urethane Spinner
Spinner Gearmotor	1/8 HP Spinner Gearmotor (Located above spinner)	1/8 HP Spinner Gearmotor (Located above spinner)
Minimum Bed Length	5'6" (168 cm)   6'6" (198 cm)   8'0" (244 cm)	5'6" (168 cm)   6'6" (198 cm)   8'0" (244 cm)
Minimum GVWR	9,000 lb (4,082 kg)   10,000 lb (4,535 kg)   15,000 lb (6,804 kg)	9,000 lb (4,082 kg)   10,000 lb (4,535 kg)   15,000 lb (6,804 kg)

BOSS Products, a division of The Toro Company, reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

©2016 BOSS Products/The Toro Company. All rights reserved. Patents: [www.ttcopats.com](http://www.ttcopats.com)