



POWER-V XT

APPLICATIONS: 4X4s, 3/4 TO 1-TON TRUCKS AND SUVs



SPECIFICATIONS	7'6" Power-V XT (Steel)	8'2" Power-V XT (Steel Poly)	9'2" Power-V XT (Steel Poly)
Blade Width (Straight)	90" (229 cm)	98" (249 cm)	110" (279 cm)
Blade Width (Vee)	81" (206 cm)	88" (224 cm)	99" (252 cm)
Blade Width (Scoop)	74" (188 cm)	81" (206 cm)	92" (234 cm)
Plowing Width @ 30° Angle	77" (196 cm)	85" (216 cm)	95" (241 cm)
Blade Height	36" (91 cm) at end, 30" (76 cm) at center	37" (94 cm) at end, 30" (76 cm) at center	38" (96.52 cm) at end, 30" (76 cm) at center
Blade Thickness	14-ga steel	11-ga steel 3/8" (1 cm) Poly	11-ga steel 3/8" (1 cm) Poly
Cutting Edge (High Performance)	1/2" x 6" (1.3 cm x 15 cm)	1/2" x 6" (1.3 cm x 15 cm)	1/2" x 6" (1.3 cm x 15 cm)
Reinforcement Ribs	6 vertical, 2 diagonal	6 vertical, 2 diagonal	8 vertical, 2 diagonal
Plow Shoes	Optional	Optional	Optional
Trip Springs	4	4	4
SmartLock Cylinders	1-3/4" x 10" (5 cm x 25 cm)	1-3/4" x 10" (5 cm x 25 cm)	1-3/4" x 10" (5 cm x 25 cm)
Lift Cylinder	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)
Attachment System	SmartHitch 2	SmartHitch 2	SmartHitch 2
Plow Weight*	713 lb (323 kg)	785 lb (356 kg) 795 lb (361 kg)	842 lb (382 kg) 852 lb (387 kg)
Plow Lights	SL3 L.E.D. with Ice Shield Technology	SL3 L.E.D. with Ice Shield Technology	SL3 L.E.D. with Ice Shield Technology

*Plow weight does not include vehicle mount weight. Vehicle mount weight range: 75-105 lb (34-48 kg).

**Includes 1-ton trucks with dual rear wheels.