


IRRITROL SYSTEMS 5825 JASMINE ST. RIVERSIDE, CA 92504 TOLL FREE: 1-800-634-8873 PHONE: (951) 785-3454 www.irritrol.com



SECTION

LEGEND:

- IRRITROL 2400S ELECTRIC CONTROL VALVE.
- ⑦ FINISH GRADE.
- 3 VALVE BOX (HEIGHT ABOVE GRADE AS REQUIRED).
- PVC SCHEDULE 40 SLIP BRUSHING (IF REQUIRED).
- 5 WATERPROOF WIRE CONNECTORS.
- PVC LATERAL LINE-ANGLE TO PROPER DEPTH WITH 450 ELLS.
- (7) COMMON RED BRICK (4 REQUIRED).
- 8 PEA GRAVEL 12" DEEP.
- 9 PVC SCHEDULE 80 PIPE.
- DVC SCHEDULE 40 S ELL.
- COMMON AND CONTROL WIRES TO CONTROLLER LOCATION.
- PRESSURE MAIN LINE PIPING WITH MAIN LINE FITTING (DEPTH AS REQUIRED).

NOTES:

743-042

- 1. REFER TO PRODUCT LITERATURE FOR ADDITIONAL INSTALLATION AND ADJUSTMENT INFORMATION.
- 2. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 3. DO NOT SCALE DRAWING.
- 4. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 5. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- 6. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 743-042.

2400 SERIES: 2400S GLOBE SLIP CONNECTION VALVE