

ᠿ

2

ന

TORO-IRRIGATION DIVISION 5825 JASMINE STREET RIVERSIDE, CA 92504 TOLL FREE: 1-877-345-8676 FAX: (951) 359-1870 crc@toro.com www.toro.com



(4)

① TURBO-SC[™] PLUS PRESSURE COMPENSATING EMITTER TORO MODEL T-DPJ0X-XXX (X-XXX DENOTES FLOW RATE & OPTIONAL INLET CHECK SCREEN)

② 1/4" TUBING LOCATOR STAKE TORO MODEL: T-IPS0104.

③ 1/4" BLUE STRIPE DRIP HOSE TORO MODEL: T-EHW437 (LENGTH AS REQUIRED)

④ 9-OUTLET DRIP MANIFOLD TORO MODEL: T-PR25-9 PRESSURE REGULATING (25 PSI)

(5) TOP OF MULCH AND/OR DECORATIVE BARK.

6 FINISH GRADE.

⑦ PVC SCH 80 1/2" NIPPLE (LENGTH AS REQUIRED).

8 PVC SCH 40 TEE OR ELL.

PVC LATERAL PIPE.

(10) 6" ROUND VALVE BOX.

(11) 3" MINIMUM DEPTH OF 3/4" WASHED GRAVEL.

NOTES:

1. LOCATE STAPLES ALONG TUBING AT 4'-6' ON CENTER AND AT ALL FITTINGS (TEES, ELLS, ETC.)

5-5-0-5-0-5-0-5-

(A) COIL ADDITIONAL 6" OF 1/4" TUBING IN VALVE BOX

TO FACILITATE MAINTENANCE.

B CAP OFF ALL UNUSED CONNECTORS.

SECTION/ELEVATION

- 2. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 3. DO NOT SCALE DRAWING.

NOTES:

- 4. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 5. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.

LANDSCAPE DRIP

TURBO-SC[™] PLUS PRESSURE COMPENSATING EMITTER - 9-OUTLET DRIP MANIFOLD

REVISION DATE JAN. 2023