TORO_®

DRIP IRRIGATION SYSTEMS FOR GREENHOUSES

WHITE SPIDER ASSEMBLIES

Toro[®] White Spider Assemblies represent the highest quality drip irrigation for high value crops.

- The tubing resins are selected to provide high durability, high reflection, flexibility, and ease of cleaning.
- The emitters and fittings are built to last for many crop cycles, retaining their very high level of accuracy.











WHITE SPIDER ASSEMBLIES

DRIPPER STAKE ASSEMBLY DWST1-24-02AL - - - - 0.5 gph 24" DWST1-30-02AL - - - - 0.5 gph 30" DWST1-24-03AL - - - 0.8 gph 24" DWST1-30-03AL - - - 0.8 gph 30"



1-WAY SPIDER

DWST1-18 - - - - 18" DWST1-24 - - - - 24" DWST1-30 - - - 30" * use with all flows NGE emitters

2-WAY SPIDER"

DWST2Q-18 - - - 2 Way 18" DWST2Q-24 - - - 2 Way 24" DWST2Q-30 - - - 2 Way 30" DWST2Q-36 - - - 2 Way 36" ** use with 0.5, 0.8, or 1 gph NGE emitters

4-WAY SPIDER***

DWST4Q-18 - - - - 4 way 18" DWST4Q-24 - - - - 4 way 24" DWST4Q-30 - - - - 4 way 30" DWST4Q-36 - - - - 4 way 36" DWST4Q-1830 - - - 4 way 18" & 30" DWST4Q-2436 - - - 4 way 24" & 36" **** use with 1 or 2 gph NGE emitters








LOOKS CLEAN

STAYS CLEAN



BRILLIANT WHITE:

STAY-CLEAN SHINE:

• Easy to clean & keep clean

• High gloss finish

- High visibility
- Highly reflective
- Completely opaque

RESISTS STRETCHING & KINKING:

• Tough exterior layer adds durability, but retains ultra-flexibility

Both white PE & diamond white micro tube have a bright white layer over an opaque black core



-	-		-	-	
-	_	•	-	-	
-			_		



White PE 20mm

White Micro Tubing 5/3mm

WHITE BLUE STRIPE[®] HIGH QUALITY POLYETHYLENE PIPE:


• Many sizes available pre-punch





COMPONENTS

STAKES




USED IN SINGLE STAKE ASSEMBLIES (A) Barbed Angle Stake - - - - - IPST0301BQ (B) Clip Angle Stake - - - - - IPS03010SW USED IN MULTI STAKE ASSEMBLIES (C) Straight Turbo Stake - - - - IPST0301

(D) Angle Turbo Stake - - - - - IPST0301Q



FITTINGS



(A) Elbow Dripper Adapter - - - - - FBS1E
(B) Tee Dripper Adapter - - - - - FBS2
(C) 4-Way Cross Dripper Adapter - - - FBST4-X

TUBING



WHITE BLUE STRIPE® POLY TUBING 16mm (.615" ID - .705" OD) 500 Roll - - - WHD1645-50 20mm (.805" ID - .919" OD) 500 Roll - - - WHD2057-50

* Additional diameters and wall thicknesses available. Please see our website, toro.com/agriculture or call customer service 1 (877) 373-0087 or +1 (619) 596-2495

MICRO TUBING



DIAMOND WHITE MICRO TUBE (3mm ID - 5mm 0D) 1,000' Reel - - - - - - WHDT0335-100 12" Precut Tube - - - - SFHWT0335-12 18" Precut Tube - - - - SFHWT0335-18 24" Precut Tube - - - - SFHWT0335-24 30" Precut Tube - - - - SFHWT0335-30 36" Precut Tube - - - - SFHWT0335-36

NGE[®] EMITTERS

- Pressure compensating drippers with self flushing mechanism deliver a precise flow to each plant, season after season
- Check valve feature prevents line drainage, enabling efficient pulse irrigation
- Highly resistant to chemicals and low pH: polyethylene body and silicone diaphragm work with a wide range of fertilizers and line cleaners
- Sturdy construction resists physical damage

FLOWS AVAILABLE									
GPH	0.5	0.8	1.0	2.0					
LPH	2	3	4	8					
	Light Blue	Light Green	Grey	Light Red					

TECH SPECS:

- Opening pressure: 10-12 psi;
- Closing pressure: 3.5-5 psi
- Recommended filtration: 140 mesh



BARBED OUTLET

Connects directly to diamond white micro tu	be
DPCT02-3-AL-BLUE 0.5 gph (2 lp	h)
DPCT03-3-AL-GRN 0.8 gph (3 lp	h)
DPCT04-3-AL-BLK 1.1 gph (4 lp	h)



MALE ADAPTER OUTLET

Connects directly to white spider assemblies DPCT02-MA-AL-BLUE - - - - 0.5 gph (2 lph) DPCT03-MA-AL-GRN - - - - 0.8 gph (3 lph) DPCT04-MA-AL-BLK - - - - 1.1 gph (4 lph) DPCT08-MA-AL-RED - - - - 2.1 gph (8 lph)



AUTOMATION

VALVES & CONTROLLERS



TORO AG SERIES 100 VALVES

- Nylon construction for maximum strength and durability
- Can be mounted either straight or angle
- Adjustable flow control
- Manual bleed to open

A-100P1 - - - 1" FPT Valve 24v AC A-100P1.5 - - 1.5" FPT Valve 24v AC A-100P2 - - - 2" FPT Valve 24v AC A-100P3 - - - 3" FPT Valve 24v AC

Operating Pressure: 20-220 psi





For full technical details, see: www.Toro.com/evolution-ag or scan QR code

EVOLUTION[®] AG CONTROLLER

- Seconds, minutes, hours Program what you want
- Watering, misting, pulsing Water how you want
- Fertilizer injection The easy way
- Easy to program
 Mobile ready
- EVO-4AG - 4 Station Controller
- A-EMOD - - 4 Station Expansion Module
- A-EMOD-12 - 12 Station Expansion Module
- A-EVO-SC - Smart Connect Plug-In Receiver
- A-SMRT-T - Wireless Internet Gateway
- A-EVO-HH - Wireless Handheld Controller
- A-EVO-AR - Wireless Auxiliary Relay 110v

TORO AG PVC VALVES

- Economical, reliable operation, easy to service
- 1.5" & 2" can be mounted either straight, or angle

A-2400TF - - - 1" FPT PVC valve threaded bonnet 24v AC A-2400S - - - 1" Slip PVC valve threaded bonnet 24v ACA-205TF - - 1" FPT PVC valve w/ flow control 24v AC A-216B - - - - 1.5" FPT PVC valve w/ flow control 24v AC

A-217B - - - 2" FPT PVC valve w/ flow control 24v AC

Operating Pressure: 1": 10 to 150 psi; 1.5" & 2": 20 to 150 psi



TORO AG 1" PRESSURE REGULATOR

- Handles very wide flow range: 0.1 gpm - 35 gpm
- Highly accurate, protects system, while optimizing hydraulic performance

A-T-PMR30 - - - 30 psi output A-T-PMR40 - - - 40 psi output 120 psi max pressure





WHEN WE SAY COUNT ON IT, WE MEAN IT

With an expanding population, growers around the world are looking to technologies that help increase productivity of existing land and maximize precious water resources. Toro's drip irrigation solutions help growers of permanent, field and row crops around the world realize substantial benefits in yield, quality, and water savings from the precise application of water and nutrients.

Visit **toro.com** or call **(877) 373-0087** for more information or to find your local Toro dealer. Visit **driptips.toro.com** to learn more about drip irrigation and how it can help your farm.



© 2018 The Toro Company. All Rights Reserved. Printed in the USA.

Toro Ag 1588 N. Marshall Avenue El Cajon, CA 92020-1523, USA Tel: + 1 (877) 373-0087 or + 1 (619) 596-2495 Fax: +1 (800) 892-1822 or +1 (619) 258-9973 toro.com | driptips.toro.com

ALT263 01/18

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your dealer for details on all our warranties.