

The Toro logo is displayed in white, bold, sans-serif capital letters on a red rectangular background with rounded corners.

APPLICATION

Toro's pressure compensating Micro Sprinkler PC is specifically designed for orchards, vineyards, and nursery applications where undulating terrain and long lateral lengths are challenging. Its unique pressure compensating design provides uniform flows and diameters over a wide range of operating pressures. The Micro Sprinkler PC now has a wider diameter of throw than Toro's previous micro sprinklers.



Micro Sprinkler PC

FEATURES & BENEFITS

- Wide diameter of throw from 16 feet to 31 feet, depending on sprinkler
- Pressure compensating sprinkler provides uniform flow over a wide range of operating pressures: 20 psi – 60 psi
- Low angle of throw for maximizing under foliage irrigation
- Easy identification in eight color coded flow rates ranging from 9 GPH – 40 GPH
- Snap-fit bearing provides easy field inspection and maintenance
- Improved distribution characteristics with large droplet size, less susceptible to wind
- Anti-insect/dust proof spinner retracts to protect nozzle when not in operation
- Optional break off deflector tab allows the sprinkler to be placed near a newly planted tree to concentrate water where the roots are developing
- Fully assembled models available with pre installed tube and stake

SPECIFICATIONS

INLET: 3/8" MPT (10 mm MBSP/ NPT)

MATERIALS:

Frame, bearing, and nozzle: Acetal.
Spinner: Nylon.
Diaphragm: Rubber.

Assemblies:

Use 4 mm tube and stake (CPS1004)
Recommended Operating Pressure: 20 psi–60 psi

Micro Sprinkler PC



The latest generation Micro Sprinkler PC pressure compensating sprinkler is suitable for various applications, including under tree irrigation, overhead irrigation, vegetables, vineyard, orchards and greenhouse applications. This innovative micro sprinkler can also be used for overhead frost protection.

The diverse Micro Sprinkler PC range delivers a spray pattern that suits a wide range of crops to meet growers' needs.

PERFORMANCE CHART

Model	With Deflector Tab No.	Nozzle Color	Orifice Dia. Inch (mm)	Pressure		Flow Rate		Diameter		Radius with Deflector Tab		Stream Height	
				Psi	Bar	gph	lph	Feet	Meters	Feet	Meters	Feet	Meters
MS7PC9	MS7PC9D	Black	.036 (0.91)	20	1.38	9.0	34	15.7	4.8	0.98	0.3	1.3	0.39
				30	2.07	9.8	37	19.7	6.0				
				40	2.76	9.2	35	19.0	5.8				
				50	3.45	9.5	36	18.4	5.6				
				60	4.14	9.8	37	19.7	6.0				
MS7PC12	MS7PC12D	Lt-Blue	0.042 (1.07)	20	1.38	11.6	44	18.4	5.6	1.64	0.5	1.2	0.36
				30	2.07	13.2	50	23.0	7.0				
				40	2.76	12.2	46	21.0	6.4				
				50	3.45	12.4	47	21.7	6.6				
				60	4.14	12.7	48	22.3	6.8				
MS7PC15	MS7PC15D	White	0.046 (1.17)	20	1.38	13.7	52	18.4	5.6	2.30	0.7	1.4	0.43
				30	2.07	15.3	58	22.3	6.8				
				40	2.76	14.8	56	21.0	6.4				
				50	3.45	15.6	59	23.0	7.0				
				60	4.14	15.9	60	23.6	7.2				
MS7PC20	MS7PC20D	Maroon	0.053 (1.34)	20	1.38	18.8	71	22.3	6.8	2.30	0.7	1.1	0.33
				30	2.07	20.3	77	25.6	7.8				
				40	2.76	19.3	73	23.6	7.2				
				50	3.45	19.6	74	24.3	7.4				
				60	4.14	20.1	76	24.3	7.4				
MS7PC26	MS7PC26D	Green	0.060 (1.52)	20	1.38	24.6	93	24.9	7.6	2.30	0.7	1.6	0.50
				30	2.07	26.2	99	27.6	8.4				
				40	2.76	24.8	94	25.6	7.8				
				50	3.45	25.6	97	26.9	8.2				
				60	4.14	26.7	101	28.2	8.6				
MS7PC31	MS7PC31D	Purple	0.071 (1.81)	20	1.38	30.6	116	26.9	8.2	2.30	0.7	1.2	0.35
				30	2.07	30.9	117	27.6	8.4				
				40	2.76	29.3	111	23.6	7.2				
				50	3.45	30.4	115	24.9	7.6				
				60	4.14	31.4	119	24.9	7.6				
MS7PC35	MS7PC35D	Blue	0.071 (1.81)	20	1.38	34.3	130	28.2	8.6	2.62	0.8	1.6	0.50
				30	2.07	36.2	137	30.2	9.2				
				40	2.76	33.8	128	26.9	8.2				
				50	3.45	35.1	133	28.9	8.8				
				60	4.14	36.5	138	30.8	9.4				
MS7PC40	MS7PC40D	Grey	0.075 (1.90)	20	1.38	38.6	146	26.2	8.0	3.28	1.0	1.3	0.39
				30	2.07	40.7	154	28.2	8.6				
				40	2.76	38.0	144	26.2	8.0				
				50	3.45	39.1	148	26.9	8.2				
				60	4.14	40.7	154	28.2	8.6				

©2017 The Toro Company

Micro-Irrigation Business

1588 N. Marshall Avenue,
El Cajon, CA 92020-1523, USA

Tel: +1 (800) 333-8125 or +1 (619) 562-2950

Fax: +1 (800) 892-1822 or +1 (619) 258-9973

toro.com

ALT209 8/17

TORO.

Count on it.