

**TORO**

**Count on it.**

**GROUNDMASTER® 4000-D/4100-D**

WIDE AREA ROTARY MOWERS



**TAKE YOUR PRODUCTIVITY  
TO NEW LEVELS.**



## COMMON FEATURES OF GROUNDMASTER® 4000-D /4100-D SERIES MOWERS

**4000-D & 4100-D series mowers deliver power, durability & excellent quality of cut.**

These machines are the workhorses of turf maintenance. With powerful engines, nimble operation, variability of cutting width, and four-wheel drive, there are no other mowers in its class that can provide the productivity and maintain the diversity of landscapes as efficiently while leaving a consistent, manicured appearance.



### ALL-SEASON CAB

All-season comfort with heat and air conditioning. (4010-D and 4110-D).

### EASY MAINTENANCE

Quick and easy access to all major service areas.



### AIR-RIDE SUSPENSION SEAT

All-day operator comfort for greater productivity.



### SMART COOL®

Automatically reverses cooling fan to blow off radiator screen chaff to help prevent overheating.



### SMART POWER®

Automatically adjusts ground speed when encountering heavy cutting conditions, providing a consistent quality of cut.



### DURABILITY

Heavy-duty, 7-gauge steel decks with bullnose bumpers and the industry's toughest spindle assembly for extended product life.



### VARIABLE CUTTING WIDTHS

Versatility in both wide area and trim mowing applications, depending on decks operating. And the ability to achieve a "zero" uncut circle, leaving no uncut grass in turns.

### HybridDrive™ CUTTING DECKS

Works in conjunction with the SmartPower® system, providing optimal power to the cutting blades.



### UNMATCHED POWER

Yanmar® 55 hp (41 kW) turbo-charged diesel engines provide ample power to mow in the toughest conditions.



## GROUNDMASTER® 4000-D/4010-D

**A highly productive deck design allowing wide area mowing or precise trimming.**

The three-deck design of the Groundmaster 4000-D and 4010-D provides superior ground-following ability for excellent quality of cut results. Additionally, the incredible productivity that comes with varying the cutting width, from 11' to 8' to 5' on-the-fly, along with nimble, zero uncut circle capability, allows maintaining diverse landscapes from tight trim areas to wide open fields all with one machine.



Groundmaster 4000-D



Groundmaster 4010-D



» **PRODUCTIVITY  
IN UNEVEN TERRAIN**

- The parallel hydraulic system gives superior traction, making it much easier to trim around an object on a hillside without scuffing the turf, in forward or reverse.



» **PRODUCTIVITY  
AT EVERY TURN**

- Incredible maneuverability that accomplishes a "zero" uncut circle, allowing the operator to cut in a back and forth pattern with no uncut grass.

# GROUNDMASTER® 4100-D/4110-D

The Groundmaster 4100-D & 4110-D series feature an all out-front deck design.

The 10.3' (3.15 m) continuous deck gives operators immense visibility and control over the mowing process.

Not only is the 4100 series good for wide-open areas, it also allows for excellent trimming under bushes and trees while keeping the operator's eyes looking forward.



Groundmaster 4110-D



Groundmaster 4100-D has a 10.3' (3.15 m) overall width of cut. Center deck section is 4.5' (1.37 m) with two 3.08' (.9 m) wings and a 7.4' (2.26 m) width of cut with one wing up.

## ATTACHMENTS/ACCESSORIES WORK WITH 4000-D, 4010-D, 4100-D & 4110-D MODELS



ROTARY BROOM



SNOWTHROWER



SUNSHADE

## SPECIFICATIONS

### GROUNDMASTER® 4000-D/4100-D SERIES

MODEL	GROUNDMASTER 4000-D	GROUNDMASTER 4010-D	GROUNDMASTER 4100-D	GROUNDMASTER 4110-D
<b>ENGINE</b>	Yanmar® 4-cylinder, liquid-cooled, turbo-charged diesel. 127 cu. in. (2.1 liter) displacement. Engine rated at 55 hp (41 kW) net and 125 ft.-lbs. (169 Nm) torque at 2,000 rpm. 8 quart (7.6 liter) oil capacity. EPA Tier IV and Stage V Compliant.			
<b>RADIATOR</b>	Rear-mount, cross-flow, 7-row, 6.3 fins per inch, 9 quart (8.5 liter) capacity. SmartCool® reversible fan			
<b>FUEL CAPACITY</b>	21 gallons (79.5 liters) diesel fuel. Biodiesel-Ready for use up to B-20(20% biodiesel and 80% petroleum blend)			
<b>TRACTION DRIVE</b>	Parallel hydrostatic, closed loop system with full-time 4WD. Forward/reverse in low (mow) and high (transport) range with full-time, automatic traction assist (forward only). Variable displacement piston pump with electronic servo control powers dual speed displacement piston motor, powers drive into double reduction planetary in front, and mechanical axle in rear. Smart Power® feature controls traction speed to maintain optimal cutting blade speed.			
<b>GROUND SPEED</b>	Transport: 0-16.2 mph (0-26.1 km/h) forward, 0-8.1 mph (0-13 km/h) reverse. Mow: 0-8.3 mph (0-13.4 km/h) forward, 0-4 mph (0-6.4 km/h) reverse.			
<b>WIDTH OF CUT</b>	Overall: 132" (335 cm), Front: 62" (157.5 cm), Wings: 42" (106.7 cm), Overlap: 7" (17.8 cm).		Overall: 124" (315 cm), Center deck section: 54" (137.1 cm), Two 37" (93 cm) width of cut wings. 89" (226 cm) width of cut with one wing up.	
<b>BRAKES</b>	Mechanically actuated, internal wet disc brakes on input to each planetary drive. Individual foot-operated steering brake control of left and right wheel. Lock pedals together and latch to engage parking brake.			
<b>STEERING</b>	Power steering with dedicated power source. Steering wheel tilts to desired operator position. Uncut circle: 0" diameter.			
<b>MAIN FRAME</b>	All welded formed-steel frame with integral tie-down anchors.			
<b>HYDRAULICS/COOLING</b>	8.75 gallon (33.1 liter) capacity with 10 micron remote spin-on filter. 9 row, single pass cooler, 6.3 fins per inch, that tilts out for cleaning. Variable speed radiator cooling fan with automatic (based on coolant and oil temps) and manual reversing capabilities.			
<b>TIRES</b>	Front: 26 x 12-12, 6-ply tubeless Multi-Trac. Rear: 20 x 10-10, 6-ply tubeless Multi-Trac.			
<b>DIAGNOSTICS</b>	Diagnostic pressure test ports: forward and reverse traction, left, center and right decks, reverse 4WD, lift, steering, charge and deck counterbalance circuits.			
<b>INSTRUMENTATION</b>	InfoCenter™: Onboard LCD display shows gauges, alerts/faults, service reminders, electrical system diagnostics. Indicates fuel level, coolant temp, intake temperature, low oil pressure, alternator, engine hours, engine rpm, hydraulic oil temperature, and voltage.			
<b>OVERALL DIMENSIONS</b>	<b>Height:</b> 85" (216 cm) w/ROPS up, 93.9" (237 cm) w/ cab, <b>Length:</b> 135" (343 cm) w/decks down, <b>Width:</b> 136" (346 cm) w/decks down, <b>Transport Width:</b> 71" (180 cm), @ 2" (5 cm) HOC, <b>Wheelbase:</b> 55.5" (140 cm)		<b>Height:</b> 85.3" (216.7 cm) w/ROPS up, 93.3" (237 cm) w/ cab, <b>Length:</b> 144" (366 cm) w/decks down, <b>Width:</b> 127" (323 cm) w/decks down, <b>Transport Width:</b> 71" (180 cm), @ 2" (5 cm) HOC, <b>Wheelbase:</b> 55.5" (140 cm)	
<b>WEIGHT</b>	4205 lbs. (1907 kg) w/full fluids.	4759 lbs. (2159 kg) w/full fluids.	4237 lbs. (1922 kg) w/full fluids.	4890 lbs. (2218 kg) w/full fluids.
<b>CONTROLS</b>	Tilt steering, ignition switch, throttle switch, foot-operated traction pedal, lockable individual brake pedals, parking brake lock, mow/transport speed selector switch, 3, two-position switches for individual deck lift/lower, counterbalance adjustment, tow valves, cup holder, toolbox, radio holder, fan switch and 12-volt power outlet.			
<b>WARRANTY</b>	Two-year limited warranty. Refer to operator's manual for further details.			

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



**Count on it.**

**LEARN MORE**

CONTACT US AT: **800-803-8676**  
OR VISIT US AT: **toro.com**

©2022 The Toro Company. Bloomington, MN 55420 All rights reserved.  
All other trademarks are property of their respective owners. Printed in the  
USA. Rev. 2/22

Part Number 20-044-T

*Products depicted in this literature are for demonstration purposes only. Actual  
products offered for sale may vary in use, design, required attachments and  
safety features. We reserve the right to improve our products and make changes  
in specifications, design and standard equipment without notice and without  
incurring obligation. See your distributor for details on all our warranties.*

FOLLOW US!



[facebook.com/toro](https://facebook.com/toro)  
[twitter.com/TheToroCompany](https://twitter.com/TheToroCompany)  
[twitter.com/ToroGolf](https://twitter.com/ToroGolf)  
[twitter.com/ToroGrounds](https://twitter.com/ToroGrounds)  
[youtube.com/toro](https://youtube.com/toro)  
[linkedin.com/company/the-toro-company](https://linkedin.com/company/the-toro-company)

