



Debris Blower 600

The Toro® Debris Blower 600 creates incredible wind power to quickly clear large areas of unwanted debris.



DEBRIS BLOWER 600, MODEL 44536*	
POWER SOURCE	Category one and two 3-point hitch of any tractor in the 25 PTO hp range with a 3-point hitch and 540 PTO.
FAN SPEED	1173 rpm @ 540 PTO input.
OUTLET AREA	100 square inches (645 cm ²).
DIRECTIONAL CONTROL	Deflector chute for 180° diversion as standard. Rotational control of diversion gate just behind 3-point hitch.
CASTER WHEELS	Two 13 x 5-6 pneumatic rubber tires.
HEIGHT ADJUSTMENT	0-1.5" (0-4 cm) adjustable in .5" (1.3 cm) increments.
TURF PROTECTION	16" (41 cm) long, 4" (10 cm) diameter turf roller behind fan housing. 8" (20 cm) long, 4" (10 cm) diameter turf roller under deflector chute. Beveled skid plate under deflector chute.
GROUND CLEARANCE	Determined by turf tractor 3-point hitch and caster wheels.
FAN	Radial design with 27" (69 cm) diameter center disc, 8 blades. Outer diameter 36" (91.4 cm).
FAN HOUSING	Split housing: upper and lower. Upper Housing – 12-gauge steel front and rear plates flanged at separation seam with 12-gauge steel rolled and flanged blower band. Lower housing – 10-gauge steel front and rear plates flanged at separation seam with 12-gauge and blower band.
DRIVE	Belt drive 4-5VX. Power source: 30 PTO hp turf tractor with 3-point hitch and 540 PTO.
WEIGHT	500 lbs. (227 kg)
MOUNTING	Category one and two 3-point hitch of any tractor in the 30 PTO hp range with a 3-point hitch and 540 PTO.
DIMENSIONS	Length: 49" (125 cm), Width: 59" (150 cm), Height: 46" (117 cm)

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.
Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

