



OUTCROSS® 9060

TURF UTILITY VEHICLE



DO MORE.

OUTSMART.

The Outcross® 9060 is the only machine of its kind to be purpose built for the management of fine turf. Its balanced design, four-wheel steer, and four-wheel drive system make it extremely gentle on delicate turf. A hydrostatic drive system and simple, one-action controls eliminate the need for an operator who is proficient with the complicated controls and shifting commonly associated with a traditional tractor. Simply select forward or reverse, and drive!



» TURF-FRIENDLINESS

With its unique four-wheel steering and four-wheel drive systems, the Outcross 9060 provides turf friendliness and maneuverability. Each wheel turns and rotates independently to avoid scuffing, over or under rotation, and turf damage, while

also providing superior traction. Outcross 9060's balanced design removes the need for front counterweights, making it significantly more gentle on fine turf than traditional tractors.



» EASY TO OPERATE

The Outcross 9060 drives like an automobile and features controls that combine multiple functions. This makes complicated tasks simple, which gives invaluable peace of mind and flexibility to the operation-critical tasks that keep Turf Managers up at night. Intuitive and

familiar controls make less-experienced operators more comfortable and confident, creating a larger operator pool that provides flexibility and keeps the team productive.

OUTSIDE THE BOX.

Set-up and save the parameters for each of your attachments – one time, upfront – to ensure the machine and operator performs exactly to your specifications and provides repeatable results. Store settings for up to 16 attachments for easy use and consistent performance, making every operator an expert no matter their skill level.



» CONSISTENCY

Preset parameters and programmable guardrails take the decision making away from the operator and puts it back into the Turf Manager's hands. Password protection options and the flexibility to run attachments

with the characteristics of a manual or hydrostatic tractor (or both) gives Outcross 9060 users unmatched consistency and control.



» RELIABILITY

Saving attachment settings makes for easy use and consistent performance a week, month, or years later, no matter the skill level of the operator in the seat. All relevant Toro attachment

settings are pre-populated and allied attachments can be added in just minutes.

OUTWORK.

One machine doing the work of multiple machines maximizes the investment and increases the efficiency of any turf maintenance operation. With three-point, drawbar, bed and loader capabilities, productivity comes standard. Outcross® 9060 owners can mow grass, spread fertilizer, load sand, haul a pallet of sod, aerate, topdress, remove snow, blow leaves, prune roots, spread seed, tow a trailer, sweep a path, and much, much more. Put your investment to work every day and receive consistency, efficiency, and reliability in return.



» QUICK CHANGEABILITY

Quickly change between attachments with the InchMode™ remote control that allows the operator to creep the machine forward or backward, raise and lower the three-point, or spin the PTO, while standing near the rear

of the machine. In a matter of minutes you can switch from a three-point attachment to the cargo bed and haul over two tons, or hook up the loader to move a variety of materials.



» VERSATILITY

The Outcross 9060 is always ready to work. Use a three-point or drawbar attachment with PTO, hydraulic power, or put a bucket or forks on the loader arms. The Outcross 9060 is capable of completing multiple tasks in one compact package and

is compatible with a wide range of attachments because it features a standard category 2 three-point hitch and its loader arms utilize a universal skid steer mounting plate.

OUTPERFORM.

The Outcross® 9060 will always be on the move, no matter the conditions. Whether you need to haul a heavy load, push snow, or mow grass, you can configure Outcross 9060 for the task. An optional all-season cab keeps the operator warm in the winter, dry in the rain, and cool in the summer heat. The optional loader arms can be used to move snow or materials. With an Outcross 9060, you'll be ready for any season.



» CONTROL

Cruise control, shuttle shifting, a passenger seat, and customizable controls add to the ease-of-use, performance, and efficiency Outcross 9060 offers. The standard utility bed offers ample storage while allowing

full movement of the three-point hitch. Operators stay comfortable in the optional cab that includes heat and air conditioning.



» EFFICIENCY

Save money by maintaining one machine instead of two or three. Spread fertilizer and seed more accurately to reduce waste. Bring extra materials, tools, and laborers to the job site to avoid burning fuel on

multiple trips back to the shop. Spend less on repairing damage caused by operator error or turning tires. Use existing three-point, drawbar, or loader attachments to maximize previous investments in implements.

OUTCROSS® 9060



SPECIFICATIONS

OUTCROSS® 9060				
MODEL	OUTCROSS 9060	OUTCROSS 9060 W/ CAB	OUTCROSS 9060 W/ LOADER ARMS	OUTCROSS 9060 W/ LOADER ARMS & CAB
ENGINE	Yanmar® 4-cylinder, direct injection, turbo-charged, liquid-cooled diesel. Power: 59 hp (44 kW) gross, @ 3000 rpm. Displacement: 127.6 cu. in. (2.1 L) EPA Tier IV Final Compliant.			
CAPACITIES	Fuel: 14 gallons (53 L) Engine oil with filter: 6.1 quarts (5.8 L)			
ELECTRICAL SYSTEM	12-volt system. Battery: 690 CCA. Alternator: 80 amp.			
TRACTION DRIVE	2-speed hydrostatic			
PTO	Rear independent mechanical up to 540 rpm. Power: 51 hp (38 kW)			
INSTRUMENTATION	InfoCenter™. Onboard LCD displays for attachment parameter setup and to show gauges, alerts/faults, service reminders, electrical system diagnostics. Indicates fuel level, coolant temp, intake temperature, low oil pressure, alternator, engine hours, engine rpm, hydraulic oil temperature, voltage.			
GROUND SPEED / CLEARANCE	Forward: 21 mph (33.8 km/h) Reverse: 20 mph (32.2 km/h) Ground Clearance: 7" (18 cm)			
HYDRAULICS	Open center			
AUX / REMOTE	12 gpm @ 3000 psi. Standard: 1 remote. Optional: additional hydraulic remote			
LENGTH	Front Bumper to 3-point Linkage: 161" (409 cm)		Mounting Plate to Counter Weight End: 202.5" (514 cm)	
WIDTH	With Bed – 77" (195 cm)			
HEIGHT	95" (241 cm)	98" (249 cm)	95" (241 cm)	98" (249 cm)
WEIGHT	5,160 lbs. (2,340 kg)	5,820 lbs (2,640 kg)	5,910 lbs (2,680 kg)**	6,570 lbs (2,980 kg)**
BED CAPACITY	Standard Bed: 1,000 lbs. (453.6 kg)		Cargo Bed: 4,500 lbs. (2,041 kg)	
INSIDE TURNING RADIUS	57" (145 cm)			
OUTSIDE TURNING RADIUS	150" (381 cm)			
WHEELBASE	83" (211 cm)			
TIRES	Standard: Front: 29.5 x 12.5 (6-ply) Rear: 32 x 16 (6-ply) Standard with Loader Arms: Front: 29.5 x 12.5 (12-ply) Rear: 32 x 16 (6-ply) Aggressive: Front: 29.5 x 12.5 (12-ply) Rear: 32.5 x 12.5 (10-ply)			
TRACK WIDTH	57.5" (146 cm)			
3-POINT HITCH	Category 2. Lift capacity 24" (61 cm) behind lift point: 2,500 lbs. (1,134 kg)			
WARRANTY / CERTIFICATION	Two-year limited warranty. Refer to operators manual for further details. Certified to meet SAE J2194			

**Without loader attachment and recommended 1,800 lbs. (816.5 kg) rear counter weight
For complete specifications, visit toro.com/outcross. Specifications subject to change.



WHEN WE SAY **COUNT ON IT**, WE MEAN IT

Every product that carries the Toro® brand is backed by over 100 years of history, innovation and timeless dependability. We never stop investing in research and development to give our customers the latest features. That's why Toro is one of the best-known, most trusted brands in the business. We also stand behind our products with a global network of knowledgeable dealers for parts and service support. **Real People. Real Support.**

Smart Features. Proven Dependability.



Count on it.

toro.com
Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801
Fax: (1) 952 887 8258

©2019 The Toro Company.
All Rights Reserved.

19-213-GB

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your distributor for details on all our warranties.



facebook.com/ToroCompany
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope