

The Toro logo is displayed in white, bold, sans-serif capital letters inside a red rounded square.

Workman® GTX Series

UTILITY VEHICLES

FEATURES

- **Power** – Whether you choose the 429 cc EFI gasoline, 48-volt A/C electric or Lithium-Ion Workman GTX, power and performance come standard. An improved power to weight ratio boosts payload capacity and productivity by allowing you to do more, every day!
- **Steering** – An automotive-grade rack and pinion steering system provides more control and lowers steering effort, while operating loaded or empty. This allows operators to focus on the task at hand and nothing else.
- **Suspension** – Coil-over shocks all around the vehicle deliver greater suspension travel and adjustability resulting in a smoother ride and minimized operator fatigue.
- **Versatility** – The Workman GTX is adaptable for any task. Two or four-seat configurations come with bench or bucket seats. Front and rear attachment points free up the bed for more hauling capacity. 4 and 6-foot flat beds are also available.



- **Hydraulic Disk Brakes** – Minimal maintenance, no cable adjustment and less pedal force than mechanical cable brakes affords the Workman GTX reliable and consistent stopping power.
- **Durability** – Virtually unbreakable composite exterior components and a powder coated frame and underbody give the Workman GTX superior durability. Run it hard, day after day.

Simply Superior.

The Workman GTX is a grounds and turf crossover vehicle that boasts an unequalled combination of comfort, utility and control, making it simply superior to the competition. Its increased power, improved steering and exclusive suspension and braking systems make the Workman GTX the most versatile, practical and comfortable utility vehicle in its class. Available in gas or electric, the Workman GTX features hundreds of configuration options; including front and rear attachments, a flat bed and a four-seat option. So whether you are setting cups, checking on irrigation, working around campus, or moving people or materials, the Workman GTX has the power and versatility to get the job done right.

toro.com/gtx



Call your Toro distributor at 800-803-8676



Workman® GTX Series Specifications*

	WORKMAN GTX (GAS EFI), MODELS, 07409, 07411EX	WORKMAN GTX – LIFTED (GAS EFI), MODEL 07059LT	WORKMAN GTX (ELECTRIC), MODELS, 07410, 07412EX		
POWER SYSTEM	429cc, air-cooled, single cylinder Kohler® EFI gasoline engine. Meets current EPA & CARB exhaust and evaporative emissions regulations.		48V brushless AC induction drive.		
STEERING	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 13.75" (35 cm) diameter.				
TURNING RADIUS	Standard model: turning clearance circle: 20.7' (6.3 m), inside turning radius: 60.25" (153 cm). Extended model: turning clearance circle: 31' (9.45 m), inside turning radius: 100" (254 cm).				
BRAKES	Front and rear wheel hydraulic disc brakes.				
SUSPENSION	FRONT - Modified MacPherson Strut. REAR - Articulating Swing Arm. Adjustable Coil Over Shocks at all four wheels.				
SUSPENSION TRAVEL	Front Suspension Travel: 3.5" Rear Suspension Travel: 4".				
FUEL CAPACITY	5 gallons (18.9 liters)		N/A		
GROUND SPEED	16 mph (25.6 km/h) governed. Speed reduction kits available.		16 mph (25.6 km/h), adjustable.		
TRANSAXLE	11.47:1 Forward, 14.35:1 Reverse		17:1 double-reduction high torque.		
GROUND CLEARANCE	Front: 9" (22.8 cm), Rear: 6" (15.2 cm)	Front: 12" (30.4 cm), Rear: 7" (17.8 cm)	Front: 9" (22.8 cm), Rear: 6" (15.2 cm)		
TIRES	20 x 8-10, 4-ply. Or alternate 4-ply/6-ply.	22 x 9.5-12, 4-ply. Or alternate 4-ply/6-ply.	20 x 8-10, 4-ply. Or alternate 4-ply/6-ply.		
WHEELS	10" (25.4 cm) steel	12" (30.5 cm) aluminum	10" (25.4 cm) steel		
BATTERIES	One 12-volt starter battery		Eight Trojan® T-125 Advanced Deep Cycle 6V batteries featuring a single port fill system and water level indicators.		
CONTROLLER	N/A		540 amps max with regenerative motor braking, roll-away protection, thermal cutback, sealed/ waterproof, status light and three power modes.		
CHARGER	N/A		On-board high efficiency 1kW smart charger with 85-265VAC global input, temperature controlled, sealed & waterproof, remote indicator viewable at charge port.		
ELECTRIC MOTOR	N/A		Brushless high-torque AC Induction motor with 5.0kW continuous power.		
INSTRUMENTS/DASH	Hour meter, fuel gage, USB power port, headlight switch, on/off ignition key switch, horn, gear selector and parking brake lever. Two cup holders, radio holder and three in-dash storage compartments.		Hour meter, battery level indicator, USB power port, headlight switch, on/off ignition key switch, gear selector and parking brake lever. Two cup holders, radio holder and three in-dash storage compartments.		
STARTING	Pedal or key start capability standard.		Pedal start.		
DIMENSIONS	Vehicle Configuration	Width	Length	Height:	Wheel Base
	2-Seat with Bed (GTX Std.)	47" (119.3 cm)	119" (302 cm)	50.2" (127 cm)	77.8" (197 cm)
	2-Seat with Bed (GTX Lifted)	47" (119.3 cm)	119" (302 cm)	53.2" (135 cm)	77.8" (197 cm)
	4-Seat with Bed (GTX Std.)	47" (119.3 cm)	144" (366 cm)	50.2" (127 cm)	114" (290 cm)
	2-Seat with 6' Flat Bed (GTX Std.)	47" (119.3 cm)	156" (396 cm)	50.2" (127 cm)	114" (290 cm)
CAB DIMENSIONS INSTALLED	Height: 79" (201 cm) Width: 56" (142 cm)	Height: 82" (208 cm) Width: 56" (142 cm)		Height: 79" (201 cm) Width: 56" (142 cm)	
CANOPY DIMENSIONS INSTALLED	Height: 75.2" (191 cm) Width: 54.3" (138 cm)	Height: 78.2" (199 cm) Width: 54.3" (138 cm)		Height: 75.2" (191 cm) Width: 54.3" (138 cm)	
WEIGHT	Vehicle Configuration	Weight		Vehicle Configuration	Weight
	2-Seat with Bed	875 lbs. (397 kg)		2-Seat with Bed	1395 lbs. (633 kg)
	4-Seat with Bed	1150 lbs. (522 kg)		4-Seat with Bed	1670 lbs. (757 kg)
	2-Seat with 6' Flat Bed	1264 lbs. (573 kg)		2-Seat with 6' Flat Bed	1784 lbs. (809 kg)
CARGO BED	Width: 38.5" (97.8 cm) Length: 40" (101.6 cm) Height: 11" (27.9 cm)	Capacity: 800 lbs (363 kg)			
VEHICLE CAPACITY	2-seat with bed 1,200 lbs. (544 kg)				
TOWING CAPACITY	1,500 lbs. (680 kg) Class 1 – 1.25" receiver standard.				
OPTIONAL ACCESSORIES	Canopy, solid folding windshield, 4-seat configuration, flat bed, 6-foot flat bed, bed sides, storage box, trash can mount, bed racking, electric bed lift, brush guard, 12V outlet, Brake/tail/signal lights, ROPS certified hard cab, horn kit, back up alarm kit, parking brake alarm kit, L-track attachment system, all-terrain tire kit, 2-post ROPS kit, beverage cart, range cage, glass windshield, medical-bed.				
WARRANTY	Two-year or 1500 hour limited warranty. Three-year engine warranty. Refer to the Operator's manual for further details.				

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.

Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

