

The Toro logo is a red rounded rectangle with the word "TORO" in white, bold, sans-serif capital letters.

# Workman<sup>®</sup> MDX

UTILITY VEHICLE

## F E A T U R E S

- **More Power** – A 480 cc gasoline or a 600 cc diesel engine powers the Workman MDX to an impressive 1,250 lbs. (567 kg) cargo capacity and 1,200 lbs. (544 kg) towing capacity. This vehicle is built to haul your toughest load to any jobsite and features hydraulic brakes on all four wheels to safely stop you when you get there.
- **More Comfort** – The SRQ™ suspension boasts an independent A-frame front suspension with coil over shock absorbers, proprietary active in-frame twister joint and a rear suspension featuring a swing arm design with coil-over shock absorbers. The result is a smooth ride that you and your team will notice immediately. Operators suffer less fatigue and stay more productive throughout the day.
- **More Control** – An automotive-grade rack and pinion steering system provides more control and lowers steering effort, while operating loaded or empty. This allows operators to focus on the task at hand and move throughout your property more safely.
- **More Durable** – Virtually unbreakable exterior components make the Workman MDX more durable and dependable. This vehicle is built to work as hard as you do, year after year.
- **More Accessories** – A deluxe hard cab, canopy and windshield provide protection from the sun or the elements. The roll-over protective structure (ROPS), brush guard, and optional all-terrain tires help you operate in more challenging terrain. Add the deluxe portable refreshment center to turn your Workman into a revenue producing machine.

## Do more ... with more.

The Workman<sup>®</sup> MDX with SRQ™ combines a coil-over shock absorber suspension design with an Active In-Frame™ twister joint. These features deliver superior ride quality for optimum operator comfort and control. The hefty payload capacity and four-wheel hydraulic brakes enhanced productivity to tackle the toughest jobs. The Workman MDX has the power and versatility to help you do more, with more!





# Workman® MDX Specifications

	WORKMAN MDX, MODEL 07235	WORKMAN MDX-D, MODEL 07236TC
<b>ENGINE</b>	480 cc, air-cooled, two-cylinder, Briggs & Stratton® Vanguard®. Meets 2011 EPA & CARB exhaust & evaporative emissions regulations.	600 cc, liquid-cooled, 2-cylinder, Kubota® diesel. Biodiesel ready for use up to B-20 (20% biodiesel and 80% petroleum blend).
<b>SRQ™ SYSTEM</b>	Active In-Frame™ twister pivot joint, front and rear suspension.	
<b>FRONT SUSPENSION</b>	Modified MacPherson strut, adjustable coil over shock absorbers.	
<b>REAR SUSPENSION</b>	Trailing arm with adjustable coil over shock absorbers.	
<b>GROUND SPEED</b>	16 mph (25.6 km/h) governed. Optional 20 mph (32 km/h) requires ROPS and seat belts.	
<b>BRAKES</b>	Front wheel hydraulic disc. Rear wheel hydraulic drum.	
<b>STEERING</b>	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 13.75" (35 cm) diameter.	
<b>FRAME</b>	Welded steel channel and tube in body construction. Frame surfaces are dipped e-coat. Body and bed constructed of dent and corrosion-resistant polyethylene.	
<b>GROUND CLEARANCE</b>	Front: 10" (25.4 cm), Rear: 7" (18 cm)	
<b>TIRES</b>	Front: 22 x 9.5-10, 4-ply, Rear: 24 x 12-10, 4-ply. Optional all-terrain tires	
<b>FUEL CAPACITY</b>	6.5 gallons (24.6 liters)	
<b>DIMENSIONS</b>	<b>Width</b> 61.2" (155.4 cm)	<b>Length</b> 121.1" (307.5 cm) <b>Wheel Base</b> 80.4" (204.2 cm)
<b>CAB DIMENSIONS INSTALLED</b>	<b>Height</b> 79.2" (201.1 cm)	<b>Width</b> 64" (162.5 cm)
<b>CANOPY DIMENSIONS INSTALLED</b>	<b>Height</b> 79.5" (201.9 cm)	<b>Width</b> 61.2" (155.4 cm)
<b>TURNING CLEARANCE CIRCLE</b>	Inside rear tire: 87" (221), outside front tire: 257" (653 cm).	
<b>INSTRUMENTATION</b>	Hour meter, low oil pressure warning light, accessory power port, and horn. Dash has 2 cup holders, radio holder and glove box storage.	Hour meter, oil pressure, glow plug, coolant temperature, battery charge indicator lights and accessory power port. Dash has 2 cup holders, radio holder and glove box storage.
<b>STARTING</b>	Pedal start (optional key start)	Key start
<b>CARGO BED SIZE INTERNAL</b>	Length: 44.5" (113 cm), Width: 49" (125 cm), Height: 10.25" (26 cm), LLDPE resin.	
<b>TOTAL VEHICLE CAPACITY</b>	1,650 lbs. (750 kg)	
<b>CARGO BED PAYLOAD CAPACITY</b>	1,250 lbs. (567 kg)	
<b>TRAILER TOWING CAPACITY</b>	400 lbs. (182 kg) trailer, 50 lbs. (23 kg) tongue weight with standard hitch. 1,200 lbs. (544 kg) trailer, 100 lbs. (45 kg) tongue weight with heavy-duty tow hitch.	
<b>OPTIONAL ACCESSORIES</b>	Canopy, Solid Folding Windshield, Electric Bed Lift, Brush Guard, ROPS, Brake/Tail/Signal Light Kit, Receiver Hitch, BOSS® Plow, Beverage Cart.	
<b>WARRANTY</b>	Two-year or 1500 hour limited warranty. Refer to the Operator's Manual for further details.	

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.  
Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

