		POWER CLEAR 721 R/E 38741 / 38742	COMMERCIAL POWER CLEAR 721 R-C 38751	POWER CLEAR 721 QZE 38744
THROW DISTANCE*	Up to 25' (8 m)	≫ Up to 35' (11 m)	Up to 35' (11 m)	Up to 35' (11 m)
CLEARING WIDTH	18" (46 cm)	≫ 21" (53 cm)	≫ 21" (53 cm) w/ Extended Life Paddles	21" (53 cm)
AUGER SYSTEM	Power Curve [®] Rotor	Power Curve Rotor	Power Curve Rotor	Power Curve Rotor
SNOW CUT DEPTH — 1 PASS	12" (30.5 cm)	>> 12.5" (31.75 cm)	12.5" (31.75 cm)	12.5" (31.75 cm)
ENGINE				
ENGINE	99cc Toro® Premium 4-cycle OHV	>> 212cc Toro Premium 4-cycle OHV	212cc Toro Premium 4-cycle OHV	212cc Toro Premium 4-cycle OHV
STARTER	Recoil / Electric Start	Recoil / Electric Start	Recoil Start	>> Electric Start
FUEL CAPACITY	1.6 Quarts (1.5 L)	1.1 Quarts (1.0 L)	1.1 Quarts (1.0 L)	1.1 Quarts (1.0 L)
USER-FRIENDLY FEATURES				
DRIVE SYSTEM	Rotor Propelled	➢ Power Propel Self-Propel	Power Propel Self-Propel	Power Propel Self-Propel
HANDLE	Straight	Straight	➢ Reflective & Ergonomic	Ergonomic
CHUTE TYPE	Curved w/Zip Deflector	Curved Steel w/Friction Deflector	Curved Steel w/Friction Deflector	>> High Capacity w/Zip Deflector
CHUTE CONTROL	Chute-Mounted Handle	Chute-Mounted Handle	Chute-Mounted Handle	➢ Quick Shoot
CHUTE ROTATION	210°	210°	210°	210°
WHEELS	6" x 1.5" (15 cm x 3.8 cm)	≫ 7" x 1.5" (18 cm x 3.8 cm)	7" x 1.5" (18 cm x 3.8 cm)	7" x 1.5" (18 cm x 3.8 cm)
SCRAPER	Stationary	➢ Pivoting	Pivoting	Pivoting
WEIGHT: RECOIL / ELECTRIC START	54 lbs. / 58 lbs. (25 kg / 27 kg)	83 lbs. / 88 lbs. (38 kg / 40 kg)	85 lbs. (39 kg)	85 lbs. / 90 lbs. (39 kg / 41 kg)
STORAGE DIMENSIONS (WITH HANDLE FOLDED)	29.5" 18.7" X 27.5" (75 cm x 47.5 cm x 70 cm)	30" x 21" X 37" (76 cm x 53 cm x 94 cm)	30" x 21" X 35" (76 cm x 53 cm x 89 cm)	30" x 21" X 35" (76 cm x 53 cm x 89 cm)
GUARANTEED-TO-START® WARRANTY**	2-Year / Residential Only	2-Year / Residential Only	2-Year / Residential Only	2-Year / Residential Only
WARRANTY**	2-Year Full	2-Year Full	2-Year Full Residential 1-Year Limited Commercial	2-Year Full

>> = Enhanced or Step-up feature

SPECIFICATIONS



POWER PROPEL SYSTEM

This system takes the work out of snowblowing. An innovative pivoting scraper keeps the rotor in constant contact with the pavement, making the job quicker and easier. (Select models only.)



LOCKING ZIP DEFLECTOR Throw snow high, low or in-between.

The deflector locks in to any angle in less than a second–with just a touch of your hand. (Select models only.)



QUICK SHOOT CONTROL SYSTEM

You can change the chute direction without even slowing down. Just squeeze the trigger and slide the handle-mounted grip to throw snow exactly where you want it. (Select models only.)



POWER CURVE TECHNOLOGY

This technology, with curved rotor and inverted funnel housing moves more snow in less time and virtually eliminates clogging. Wide rubber paddles propel the snowthrower forward while cleaning down to the pavement.



490-9804 ©2017 The Toro Company. All Rights Reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *Throw distance will vary with conditions. **See toro.com (US), toro.ca (Canada) or your dealer for warranty details.