

	POWER MAX®					POWER MAX® HD				
	724 OE 37779	824 OE 37793	826 OE 37780	826 OXE 37781	826 OXE 37797	826 OXE 38805	928 OHXE 38801	1028 OHXE 38802	1028 OHXE 38806	
PERFORMANCE	Limited Quantity		Limited Quantity		Limited Quantity					
THROW DISTANCE*	Up to 40' (12 m)	Up to 40' (12 m)	Up to 40' (12 m)	Up to 40' (12 m)	Up to 40' (12 m)	» Up to 45' (13.5 m)	Up to 45' (13.5 m)	Up to 45' (13.5 m)	Up to 45' (13.5 m)	
CLEARING WIDTH	24" (61 cm)	24" (61 cm)	» 26" (66 cm)	26" (66 cm)	26" (66 cm)	26" (66 cm)	» 28" (71 cm)	28" (71 cm)	28" (71 cm)	
POWER STEERING	N/A	N/A	N/A	» Automatic Steering	Automatic Steering	» Power Steering	Power Steering	Power Steering	Power Steering	
SPEEDS	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	
SNOW CUT DEPTH – 1 PASS	20" (51 cm)	20" (51 cm)	20" (51 cm)	20" (51 cm)	20" (51 cm)	» 21.5" (55 cm)	21.5" (55 cm)	21.5" (55 cm)	» 21.5" (55 cm) w/ Standard Drift Breaker	
AUGER SYSTEM	Power Max Anti-Clogging System (ACS)	Power Max Anti-Clogging System (ACS)	Power Max Anti-Clogging System (ACS)	Power Max Anti-Clogging System (ACS)	Power Max Anti-Clogging System (ACS)	Power Max Anti-Clogging System (ACS)	Power Max Anti-Clogging System (ACS)	Power Max Anti-Clogging System (ACS)	Power Max Anti-Clogging System (ACS)	
AUGER DIAMETER	11" (28 cm)	11" (28 cm)	11" (28 cm)	11" (28 cm)	11" (28 cm)	» 14" (36 cm)	14" (36 cm)	14" (36 cm)	14" (36 cm)	
AUGER GEARBOX	Hardened Gears	Hardened Gears; No shear pins needed	Hardened Gears	Hardened Gears	Hardened Gears; No shear pins needed	» Commercial-Grade; No shear pins needed	Commercial-Grade; No shear pins needed	Commercial-Grade; No shear pins needed	Commercial-Grade; No shear pins needed	
ENGINE	» 252cc Toro Premium OHV 4-cycle		252cc Toro Premium OHV 4-cycle	252cc Toro Premium OHV 4-cycle	252cc Toro Premium OHV 4-cycle	252cc Toro Premium OHV 4-cycle	» 265cc Toro Premium OHV 4-cycle	» 302cc Toro Premium OHV 4-cycle	302cc Toro Premium OHV 4-cycle	
STARTER	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	
FUEL CAPACITY	2.3 Quarts (2.2 L)	2.3 Quarts (2.2 L)	» 3.1 Quarts (2.9 L)	3.1 Quarts (2.9 L)	» 3.4 Quarts (3.2 L)	3.4 Quarts (3.2 L)	3.4 Quarts (3.2 L)	3.4 Quarts (3.2 L)	3.4 Quarts (3.2 L)	
USER-FRIENDLY FEATURES										
CHUTE CONTROL	Quick Stick	Quick Stick	Quick Stick	Quick Stick	Quick Stick	Quick Stick	Quick Stick	Quick Stick	Quick Stick	
SKIDS	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	» Cast-Iron	
ONE-HAND INTERLOCK	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
HANDLE	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	» Reinforced Handle Reflection Tape	
HAND WARMERS	N/A	N/A	N/A	N/A	N/A	N/A	» Standard	Standard	Standard	
SCRAPER	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	
TIRES	13" (33 cm) Deep Lug, Directional	13" (33 cm) x 5" (13 cm)	13" (33 cm) Deep Lug, Directional	13" (33 cm) Deep Lug, Directional	15" (38 cm) x 5" (13 cm)	» 16" (41 cm) Deep Lug, Directional	16" (41 cm) Deep Lug, Directional	16" (41 cm) Deep Lug, Directional	16" (41 cm) Deep Lug, Directional	
HEADLIGHT	N/A	N/A	N/A	» Yes	Yes	Yes	Yes	Yes	Yes	
WEIGHT	172 lbs. (78 kg)	180 lbs. (81 kg)	175 lbs. (79 kg)	176 lbs. (79 kg)	180 lbs. (81 kg)	243 lbs. (110 kg)	262 lbs. (119 kg)	267 lbs. (121 kg)	269 lbs. (122 kg)	
STORAGE DIMENSIONS	56" x 27.8" x 43.5"	56" x 27.8" x 43.5"	56" x 27.8" x 43.5"	56" x 27.8" x 43.5"	56" x 27.8" x 43.5"	62" x 29.5" x 44.5"	62" x 29.5" x 44.5"	62" x 29.5" x 44.5"	62" x 29.5" x 44.5"	
MACHINE WARRANTY**	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	» 3-Year Limited 1-Year Commercial	
DEFLECTOR, BYPASS, CHUTE WARRANTY**	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	

POWER MAX®

POWER MAX® HD



ANTI-CLOG SYSTEM (ACS)

Reduces clogging and maximizes impeller speed and snowblowing velocity.



QUICK STICK® CHUTE CONTROL

An innovative joystick control allows you to change the chute direction quickly and easily, even on the go.



MAXIMUM STRENGTH

The unique one-piece frame offers maximum strength for years of dependable use.



SUB ZERO MATERIAL

The chute, deflector, and ACS are made out of a special cold-weather material durable to -104°F. Guaranteed for Life*.



HAND WARMERS

Keep warm in subzero temperatures for added comfort.



FREEWHEEL POWER STEERING

Handle-mounted triggers allow you to disengage one or both wheels for effortless maneuverability.



14" SERRATED AUGER

Extra-large auger designed to chew through even the toughest snow.

COMMERCIAL-GRADE GEARBOX

Unlike others, this gearbox is tough enough not to need shear pins so you never need to worry about replacing them.

TORO®

*See retailer for warranty details. » = Enhanced or Step-up feature

490-9805 ©2017 The Toro Company. All Rights Reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *Throw distance will vary with conditions. **See toro.com (US), toro.ca (Canada) or your dealer for warranty details.