

	POWER MAX 824 OE 37798	POWER MAX 826 OXE 37799	POWER MAX® HD 928 OAE 38840	POWER MAX HD 1028 OHXE 38841	POWER MAX HD 1232 OHXE 38842	POWER MAX HD 1428 OHXE Commercial 38843	POWER MAX HD 1432 OHXE Commercial 38844
ENGINE							
ENGINE	Toro Premium 252cc OHV 4-cycle	Toro Premium 252cc OHV 4-cycle	Toro Premium 265cc OHV 4-cycle	» Toro Premium 302cc OHV 4-cycle	» Toro Premium 375cc OHV 4-cycle	» Toro Premium 420cc OHV 4-cycle	Toro Premium 420cc OHV 4-cycle
STARTER	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start
FUEL CAPACITY	3.1 Quarts (3.0 L)	3.1 Quarts (3.0 L)	3.6 Quarts (3.5 L)	3.6 Quarts (3.5 L)	» 4.8 Quarts (4.5 L)	4.8 Quarts (4.5 L)	4.8 Quarts (4.5 L)
PERFORMANCE							
THROW DISTANCE*	Up to 45' (13.5 m)	Up to 45' (13.5 m)	Up to 45' (13.5 m)	Up to 45' (13.5 m)	» Up to 57' (17.4 m)	Up to 60+ (18.3 m)	Up to 60+ (18.3 m)
CLEARING WIDTH	24" (61 cm)	26" (66 cm)	» 28" (71 cm)	28" (71 cm)	» 32" (71 cm)	28" (71 cm)	32" (81 cm)
STEERING	-	Automatic Steering	Automatic Steering	Power Steering	Power Steering	Power Steering	Power Steering
SPEEDS	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.
DRIVE SYSTEM	Friction Disk	Friction Disk	-	-	-	-	-
AUGER SYSTEM	Anti-Clogging System (ACS), 11" / 28 cm Dia., Hardened Gears; no shear pins needed	Anti-Clogging System (ACS), 11" / 28 cm Dia., Hardened Gears; no shear pins needed	Anti-Clogging System (ACS), 14" / 36 cm Dia., Commercial- Grade; no shear pins needed	Anti-Clogging System (ACS), 14" / 36 cm Dia., Commercial- Grade; no shear pins needed	Anti-Clogging System (ACS), 14" / 36 cm Dia., Commercial- Grade; no shear pins needed	Anti-Clogging System (ACS), 14" / 36 cm Dia., Commercial- Grade; no shear pins needed	Anti-Clogging System (ACS), 14" / 36 cm Dia., Commercial- Grade; no shear pins needed
SNOW CUT DEPTH – 1 PASS	20" (51 cm)	20" (51 cm)	21.5" (55 cm)	21.5" (55 cm)	21.5" (55 cm)	» 21.5" (55 cm) w/ Standard Drift Breaker	21.5" (55 cm) w/ Standard Drift Breaker
FEATURES							
HANDLE	-	-	Reinforced	Reinforced	Reinforced	» 1.5" x 2" Diameter One Piece	1.5" x 2" Diameter One Piece
DEFLECTOR	Steel, Double Deflector	Steel, Double Deflector	Steel, Double Deflector	Steel, Double Deflector	Steel, Double Deflector	Steel, Double Deflector	Steel, Double Deflector
CHUTE CONTROL	Quick Stick 200° Rotation	Quick Stick 200° Rotation	Quick Stick 200° Rotation	Quick Stick 200° Rotation	Quick Stick 200° Rotation	Quick Stick 200° Rotation	Quick Stick 200° Rotation
SKIDS	Standard	Standard	Standard	Standard	Standard	» Cast-Iron	Cast-Iron
ONE-HAND INTERLOCK	Standard	Standard	Standard	Standard	Standard	Standard	Standard
HAND WARMERS	N/A	N/A	N/A	» Standard	Standard	Standard	Standard
SCRAPER	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
TIRES	15" x 4"	» 15" x 5"	16" (41 cm) Deep Lug, Directional	16" (41 cm) Deep Lug, Directional	16" (41 cm) Deep Lug, Directional	16" (41 cm) Deep Lug, Directional	16" (41 cm) Deep Lug, Directional
HEADLIGHT	N/A	» LED	LED	LED	LED	LED	LED
DRIFT BREAKER	N/A	N/A	N/A	N/A	N/A	Standard	Standard
WEIGHT	171 lbs. / 78 kg	180 lbs. / 81 kg	264 lbs. (120 kg)	283 lbs. (128 kg)	300 lbs. (136 kg)	305 lbs. (138 kg)	310 lbs. (141 kg)
STORAGE DIMENSIONS			62" x 29.5" x 44.5"	62" x 29.5" x 44.5"	62" x 33.5" x 44.5"	62" x 29.5" x 44.5"	62" x 33.5" x 44.5"
WARRANTY**	3 Year Limited	3 Year Limited	3 Year Limited, 45 Days Commercial	3 Year Limited, 45 Days Commercial	3 Year Limited, 45 Days Commercial	» 3 Year Limited, 1 Year Commercial	3 Year Limited, 1 Year Commercial
GUARANTEED FOR LIFE WARRANTY**	ACS Only	ACS Only	-	-	-	-	-

» = Enhanced or Step-up feature