	POWER CLEAR® 518 ZR/ZE 38472 / 38473	POWER CLEAR 721 R/E 38741 / 38742	POWER CLEAR 721 R-C	POWER CLEAR 721 QZE 38744	SNOWMASTER® 724 ZXR 36001	SNOWMASTER 724 QXE 36002	SNOWMASTER 824 QXE 36003
ENGINE							
ENGINE	Toro® Premium 99cc OHV 4-cycle	» Toro Premium 212cc OHV 4-cycle	Toro Premium 212cc OHV 4-cycle	Toro Premium 212cc OHV 4-cycle	Toro Premium 212cc OHV 4-cycle	Toro Premium 212cc OHV 4-cycle	» Toro Premium 252cc OHV 4-cycle
STARTER	Recoil / Electric Start	Recoil / Electric Start	Recoil Start	» Electric Start	Recoil Start	» Electric Start	Electric Start
FUEL CAPACITY	1.6 Quarts (1.5 L)	1.1 Quarts (1.0 L)	1.1 Quarts (1.0 L)	1.1 Quarts (1.0 L)	2.3 Quarts (2.2 L)	2.3 Quarts (2.2 L)	» 3.1 Quarts (3.0 L)
PERFORMANCE							
THROW DISTANCE*	Up to 25' (8 m)	» Up to 35' (11 m)	Up to 35' (11 m)	Up to 35' (11 m)	Up to 40' (12 m)	Up to 40' (12 m)	Up to 40' (12 m)
CLEARING WIDTH	18" (46 cm)	» 21" (53 cm)	>> 21" (53 cm) w/ Extended Life Paddles	21" (53 cm)	24" (61 cm)	24" (61 cm)	24" (61 cm)
STEERING	-	-	-	-	Automatic Steering	Automatic Steering	Automatic Steering
SPEEDS	 - 	-	-	-	Infinitely Variable (0-3.5 mph)	Infinitely Variable (0-3.5 mph)	Infinitely Variable (0-3.5 mph)
DRIVE SYSTEM	Rotor Propelled	» Power Propel Self-Propel	Power Propel Self-Propel	Power Propel Self-Propel	Personal Pace®	Personal Pace	Personal Pace
AUGER SYSTEM	Power Curve® Rotor	Power Curve Rotor	Power Curve Rotor	Power Curve Rotor	In-line 2-Stage, 10" / 25 cm dia.	In-line 2-Stage, 10" / 25 cm dia.	In-line 2-Stage, 10" / 25 cm dia.
SNOW CUT DEPTH — 1 PASS	12" (31 cm)	» 12.5" (31.75 cm)	12.5" (31.75 cm)	12.5" (31.75 cm)	18" (46 cm)	18" (46 cm)	18" (46 cm)
USER-FRIENDLY FEATURES	;						
HANDLE	Straight	Straight	» Reflective & Ergonomic	Ergonomic	Ergonomic	Ergonomic	Ergonomic
СНИТЕ ТҮРЕ	Curved w/Zip Deflector	Curved Steel w/Friction Deflector	Curved Steel w/Friction Deflector	>> High Capacity Polyethylene w/Zip Deflector	Sub-Zero Material	Sub-Zero Material	Sub-Zero Material
CHUTE CONTROL	Chute-Mounted Handle (210° Rotation)	Chute-Mounted Handle (210° Rotation)	Chute-Mounted Handle (210° Rotation)	» Quick Shoot (210° Rotation)	EZ Turn (200° Rotation)	» Quick Shoot (210° Rotation)	Quick Stick (200° Rotation)
SKIDS	-	-	-	-	Combination	Combination	Combination
SCRAPER	Stationary	>> Pivoting	Pivoting	Pivoting	Compression Loaded	Compression Loaded	Compression Loaded
WHEELS	6" x 1.5" (15 cm x 3.8 cm)	» 7" x 1.5" (18 cm x 3.8 cm)	7" x 1.5" (18 cm x 3.8 cm)	7" x 1.5" (18 cm x 3.8 cm)	11" / 28 cm Deep Lug Directional Tires	11" / 28 cm Deep Lug Directional Tires	11" / 28 cm Deep Lug Directional Tires
WEIGHT: RECOIL / ELECTRIC START	54 lbs. / 58 lbs. (25 kg / 27 kg)	82 lbs. / 87 lbs. (37 kg / 39 kg)	84 lbs. (38 kg)	91 lbs. (41 kg)	117 lbs. (53 kg)	125 lbs. (57 kg)	131 lbs. (59 kg)
STORAGE DIMENSIONS (WITH HANDLE FOLDED)	29.5" x 18.7" x 27.5" (75 cm x 47.5 cm x 70 cm)	30" x 21" x 37" (76 cm x 53 cm x 94 cm)	30" x 21" x 35" (76 cm x 53 cm x 89 cm)	30" x 21" x 35" (76 cm x 53 cm x 89 cm)			
WARRANTY**	2-Year GTS (Residential Only) 2-Year Full	2-Year GTS (Residential Only) 2-Year Full	2-Year GTS / 2-Year Full (Residential Only) 1-Year Limited (Commercial)	2-Year GTS (Residential Only) 2-Year Full	3-Year Limited	3-Year Limited	3-Year Limited
DEFLECTOR, CHUTE & LOWER CHUTE WARRANTY**	 - 	-	-	 -	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life

COMMERCIAL

POWER CLEAR®



POWER CURVE TECHNOLOGY

Curved rotor and inverted funnel housing moves more snow in less time and virtually eliminates clogging Wide rubber paddles propel the snowthrower forward while cleaning down to the pavement.



POWER PROPEL SYSTEM

Innovative pivoting scraper keeps the rotor in constant contact with the pavement. (Select models only.)

SNOWMASTER®



HANDLES WET. HEAVY SNOW

Tall, open auger housing, free of obstacles reduces clogging in deep snow. The all steel rotor has a helical design which quickly breaks up and gathers snow to the center section that throws snow far through it's tall chute opening.



PERSONAL PACE® SELF PROPEL

Toro's innovative
Personal Pace® self propel
system automatically
senses and adapts to
your walking speed.



>> = Enhanced or Step-up feature