

POWER MAX® HD

IDEAL FOR CLEARING:

10+
PARKED CARS

Concrete,
Asphalt, Gravel
surfaces

9"-20"
(23 cm - 51 cm)
snow depth

POWER CLEAR®

IDEAL FOR CLEARING:

4-9
PARKED CARS

Concrete,
Asphalt
surfaces

2"- 9"
(5 cm - 23 cm)
snow depth

POWER MAX® HD

IDEAL FOR CLEARING:

10+
PARKED CARS

Concrete,
Asphalt
surfaces

9"-20"
(23 cm - 51 cm)
snow depth

POWER BROOM

IDEAL FOR CLEARING:

Commercial
application
in all seasons

Concrete,
Asphalt
surfaces

COMMERCIAL

COMMERCIAL

COMMERCIAL

SHOW DEEP SNOW
WHO'S BOSS



3
YEAR
LIMITED
WARRANTY

ANY TIME
ANY WHERE
ANY CONDITIONS



2
YEAR
FULL
COVERAGE
WARRANTY

NEW!

OUR BIGGEST
BLIZZARD
BUSTER




3
YEAR
LIMITED
WARRANTY


CLEAR SNOW
IN A BIG WAY




COMMERCIAL
1 YEAR
FULL WARRANTY




PRECISION CONTROL
Smooth, tight turns are a snap with power steering. *(Select models)*




EASY STREET
Quickly change the chute and deflector direction with a single, smooth motion thanks to the Quick Stick® chute control.




NIGHT VISION
Your visibility will never be clearer with the LED headlight. *(Select models)*




POWER TO BLAST THROUGH HEAVY, DEEP SNOW
Toro's powerful 4-cycle OHV engines give you the power to slice through snow in no time.




EXTENDED LIFE PADDLES
Designed for less downtime with twice the life of Toro standard paddles.




REINFORCED HANDLE
Attached with 4 bolts for maximum rigidity.




ONE PIECE, REINFORCED HANDLE
For added durability and strength.




DRIFT CUTTER
Knocks down large drifts, allowing auger to collect and throw deep snow. *(Select models)*




CAST IRON SKID PLATES
Extra wide .5" skids provide maximum life and reliability. The added weight on the front helps to chew through deep snow piles.



4 TIE-DOWN POINTS
Fasten your product quickly and firmly with our structurally sound integrated tie-down points for safe and easy transportation.



UNIQUE PIN HEIGHT-OF-BRUSH SYSTEM
Precision height adjustment with up to 1/8" adjustments to minimize surface damage and brush wear.



VARIABLE SPEED & POWER STEERING
Commercial variable speed transmission allows you to shift on the fly with 6 forward and 2 reverse speeds, while power steering makes maneuvering easy.

HEAVY-DUTY TWO-STAGE			
	928 OAE 38840	1028 OHXE 38841	1232 OHXE 38842
Engine	Toro® Premium 265cc 4-cycle OHV	» Toro Premium 302cc 4-cycle OHV	» Toro Premium 375cc 4-cycle OHV
Throw Distance	Up to 45' (13.5 m)	» Up to 49' (14.9 m)	» Up to 57' (17.4 m)
Clearing Width	28" (71 cm)	28" (71 cm)	» 32" (81 cm)
Starter	Electric Start	Electric Start	Electric Start
Rotor Style	Anti-Clogging System, 11" (28 cm) Dia., Hardened Gears, No Shear Pins Needed	Anti-Clogging System, 11" (28 cm) Dia., Hardened Gears, No Shear Pins Needed	Anti-Clogging System, 11" (28 cm) Dia., Hardened Gears, No Shear Pins Needed
Snow Cut Depth - 1 Pass	21.5" (55 cm)	21.5" (55 cm)	21.5" (55 cm)
Chute/ Deflector Type	Steel Chute / Double Deflector	Steel Chute / Double Deflector	Steel Chute / Double Deflector
Headlight	✓	✓	✓
Handwarmers	-	✓	✓
Warranty^	3-Year Limited 45 Days Limited Commercial	3-Year Limited 45 Days Limited Commercial	3-Year Limited 45 Days Limited Commercial

COMMERCIAL SINGLE-STAGE		
	721 R-C 38754	821 R-C 38755
Engine	Toro Premium 212cc 4-cycle OHV	» Toro Premium 252cc 4-cycle OHV
Throw Distance	Up to 35' (11 m)	» Up to 40' (12 m)
Clearing Width	21" (53 cm) w/Extended Life Paddles	21" (53 cm) w/Extended Life Paddles
Drive System	Power Propel Self-Propel	Power Propel Self-Propel
Starter	Recoil Start	Recoil Start
Rotor Style	Power Curve Rotor	Power Curve Rotor
Snow Cut Depth - 1 Pass	12.5" (31.75 cm)	12.5" (31.75 cm)
High Capacity Chute w/Locking Deflector	✓	✓
Warranty^	2-Year Residential 1-Year Limited Commercial	2-Year Residential 1-Year Limited Commercial
GTS Warranty^	2-Year Residential Only	2-Year Residential Only


COMMERCIAL HEAVY-DUTY TWO-STAGE		
	1428 OHXE 38843	1432 OHXE 38844
Engine	Toro Premium 420cc 4-cycle OHV	Toro Premium 420cc 4-cycle OHV
Throw Distance	Up to 60' (18.3 m)	Up to 60' (18.3 m)
Clearing Width	28" (71 cm)	32" (81 cm)
Starter	Electric Start	Electric Start
Rotor Style	Anti-Clogging System (ACS), 14" / 36 cm Dia., Commercial-Grade; no shear pins needed	Anti-Clogging System (ACS), 14" / 36 cm Dia., Commercial-Grade; no shear pins needed
Snow Cut Depth - 1 Pass	21.5" / 55 cm w/Drift Breaker (31.75 cm)	21.5" / 55 cm w/Drift Breaker (31.75 cm)
Chute/Deflector Type	Steel / Double Deflector	Steel / Double Deflector
Headlight	✓	✓
Handwarmers	✓	✓
Warranty^	3-Year Residential 1-Year Limited Commercial	3-Year Residential 1-Year Limited Commercial

COMMERCIAL POWER BROOM	
	38700
Engine	Kohler® Command PRO® Multi-Season
Broom Width	36" (91.4 cm)
Broom Angle	40°
Broom Diameter	25" (63.5 cm)
Broom Speed	200 rpm
Starter	Recoil Start
Steering	Power Steering R/LH Clutch
Tires	15" x 5" (38.1 x 12.71 cm) Drive Tire 5" (12.7 cm) Caster Tire
Speeds	6/2 Variable Speed
Warranty^	1-Year Full



SNOW BLOWERS

POWER MAX® HD / POWER MAX® / SNOWMASTER® /
POWER CLEAR® / ELECTRIC / BATTERY



AMERICA'S #1
SNOW BLOWER
BRAND†



^See retailer for warranty details. † Based on average Traqline unit share for snow blower market from 2013 – 2018. * Compared to Toro® Power Max® models. Capacity will vary with conditions.
**Battery manufacture rating = 60V maximum & 54V typical usage. Actual voltage varies with load.

60V MAX™ BATTERY

ELECTRIC

POWER CLEAR®

SNOWMASTER®

POWER MAX®

IDEAL FOR CLEARING:

4-9
PARKED CARS

Concrete, Asphalt
surfaces

2"- 9"
(5 cm - 23 cm)
snow depth

DO THE JOB BETTER, FASTER, EASIER

NEW!

FULL COVERAGE WARRANTY

IDEAL FOR CLEARING:

Walkways, Patios, Decks

Concrete, Asphalt
surfaces

2"- 6"
(5 cm - 15 cm)
snow depth

SNOW-CLEARING CONVENIENCE

2 YEAR FULL COVERAGE WARRANTY

IDEAL FOR CLEARING:

4-9
PARKED CARS

Concrete, Asphalt
surfaces

2"- 9"
(5 cm - 23 cm)
snow depth

GET THE JOB DONE FASTER

NEW!

2 YEAR FULL COVERAGE WARRANTY

IDEAL FOR CLEARING:

6-12
PARKED CARS

Concrete, Asphalt
surfaces

6"- 10"
(15 cm - 25 cm)
snow depth

MAKE SNOW BLOWING LESS WORK

GUARANTEED FOR LIFE LIMITED WARRANTY

3 YEAR LIMITED WARRANTY

IDEAL FOR CLEARING:

8-14
PARKED CARS

Concrete, Asphalt, Gravel
surfaces

9"- 20"
(23 cm - 51 cm)
snow depth

SNOW-CLEARING MUSCLE

3 YEAR LIMITED WARRANTY

SNOWDRIFT STRENGTH
All the power to break through heavy, wet snow and throw it up to 40 ft.

CRUSH SNOW TO THE CURB
Rip through tough snow with the durable design of Toro's patent-pending metal Power Edge™ auger.

STARTS THE FIRST TIME, EVERY TIME
Reliable starting and low maintenance with battery power. Flex-Force 60V** batteries have intelligent software to maximize run time and power.

POWERFUL PERFORMANCE
The lightweight Power Shovel throws snow up to 20 feet while the 1800 Power Curve throws snow up to 30 feet.

TELESCOPING HANDLE
Height adjustment of 6" (15 cm) to fit any user.

QUICK CHUTE LEVER
Aim snow on the go with no cranking needed. *Standard on 1800 Power Curve.*

POWER TO BLAST THROUGH SNOW
Toro's powerful 4-cycle OHV engines give you the power to slice through snow in no time and throw up to 40 feet.

SHREDS SNOW FAST
Efficiently shreds through snow while reducing clogging with the curved paddles and funneled housing of the Power Curve® Technology.

GET A MOVE ON
Keep moving to get the job done faster with the Power Propel®. Our unique scraper keeps the paddle in constant contact with the ground, pulling you through the snow. *(select models)*

30% FASTER
THAN A TRADITIONAL TWO-STAGE*

KEEP UP THE PACE
You control how fast or slow you go with the Personal Pace® Self-Propel System. The rear wheel drive system also equips you with the best traction in any snow condition.

EASY STREET
Quickly change the chute and deflector direction in a single, smooth motion thanks to the Quick Stick® chute control. *(select models)*

STAY THE COURSE
Minimize clogging and maximize speed with the guaranteed for life anti-clogging system.

DON'T STOP
No need to replace sheer pins in the cold with the commercial-grade auger gearbox.

EASY STREET
Quickly change the chute and deflector direction in a single, smooth motion thanks to the Quick Stick® chute control.

SINGLE-STAGE			
	39901	39902	39901T <i>(Tool only)</i>
Battery Power	(1) L405 (7.5 ah, 405 wh)	» (2) L324 (6.0 ah, 324 wh)	–
Motor	Brushless DC	Brushless DC	Brushless DC
Throw Distance	Up to 40" (12 m)	Up to 40" (12 m)	Up to 40" (12 m)
Clear Space in Single Charge	Up to 12 parked cars	Up to 18 parked cars	N/A
Charge Time	180 min	150 min (per battery)	N/A
Rotor Style	All Steel Power Edge™	All Steel Power Edge	All Steel Power Edge
Snow Cut Depth - 1 Pass	12" (31 cm)	12" (31 cm)	12" (31 cm)
Chute/Deflector Type	Curved w/Locking Deflector	Curved w/Locking Deflector	Curved w/Locking Deflector
Headlight	✓	✓	✓
Snow Blower Warranty^	2-Year Full	2-Year Full	2-Year Full
Battery Warranty^	3-Year Full	3-Year Full	–

ELECTRIC		
	POWER SHOVEL™ 38361	POWER CURVE® 38381
Engine	7.5 Amp Series Wound Electric	15 Amp Series Wound Electric
Throw Distance	Up to 20' (6 m)	» Up to 30' (9 m)
Clearing Width	12" (31 cm)	» 18" (46 cm)
Starter	On/Off Switch	On/Off Switch
Rotor Style	Power Curve® Rotor	Power Curve Rotor
Snow Cut Depth - 1 Pass	6" (15 cm)	» 12" (31 cm)
Chute/Deflector Type	–	Locking Deflector
Warranty^	2-Year Full	2-Year Full

SINGLE-STAGE				
	518 ZR/ZE 38472 / 38473	721 R/E 38752 / 38753	721 QZE 38756	821 QZE 38757
Engine	Toro® Premium 99cc 4-cycle OHV	» Toro Premium 212cc 4-cycle OHV	Toro Premium 212cc 4-cycle OHV	» Toro Premium 252cc 4-cycle OHV
Throw Distance	Up to 25' (8 m)	» Up to 35' (11 m)	Up to 35' (11 m)	» Up to 40' (12 m)
Clearing Width	18" (46 cm)	» 21" (53 cm)	21" (53 cm)	21" (53 cm)
Drive System	Rotor Propelled	» Power Propel® Self-Propel	Power Propel Self-Propel	Power Propel Self-Propel
Starter	Recoil / Electric Start	Recoil / Electric Start	Electric Start	Electric Start
Rotor Style	Power Curve Rotor	Power Curve Rotor	Power Curve Rotor	Power Curve Rotor
Snow Cut Depth - 1 Pass	12" (31 cm)	» 12.5" (32 cm)	12.5" (32 cm)	12.5" (32 cm)
Chute/Deflector Type	Curved w/Locking Deflector	» High Capacity w/Locking Deflector	High Capacity w/Locking Deflector	High Capacity w/Locking Deflector
Warranty^	2-Year Full	2-Year Full	2-Year Full	2-Year Full
GTS Warranty^	2-Year Residential Only	2-Year Residential Only	2-Year Residential Only	2-Year Residential Only

SNOWMASTER®			
	724 ZXR 36001	724 QXE 36002	824 QXE 36003
Engine	Toro® Premium 212cc 4-cycle OHV	Toro Premium 212cc 4-cycle OHV	» Toro Premium 252cc 4-cycle OHV
Throw Distance	Up to 40" (12 m)	Up to 40" (12 m)	» Up to 45" (14 m)
Clearing Width	24" (61 cm)	24" (61 cm)	24" (61 cm)
Drive System	Personal Pace®	Personal Pace	Personal Pace
Starter	Recoil	» Electric Start	Electric Start
Rotor Style	In-Line 2-Stage, 10" (25 cm) Dia.	In-Line 2-Stage, 10" (25 cm) Dia.	In-Line 2-Stage, 10" (25 cm) Dia.
Snow Cut Depth - 1 Pass	18" (46 cm)	18" (46 cm)	18" (46 cm)
Chute/Deflector Type	Sub Zero Material w/Locking Deflector	» Sub Zero Material	Sub Zero Material
Warranty^	3-Year Limited Guaranteed For Life Lower Chute, Chute & Deflector	3-Year Limited Guaranteed For Life Lower Chute, Chute & Deflector	3-Year Limited Guaranteed For Life Lower Chute, Chute & Deflector

COMPACT TWO-STAGE		
	824 OE 37798	826 OAE 37799
Engine	Toro® Premium 252cc 4-cycle OHV	Toro Premium 252cc 4-cycle OHV
Throw Distance	Up to 45" (13.5 m)	Up to 45" (13.5 m)
Clearing Width	24" (61 cm)	» 26" (66 cm)
Auto-Steering	–	✓
Drive System	Friction Disk	Friction Disk
Starter	Electric Start	Electric Start
Rotor Style	Anti-Clogging System, 11" (28 cm) Dia., Hardened Gears, No Shear Pins Needed	Anti-Clogging System, 11" (28 cm) Dia., Hardened Gears, No Shear Pins Needed
Snow Cut Depth - 1 Pass	20" (51 cm)	20" (51 cm)
Chute/Deflector Type	Steel Chute	Steel Chute
Warranty^	3-Year Limited ACS Guaranteed For Life	3-Year Limited ACS Guaranteed For Life

^See retailer for warranty details. † Based on average Traqline unit share for snow blower market from 2013 – 2018. * Compared to Toro® Power Max® models. Capacity will vary with conditions. **Battery manufacture rating = 60V maximum & 54V typical usage. Actual voltage varies with load.