

# POWER PLEX™

## SPECIFICATIONS 40V MAX\* LITHIUM ION PRODUCTS

COMPLETE TOOL <i>(T90 Battery &amp; charger included)</i>	51481	51482	51491	51690	51880
BARE TOOL <i>(Battery &amp; charger NOT included)</i>	51481T	51482T	51491T	51690T	51880T
	STRING TRIMMER/EDGER	STRING TRIMMER	HEDGE TRIMMER	BLOWER	CHAINSAW
<b>CUTTING LENGTH</b>	13"	14"	24" Bar	N/A	14" Bar
<b>MOTOR</b>	Brushed DC	Brushless DC	Brushed DC	Brushless DC	Brushless DC
<b>SPEED (Up to)</b>	N/A	N/A	3,000 SPM	150 MPH 480 CFM	11 m/s
<b>CUTTING TYPE</b>	Single .080"	Dual .080"	Dual action	N/A	3/8" Pitch Chain
<b>COMFORT</b>	Variable Speed Telescoping Shaft; Adjustable Assist Handle	Variable Speed Adjustable Assist Handle	90° Rotating Handle	Variable Speed Cruise Control	Low-kickback Chain and Metal Bucking Teeth
<b>WEIGHT <i>(with battery / without battery)</i></b>	8.4 lbs. / 6.2 lbs.	9.2 lbs. / 7.0 lbs	9.2 lbs. / 7.0 lbs	8.4 lbs. / 6.2 lbs.	13.7 lbs. / 11.5 lbs.
<b>T90 BATTERY*</b> <i>Included w/Complete Tool</i>					
<b>Volts – Ah</b>	40V – 2.5	40V – 2.5	40V – 2.5	40V – 2.5	40V – 2.5
<b>Run time<sup>^</sup> (up to)</b>	45 min	40 min	60 min	60 min	40 cuts/battery
<b>Recharge</b> <i>Charger Included w/Complete Tool</i>	60 min	60 min	60 min	60 min	60 min
<b>T180 BATTERY*</b> <i>Sold separately</i>					
<b>Volts – Ah</b>	40V – 5.0	40V – 5.0	40V – 5.0	40V – 5.0	40V – 5.0
<b>Run time<sup>^</sup> (up to)</b>	90 min	80 min	120 min	120 min	80 cuts/battery
<b>Recharge</b> <i>Charger Included w/Complete Tool</i>	120 min	120 min	120 min	120 min	120 min
<b>WARRANTY</b>	3-Year Tool, 1-Year Battery				

### PARTS & ACCESSORIES

BLOWER		CHAINSAW	
Gutter Cleaning Kit	51667	Replacement Bar	88580
Oscillating Nozzle Kit	51664	Replacement Chain	88581
<b>13" STRING TRIMMER/EDGER</b>		Bar & Chain Oil (quart)	38914
Single Line Spools (3 pack)	88545	Bar & Chain Oil (gallon)	38917
<b>14" STRING TRIMMER</b>			
Dual Line Spools (3 pack)	88546		



Check out the  
**POWER PLEX™**  
family of tools at  
[toro.com/powerplex](http://toro.com/powerplex)

Actual products may vary. All specifications to be verified with final product.

[toro.com](http://toro.com) / [toro.ca](http://toro.ca)

490-9704 © 2017 The Toro Company, Bloomington, MN 55420 All rights reserved. Printed in the USA.

\*Battery manufacturer rating = 40V maximum & 36V typical usage. Actual voltage varies with load.

<sup>^</sup>Based on lowest speed in controlled laboratory testing of product.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your dealer for details on all our warranties.



**FOLLOW US!**

[facebook.com/toro.yard](https://facebook.com/toro.yard)  
[twitter.com/TheToroCompany](https://twitter.com/TheToroCompany)  
[youtube.com/toro](https://youtube.com/toro)  
[pinterest.com/thetorocompany](https://pinterest.com/thetorocompany)  
[instagram.com/thetorocompany](https://instagram.com/thetorocompany)