

TIMECUTTER®

SS4200 74705 **NEW!**SS4225 74706 **NEW!**MX5025 74727 **NEW!**

HD 75210

ENGINE AT 3600 RPM	Toro 452cc ¹	» 18 hp Kawasaki® V-Twin 603cc ²	» 23 hp Kawasaki® V-Twin 726cc ²	21.5 hp Kawasaki V-Twin 726cc ²
ENGINE GUARD	Standard	Standard	Standard	Standard
FUEL CAPACITY	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)	5 gallons (18.9 liters)
MOWING DECK	42" (107 cm) – 13 ga. 2 blades	42" (107 cm) – 13 ga. 2 blades	» 50" (127 cm) – 10 ga. 3 blades	» 48" (121.9 cm) Fabricated - Grade 50 High Strength 10 ga. Steel Shell
BLADE TIP SPEED	17,810 ft/min (5,428 m/min)	17,810 ft/min (5,428 m/min)	» 18,330 ft/min (5,587 m/min)	» 18,880+ ft/min (5,755+ m/min)
DECK WASHOUT PORTS	Standard	Standard	Standard	» 2 Standard
HEIGHT OF CUT	1.5" – 4.5" (3.8 - 11.4 cm)	1.5" – 4.5" (3.8 - 11.4 cm)	1.5" – 4.5" (3.8 - 11.4 cm)	1.5" – 4.5" (3.8 - 11.4 cm)
DECK LIFT PEDAL	Optional	Optional	Optional	» Standard 13 position
FRAME	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge
HITCH	Standard	Standard	Standard	Standard
ANTI-VIBRATION MAT	Optional	Optional	Optional	» Standard
TRANSMISSIONS	Dual Hydrostatic HG-ZT2100	Dual Hydrostatic HG-ZT2100	» Dual Hydrostatic HG-ZT2200	» Dual Hydrostatic HG-ZT3100
SMART SPEED®	Standard	Standard	Standard	Standard
AUTOMATIC PARKING BRAKE	Standard	Standard	Standard	Manual Park Brake
MOW (F/R)	7 mph/3 mph (11.3 km/h / 4.8 km/h)	7 mph/3 mph (11.3 km/h / 4.8 km/h)	7 mph/3 mph (11.3 km/h / 4.8 km/h)	
TOW (F/R)	5.5 mph/2.4 mph (8.8 km/h / 3.8 km/h)	5.5 mph/2.4 mph (8.8 km/h / 3.8 km/h)	5.5 mph/2.4 mph (8.8 km/h / 3.8 km/h)	Up to 8.5 mph (13.7 km/h)
TRIM (F/R)	4 mph/1.7 mph (6.4 km/h / 2.7 km/h)	4 mph/1.7 mph (6.4 km/h / 2.7 km/h)	4 mph/1.7 mph (6.4 km/h / 2.7 km/h)	
TIRES (REAR)	18" x 7.5" (45.7 cm x 19.1 cm)	18" x 7.5" (45.7 cm x 19.1 cm)	» 20" x 10" (50.8 cm x 25.4 cm)	» 22" x 10" (55.9 x 25.4 cm)
TIRES (FRONT)	11" x 4" (27.9 cm x 10.2 cm)	11" x 4" (27.9 cm x 10.2 cm)	» 13" x 5" (33 cm x 12.7 cm)	» 13" x 6.5" (33 x 16.5 cm)
SEAT	18" (46 cm) Extra-Tall	15" (38 cm) Standard	» 18" (46 cm) Premium	» MyRide® Suspension System 18" (46 cm) Thickly Padded Premium
ARMRESTS	Optional	Optional	Standard	Standard
HOURLY METER	Optional	Optional	Optional	» Standard
STORAGE DIMENSIONS (W x L x H)	45.3" x 71.8" x 37.3" (115 x 182 x 95 cm)	45.3" x 71.8" x 37.3" (115 x 182 x 95 cm)	53.5" x 72.9" x 39.1" (135.9 x 185 x 99.3 cm)	82" x 52.4" x 44" (208.3 x 133.1 x 111.8 cm)
RESIDENTIAL LIMITED WARRANTY*	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year 300 Hours

» = Enhanced or Step-up feature

**SMART SPEED®
CONTROL SYSTEM**

Three speed ranges to meet your needs – Trim, Tow, Mow – can be changed on the fly.

Select models only

**SMART PARK™
BRAKING SYSTEM**

Automatically stops the mower deck and sets the brake when you need to get off the mower and keeping the engine running.

SW4200 Model 74785 only

**MyRIDE® SEATING PLATFORM
SUSPENSION SYSTEM**

Quickly and easily adjust the ride settings to your personal preference. The suspended operator platform allows you to float with 3" (7.5 cm) of travel – double that of a standard suspension seat in this class.

74727 and HD 75210 models only

TORO®

490-9973 ©2018 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. ¹The gross horsepower of these engines were laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940. ²The gross horsepower of these engines were laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower. *See retailer for warranty details. [▲]2013 HANDY Magazine Innovation Award Winner