

TIMECUTTER®	SS4200 74705 <b>NEW!</b>	SS4225 74706 <b>NEW!</b>	SW4200 74785	MX5025 74727	HD 75210
ENGINE¹ AT 3600 RPM	Toro 452cc	» 22.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	» 24.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	23 hp Kawasaki® V-Twin 726cc	22.5 hp Toro Commercial V-Twin
ENGINE GUARD	Standard	Standard	Standard	Standard	Standard
FUEL CAPACITY	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)
MOWING DECK	» 42" (107 cm) – 13 ga. 2 blades	42" (107 cm) – 13 ga. 2 blades	42" (107 cm) – 13 ga. 2 blades	» 50" (127 cm) – 12 ga. 3 blades	» 48" (121.9 cm) Fabricated - Grade 50 High Strength 10 ga. Steel Shell
BLADE TIP SPEED	17,810 ft/min (5,428 m/min)	17,810 ft/min (5,428 m/min)	17,810 ft/min (5,428 m/min)	» 18,330 ft/min (5,587 m/min)	» 18,880+ ft/min (5,755+ m/min)
DECK WASHOUT PORTS	Standard	Standard	Standard	Standard	2 Standard
HEIGHT OF CUT	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm)
DECK LIFT PEDAL	Optional	Optional	Optional	Optional	Standard 13 position
FRAME	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge
HITCH	Standard	Standard	Standard	Standard	Standard
ANTI-VIBRATION MAT	Optional	Optional	Optional	Optional	Standard
TRANSMISSIONS	Dual Hydrostatic HG-ZT2100	Dual Hydrostatic HG-ZT2100	Dual Hydrostatic HG-ZT2100	» Dual Hydrostatic HG-ZT2200	» Dual Hydrostatic HG-ZT3100
SMART SPEED® / SMART PARK™	Smart Speed	Smart Speed	Smart Park	Smart Speed	Smart Speed
AUTOMATIC PARKING BRAKE	Standard	Standard	Standard	Standard	Standard
MOW (F/R)	7 mph/3 mph (11.3 km/h / 4.8 km/h)	7 mph/3 mph (11.3 km/h / 4.8 km/h)	7 mph/3 mph (11.3 km/h / 4.8 km/h)	7 mph/3 mph (11.3 km/h / 4.8 km/h)	Up to 8.5 mph (13.7 km/h)
TOW (F/R)	5.5 mph/2.4 mph (8.8 km/h / 3.8 km/h)	5.5 mph/2.4 mph (8.8 km/h / 3.8 km/h)	5.5 mph/2.4 mph (8.8 km/h / 3.8 km/h)	5.5 mph/2.4 mph (8.8 km/h / 3.8 km/h)	
TRIM (F/R)	4 mph/1.7 mph (6.4 km/h / 2.7 km/h)	4 mph/1.7 mph (6.4 km/h / 2.7 km/h)	4 mph/1.7 mph (6.4 km/h / 2.7 km/h)	4 mph/1.7 mph (6.4 km/h / 2.7 km/h)	
TIRES (REAR)	» 18" x 7.5" (45.7 cm x 19.1 cm)	18" x 7.5" (45.7 cm x 19.1 cm)	18" x 7.5" (45.7 cm x 19.1 cm)	» 20" x 10" (50.8 cm x 25.4 cm)	» 22" x 10" (55.9 x 25.4 cm)
TIRES (FRONT)	11" x 4" (27.9 cm x 10.2 cm)	11" x 4" (27.9 cm x 10.2 cm)	» 13" x 5" (33 cm x 12.7 cm)	» 13" x 6.5" (33 cm x 16.51 cm)	13" x 6.5" (33 x 16.5 cm)
SEAT	18" (46 cm) Extra-Tall	18" (46 cm) Extra-Tall	18" (46 cm) Extra-Tall	» MyRide® Suspension System 18" (46 cm) Thickly Padded Premium	MyRide Suspension System 18" (46 cm) Thickly Padded Premium
ARMRESTS	Optional	Optional	Optional	Standard	Standard
HOURLY METER	Optional	Optional	Optional	Optional	Standard
STORAGE DIMENSIONS (W x L x H)	45.3" x 71.8" x 37.3" (115 x 182 x 95 cm)	45.3" x 71.8" x 37.3" (115 x 182 x 95 cm)	45.3" x 78.9" x 45.4" (115 x 200.4 x 115.3 cm)	53.5" x 72.9" x 39.1" (135.9 x 185 x 99.3 cm)	82" x 52.4" x 44" (208.3 x 133.1 x 111.8 cm)
RESIDENTIAL LIMITED WARRANTY**	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year 300 Hours

» = Enhanced or Step-up feature



#### SMART SPEED® CONTROL SYSTEM

Three speed ranges to meet your needs – Trim, Tow, Mow – can be changed on the fly.

Select models only



#### SMART PARK™ BRAKING SYSTEM

Automatically stops the mower deck and sets the brake when you need to get off the mower and keeping the engine running.

SW4200 Model 74785 only



#### MyRIDE® SUSPENSION SYSTEM

Quickly and easily adjust the ride settings to your personal preference. The suspended operator platform allows you to float with 3" (7.5 cm) of travel – double that of a standard suspension seat in this class.

MX5025 and HD 75210 models only