



# Toro Black Bottle

## The Toro Company

Chemwatch: 5230-85  
Version No: 2.1.1.1  
Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 4

Issue Date: 02/12/2016  
Print Date: 05/10/2018  
S.GHS.USA.EN

## SECTION 1 IDENTIFICATION

### Product Identifier

Product name	Toro Black Bottle
Synonyms	Part number: 112-0176, Product Code: 04324 042319 .6B
Proper shipping name	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base; Paint related material including paint thinning, drying, removing, or reducing compound
Other means of identification	Not Available

### Recommended use of the chemical and restrictions on use

Relevant identified uses	Use according to manufacturer's directions.
--------------------------	---

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	The Toro Company
Address	8111 Lyndale Avenue South Bloomington MN 55420 United States
Telephone	+1 952 888 8801
Fax	Not Available
Website	Not Available
Email	Not Available

### Emergency phone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

## SECTION 2 HAZARD(S) IDENTIFICATION

### Classification of the substance or mixture

#### CHEMWATCH HAZARD RATINGS



#### NFPA 704 diamond



0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Flammable Liquid Category 1, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Reproductive Toxicity Category 2, Specific target organ toxicity - single exposure Category 3 (narcotic effects), Specific target organ toxicity - repeated exposure Category 2, Aspiration Hazard Category 1
----------------	--

### Label elements

Hazard pictogram(s)	
---------------------	--

SIGNAL WORD	DANGER
-------------	--------

### Hazard statement(s)

H224	Extremely flammable liquid and vapour.
------	--

## Toro Black Bottle

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H361	Suspected of damaging fertility or the unborn child.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.

**Hazard(s) not otherwise specified**

Not Applicable

**Precautionary statement(s) Prevention**

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P281	Use personal protective equipment as required.
P240	Ground/bond container and receiving equipment.

**Precautionary statement(s) Response**

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before reuse.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Precautionary statement(s) Storage**

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Precautionary statement(s) Disposal**

P501	Dispose of contents/container in accordance with local regulations.
------	---

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS****Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
108-88-3	20-<30	<u>toluene</u>
78-93-3	10-<20	<u>methyl ethyl ketone</u>
108-65-6	10-<20	<u>propylene glycol monomethyl ether acetate, alpha-isomer</u>
7631-86-9	1-<5	<u>silica amorphous</u>
1330-20-7	1-<5	<u>xylene</u>
1333-86-4	0.1-<1	<u>carbon black</u>
100-41-4	0.1-<1	<u>ethylbenzene</u>
		Ecolab Solid Soft Plus
	20-<30	Ingredients determined not to be hazardous

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

**SECTION 4 FIRST-AID MEASURES****Description of first aid measures**

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> </ul>

Continued...

## Toro Black Bottle

	<ul style="list-style-type: none"> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul>

### Most important symptoms and effects, both acute and delayed

See Section 11

### Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

Treat symptomatically.

## SECTION 5 FIRE-FIGHTING MEASURES

### Extinguishing media

- ▶ Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Do not use a water jet to fight fire.

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

### Special protective equipment and precautions for fire-fighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat, flame and/or oxidisers.</li> <li>▶ Vapour forms an explosive mixture with air.</li> <li>▶ Severe explosion hazard, in the form of vapour, when exposed to flame or spark.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion / decomposition with violent rupture of containers.</li> </ul> <p>Combustion products include: carbon dioxide (CO<sub>2</sub>) other pyrolysis products typical of burning organic material.</p> <p><b>Contains low boiling substance:</b> Closed containers may rupture due to pressure buildup under fire conditions.</p>

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb small quantities with vermiculite or other absorbent material.</li> <li>▶ Wipe up.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> </ul>

Continued...

## Toro Black Bottle

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

## Precautions for safe handling

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> </ul> <p><b>Contains low boiling substance:</b> Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.</p> <ul style="list-style-type: none"> <li>▶ Check for bulging containers.</li> <li>▶ Vent periodically</li> <li>▶ Always release caps or seals slowly to ensure slow dissipation of vapours</li> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> </ul> <p>The tendency of many ethers to form explosive peroxides is well documented. Ethers lacking non-methyl hydrogen atoms adjacent to the ether link are thought to be relatively safe</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT concentrate by evaporation, or evaporate extracts to dryness, as residues may contain explosive peroxides with DETONATION potential.</b></li> <li>▶ Any static discharge is also a source of hazard.</li> <li>▶ Before any distillation process remove trace peroxides by shaking with excess 5% aqueous ferrous sulfate solution or by percolation through a column of activated alumina.</li> <li>▶ Distillation results in uninhibited ether distillate with considerably increased hazard because of risk of peroxide formation on storage.</li> <li>▶ Add inhibitor to any distillate as required.</li> <li>▶ Electrostatic discharge may be generated during pumping - this may result in fire.</li> <li>▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment.</li> <li>▶ Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<math>\leq 1</math> m/sec until fill pipe submerged to twice its diameter, then <math>\leq 7</math> m/sec).</li> <li>▶ Avoid splash filling.</li> <li>▶ Do NOT use compressed air for filling discharging or handling operations.</li> </ul> <p>The substance accumulates peroxides which may become hazardous only if it evaporates or is distilled or otherwise treated to concentrate the peroxides. The substance may concentrate around the container opening for example.</p> <p>Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised.</p> <ul style="list-style-type: none"> <li>▶ A responsible person should maintain an inventory of peroxidisable chemicals or annotate the general chemical inventory to indicate which chemicals are subject to peroxidation. An expiration date should be determined. The chemical should either be treated to remove peroxides or disposed of before this date.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights, heat or ignition sources.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers in approved flame-proof area.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store away from incompatible materials in a cool, dry well ventilated area.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> </ul>

## Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Packing as supplied by manufacturer.</li> <li>▶ Plastic containers may only be used if approved for flammable liquid.</li> <li>▶ Check that containers are clearly labelled and free from leaks.</li> <li>▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)</li> <li>▶ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)</li> <li>▶ Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.</li> <li>▶ Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages</li> <li>▶ In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.</li> <li>▶ Avoid reaction with oxidising agents</li> </ul> <p>Avoid contact with</p> <ul style="list-style-type: none"> <li>halogens</li> <li>amines</li> <li>isocyanates</li> <li>caustic compounds</li> </ul>

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

## Control parameters

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	toluene	Methyl benzene, Methyl benzol, Phenyl methane, Toluol	100 ppm / 375 mg/m <sup>3</sup>	560 mg/m <sup>3</sup> / 150 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	toluene	Toluene	20 ppm	Not Available	Not Available	TLV® Basis: Visual impair; female repro; pregnancy loss; BEI

## Toro Black Bottle

US OSHA Permissible Exposure Levels (PELs) - Table Z2	toluene	Toluene	200 ppm	Not Available	300 ppm	(Z37.12-1967)
US OSHA Permissible Exposure Levels (PELs) - Table Z1	toluene	Toluene	Not Available	Not Available	Not Available	See Table Z-2
US NIOSH Recommended Exposure Limits (RELs)	methyl ethyl ketone	Ethyl methyl ketone, MEK, Methyl acetone, Methyl ethyl ketone	200 ppm / 590 mg/m3	885 mg/m3 / 300 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	methyl ethyl ketone	Methyl ethyl ketone	200 ppm	300 ppm	Not Available	TLV® Basis: URT irr; CNS & PNS impair; BEI
US OSHA Permissible Exposure Levels (PELs) - Table Z1	methyl ethyl ketone	2-Butanone (Methyl ethyl ketone)	200 ppm / 590 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica amorphous	Diatomaceous earth, Diatomaceous silica, Diatomite, Precipitated amorphous silica, Silica gel, Silicon dioxide (amorphous)	6 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z3	silica amorphous	Amorphous	80 / (%SiO2) mg/m3 / 20 mppcf	Not Available	Not Available	(Name (including natural diatomaceous earth))
US OSHA Permissible Exposure Levels (PELs) - Table Z1	silica amorphous	Silica, amorphous, diatomaceous earth, containing less than 1% crystalline silica	Not Available	Not Available	Not Available	See Table Z-3
US OSHA Permissible Exposure Levels (PELs) - Table Z1	silica amorphous	Silica, fused, respirable dust	Not Available	Not Available	Not Available	See Table Z-3
US OSHA Permissible Exposure Levels (PELs) - Table Z1	silica amorphous	Silica, amorphous, precipitated and gel	Not Available	Not Available	Not Available	See Table Z-3
US ACGIH Threshold Limit Values (TLV)	xylene	Xylene (all isomers)	100 ppm	150 ppm	Not Available	TLV® Basis: URT & eye irr; CNS impair; BEI
US OSHA Permissible Exposure Levels (PELs) - Table Z1	xylene	Xylenes (o-, m-, p-isomers)	100 ppm / 435 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Acetylene black, Channel black, Furnace black, Lamp black, Thermal black	3.5 mg/m3	Not Available	Not Available	Ca See Appendix A See Appendix C
US ACGIH Threshold Limit Values (TLV)	carbon black	Carbon black	3 mg/m3	Not Available	Not Available	TLV® Basis: Bronchitis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	ethylbenzene	Ethylbenzol, Phenylethane	100 ppm / 435 mg/m3	545 mg/m3 / 125 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ethylbenzene	Ethyl benzene	20 ppm	Not Available	Not Available	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair; BEI
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ethylbenzene	Ethyl benzene	100 ppm / 435 mg/m3	Not Available	Not Available	Not Available

## EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
toluene	Toluene	Not Available	Not Available	Not Available
methyl ethyl ketone	Butanone, 2-; (Methyl ethyl ketone; MEK)	Not Available	Not Available	Not Available
propylene glycol monomethyl ether acetate, alpha-isomer	Propylene glycol monomethyl ether acetate, alpha-isomer; (1-Methoxypropyl-2-acetate)	Not Available	Not Available	Not Available
propylene glycol monomethyl ether acetate, alpha-isomer	Propylene glycol monomethyl ether acetate, beta-isomer; (2-Methoxypropyl-1-acetate)	Not Available	Not Available	Not Available
silica amorphous	Silica gel, amorphous synthetic	18 mg/m3	200 mg/m3	1,200 mg/m3
silica amorphous	Silica, amorphous fumed	18 mg/m3	100 mg/m3	630 mg/m3
silica amorphous	Siloxanes and silicones, dimethyl, reaction products with silica; (Hydrophobic silicon dioxide, amorphous)	120 mg/m3	1,300 mg/m3	7,900 mg/m3
silica amorphous	Silica, amorphous fume	45 mg/m3	500 mg/m3	3,000 mg/m3
silica amorphous	Silica amorphous hydrated	18 mg/m3	220 mg/m3	1,300 mg/m3
xylene	Xylenes	Not Available	Not Available	Not Available
carbon black	Carbon black	9 mg/m3	99 mg/m3	590 mg/m3
ethylbenzene	Ethyl benzene	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
toluene	500 ppm	Not Available
methyl ethyl ketone	3,000 ppm	Not Available
propylene glycol monomethyl ether acetate, alpha-isomer	Not Available	Not Available
silica amorphous	3,000 mg/m3	Not Available
xylene	900 ppm	Not Available

## Toro Black Bottle

carbon black	1,750 mg/m <sup>3</sup>	Not Available
ethylbenzene	800 ppm	Not Available

## Exposure controls

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p>
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.</p>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Ensure there is ready access to a safety shower.</li> <li>▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot and shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn.</li> </ul>

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Toro Black Bottle

Material	CPI
BUTYL	C
BUTYL/NEOPRENE	C
CPE	C
HYPALON	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PE/EVAL/PE	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
SARANEX-23 2-PLY	C
TEFLON	C

## Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS	-	A-PAPR-AUS / Class 1
up to 50 x ES	-	A-AUS / Class 1	-
up to 100 x ES	-	A-2	A-PAPR-2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Continued...

VITON	C
VITON/CHLOROBUTYL	C
VITON/NEOPRENE	C
##methyl ethyl	ketone

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Appearance</b>	Flammable liquid.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	0.95
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	404
<b>pH (as supplied)</b>	Not Applicable	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	-94.9	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	79.59	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	-9	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	HIGHLY FLAMMABLE.	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	10	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	1.3	<b>Volatile Component (%vol)</b>	71.78
<b>Vapour pressure (kPa)</b>	4.921	<b>Gas group</b>	Not Available
<b>Solubility in water (g/L)</b>	Not Available	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available

## SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

<b>Inhaled</b>	<p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p>
<b>Ingestion</b>	<p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p>
<b>Skin Contact</b>	<p>The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p> <p>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>

## Toro Black Bottle

Eye	<p>There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.</p> <p>The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated.</p>											
Chronic	<p>Harmful: danger of serious damage to health by prolonged exposure through inhalation. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Based on experience with animal studies, exposure to the material may result in toxic effects to the development of the foetus, at levels which do not cause significant toxic effects to the mother.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>5540(3)I</p> <p>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.</p>											
Toro Black Bottle	<table border="1"> <thead> <tr> <th data-bbox="368 510 938 555">TOXICITY</th> </tr> </thead> <tbody> <tr> <td data-bbox="368 555 938 607">Not Available</td> </tr> </tbody> </table>	TOXICITY	Not Available	<table border="1"> <thead> <tr> <th data-bbox="938 510 1489 555">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="938 555 1489 607">Not Available</td> </tr> </tbody> </table>	IRRITATION	Not Available						
TOXICITY												
Not Available												
IRRITATION												
Not Available												
toluene	<table border="1"> <thead> <tr> <th data-bbox="368 607 938 651">TOXICITY</th> </tr> </thead> <tbody> <tr> <td data-bbox="368 651 938 685">Dermal (rabbit) LD50: 12124 mg/kg<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 685 938 719">Inhalation (rat) LC50: 49 mg/l/4h<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 719 938 752">Oral (rat) LD50: 636 mg/kg<sup>[2]</sup></td> </tr> </tbody> </table>	TOXICITY	Dermal (rabbit) LD50: 12124 mg/kg <sup>[2]</sup>	Inhalation (rat) LC50: 49 mg/l/4h <sup>[2]</sup>	Oral (rat) LD50: 636 mg/kg <sup>[2]</sup>	<table border="1"> <thead> <tr> <th data-bbox="938 607 1489 651">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="938 651 1489 685">Eye (rabbit): 2mg/24h - SEVERE</td> </tr> <tr> <td data-bbox="938 685 1489 719">Eye (rabbit):0.87 mg - mild</td> </tr> <tr> <td data-bbox="938 719 1489 752">Eye (rabbit):100 mg/30sec - mild</td> </tr> <tr> <td data-bbox="938 752 1489 786">Skin (rabbit):20 mg/24h-moderate</td> </tr> <tr> <td data-bbox="938 786 1489 846">Skin (rabbit):500 mg - moderate</td> </tr> </tbody> </table>	IRRITATION	Eye (rabbit): 2mg/24h - SEVERE	Eye (rabbit):0.87 mg - mild	Eye (rabbit):100 mg/30sec - mild	Skin (rabbit):20 mg/24h-moderate	Skin (rabbit):500 mg - moderate
TOXICITY												
Dermal (rabbit) LD50: 12124 mg/kg <sup>[2]</sup>												
Inhalation (rat) LC50: 49 mg/l/4h <sup>[2]</sup>												
Oral (rat) LD50: 636 mg/kg <sup>[2]</sup>												
IRRITATION												
Eye (rabbit): 2mg/24h - SEVERE												
Eye (rabbit):0.87 mg - mild												
Eye (rabbit):100 mg/30sec - mild												
Skin (rabbit):20 mg/24h-moderate												
Skin (rabbit):500 mg - moderate												
methyl ethyl ketone	<table border="1"> <thead> <tr> <th data-bbox="368 846 938 891">TOXICITY</th> </tr> </thead> <tbody> <tr> <td data-bbox="368 891 938 925">Dermal (rabbit) LD50: 6480 mg/kg<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 925 938 958">Inhalation (rat) LC50: 47 mg/l/8h<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 958 938 992">Oral (rat) LD50: 2054 mg/kg<sup>[1]</sup></td> </tr> </tbody> </table>	TOXICITY	Dermal (rabbit) LD50: 6480 mg/kg <sup>[2]</sup>	Inhalation (rat) LC50: 47 mg/l/8h <sup>[2]</sup>	Oral (rat) LD50: 2054 mg/kg <sup>[1]</sup>	<table border="1"> <thead> <tr> <th data-bbox="938 846 1489 891">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="938 891 1489 925">Eye (human): 350 ppm -irritant</td> </tr> <tr> <td data-bbox="938 925 1489 958">Eye (rabbit): 80 mg - irritant</td> </tr> <tr> <td data-bbox="938 958 1489 992">Skin (rabbit): 402 mg/24 hr - mild</td> </tr> <tr> <td data-bbox="938 992 1489 1048">Skin (rabbit):13.78mg/24 hr open</td> </tr> </tbody> </table>	IRRITATION	Eye (human): 350 ppm -irritant	Eye (rabbit): 80 mg - irritant	Skin (rabbit): 402 mg/24 hr - mild	Skin (rabbit):13.78mg/24 hr open	
TOXICITY												
Dermal (rabbit) LD50: 6480 mg/kg <sup>[2]</sup>												
Inhalation (rat) LC50: 47 mg/l/8h <sup>[2]</sup>												
Oral (rat) LD50: 2054 mg/kg <sup>[1]</sup>												
IRRITATION												
Eye (human): 350 ppm -irritant												
Eye (rabbit): 80 mg - irritant												
Skin (rabbit): 402 mg/24 hr - mild												
Skin (rabbit):13.78mg/24 hr open												
propylene glycol monomethyl ether acetate, alpha-isomer	<table border="1"> <thead> <tr> <th data-bbox="368 1048 938 1093">TOXICITY</th> </tr> </thead> <tbody> <tr> <td data-bbox="368 1093 938 1126">dermal (rat) LD50: &gt;2000 mg/kg<sup>[1]</sup></td> </tr> <tr> <td data-bbox="368 1126 938 1160">Inhalation (rat) LC50: 6510.0635325 mg/l/6h<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 1160 938 1227">Oral (rat) LD50: &gt;5000 mg/kg<sup>[1]</sup></td> </tr> </tbody> </table>	TOXICITY	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Inhalation (rat) LC50: 6510.0635325 mg/l/6h <sup>[2]</sup>	Oral (rat) LD50: >5000 mg/kg <sup>[1]</sup>	<table border="1"> <thead> <tr> <th data-bbox="938 1048 1489 1093">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="938 1093 1489 1227">Not Available</td> </tr> </tbody> </table>	IRRITATION	Not Available				
TOXICITY												
dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>												
Inhalation (rat) LC50: 6510.0635325 mg/l/6h <sup>[2]</sup>												
Oral (rat) LD50: >5000 mg/kg <sup>[1]</sup>												
IRRITATION												
Not Available												
silica amorphous	<table border="1"> <thead> <tr> <th data-bbox="368 1227 938 1272">TOXICITY</th> </tr> </thead> <tbody> <tr> <td data-bbox="368 1272 938 1305">Dermal (rabbit) LD50: &gt;5000 mg/kg<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 1305 938 1339">Inhalation (rat) LC50: &gt;0.139 mg/l/14h*[Grace]<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 1339 938 1406">Oral (rat) LD50: 3160 mg/kg<sup>[2]</sup></td> </tr> </tbody> </table>	TOXICITY	Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>	Inhalation (rat) LC50: >0.139 mg/l/14h*[Grace] <sup>[2]</sup>	Oral (rat) LD50: 3160 mg/kg <sup>[2]</sup>	<table border="1"> <thead> <tr> <th data-bbox="938 1227 1489 1272">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="938 1272 1489 1305">Eye (rabbit): non-irritating *</td> </tr> <tr> <td data-bbox="938 1305 1489 1406">Skin (rabbit): non-irritating *</td> </tr> </tbody> </table>	IRRITATION	Eye (rabbit): non-irritating *	Skin (rabbit): non-irritating *			
TOXICITY												
Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>												
Inhalation (rat) LC50: >0.139 mg/l/14h*[Grace] <sup>[2]</sup>												
Oral (rat) LD50: 3160 mg/kg <sup>[2]</sup>												
IRRITATION												
Eye (rabbit): non-irritating *												
Skin (rabbit): non-irritating *												
xylene	<table border="1"> <thead> <tr> <th data-bbox="368 1406 938 1451">TOXICITY</th> </tr> </thead> <tbody> <tr> <td data-bbox="368 1451 938 1485">Dermal (rabbit) LD50: &gt;1700 mg/kg<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 1485 938 1518">Inhalation (rat) LC50: 4994.295 mg/l/4h<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 1518 938 1608">Oral (rat) LD50: 4300 mg/kg<sup>[2]</sup></td> </tr> </tbody> </table>	TOXICITY	Dermal (rabbit) LD50: >1700 mg/kg <sup>[2]</sup>	Inhalation (rat) LC50: 4994.295 mg/l/4h <sup>[2]</sup>	Oral (rat) LD50: 4300 mg/kg <sup>[2]</sup>	<table border="1"> <thead> <tr> <th data-bbox="938 1406 1489 1451">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="938 1451 1489 1485">Eye (human): 200 ppm irritant</td> </tr> <tr> <td data-bbox="938 1485 1489 1518">Eye (rabbit): 5 mg/24h SEVERE</td> </tr> <tr> <td data-bbox="938 1518 1489 1552">Eye (rabbit): 87 mg mild</td> </tr> <tr> <td data-bbox="938 1552 1489 1608">Skin (rabbit):500 mg/24h moderate</td> </tr> </tbody> </table>	IRRITATION	Eye (human): 200 ppm irritant	Eye (rabbit): 5 mg/24h SEVERE	Eye (rabbit): 87 mg mild	Skin (rabbit):500 mg/24h moderate	
TOXICITY												
Dermal (rabbit) LD50: >1700 mg/kg <sup>[2]</sup>												
Inhalation (rat) LC50: 4994.295 mg/l/4h <sup>[2]</sup>												
Oral (rat) LD50: 4300 mg/kg <sup>[2]</sup>												
IRRITATION												
Eye (human): 200 ppm irritant												
Eye (rabbit): 5 mg/24h SEVERE												
Eye (rabbit): 87 mg mild												
Skin (rabbit):500 mg/24h moderate												
carbon black	<table border="1"> <thead> <tr> <th data-bbox="368 1608 938 1653">TOXICITY</th> </tr> </thead> <tbody> <tr> <td data-bbox="368 1653 938 1686">Dermal (rabbit) LD50: &gt;3000 mg/kg<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 1686 938 1742">Oral (rat) LD50: &gt;10000 mg/kg<sup>[1]</sup></td> </tr> </tbody> </table>	TOXICITY	Dermal (rabbit) LD50: >3000 mg/kg <sup>[2]</sup>	Oral (rat) LD50: >10000 mg/kg <sup>[1]</sup>	<table border="1"> <thead> <tr> <th data-bbox="938 1608 1489 1653">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="938 1653 1489 1742">Not Available</td> </tr> </tbody> </table>	IRRITATION	Not Available					
TOXICITY												
Dermal (rabbit) LD50: >3000 mg/kg <sup>[2]</sup>												
Oral (rat) LD50: >10000 mg/kg <sup>[1]</sup>												
IRRITATION												
Not Available												
ethylbenzene	<table border="1"> <thead> <tr> <th data-bbox="368 1742 938 1787">TOXICITY</th> </tr> </thead> <tbody> <tr> <td data-bbox="368 1787 938 1821">Dermal (rabbit) LD50: &gt;5000 mg/kg<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 1821 938 1854">Inhalation (mouse) LC50: 17.75 mg/l/2h<sup>[2]</sup></td> </tr> <tr> <td data-bbox="368 1854 938 1897">Oral (rat) LD50: 3500 mg/kg<sup>[2]</sup></td> </tr> </tbody> </table>	TOXICITY	Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>	Inhalation (mouse) LC50: 17.75 mg/l/2h <sup>[2]</sup>	Oral (rat) LD50: 3500 mg/kg <sup>[2]</sup>	<table border="1"> <thead> <tr> <th data-bbox="938 1742 1489 1787">IRRITATION</th> </tr> </thead> <tbody> <tr> <td data-bbox="938 1787 1489 1821">Eye (rabbit): 500 mg - SEVERE</td> </tr> <tr> <td data-bbox="938 1821 1489 1897">Skin (rabbit): 15 mg/24h mild</td> </tr> </tbody> </table>	IRRITATION	Eye (rabbit): 500 mg - SEVERE	Skin (rabbit): 15 mg/24h mild			
TOXICITY												
Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>												
Inhalation (mouse) LC50: 17.75 mg/l/2h <sup>[2]</sup>												
Oral (rat) LD50: 3500 mg/kg <sup>[2]</sup>												
IRRITATION												
Eye (rabbit): 500 mg - SEVERE												
Skin (rabbit): 15 mg/24h mild												

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

**TOLUENE**

For toluene:  
 Acute toxicity: Humans exposed to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis (sleepiness) and death. When inhaled or swallowed, toluene can cause severe central nervous system depression, and in large doses has a narcotic effect. 60mL has caused death. Death of heart muscle fibres, liver swelling, congestion and bleeding of the lungs and kidney injury were all found on autopsy.  
 Exposure to inhalation at a concentration of 600 parts per million for 8 hours resulted in the same and more serious symptoms including euphoria (a feeling

	of well-being), dilated pupils, convulsions and nausea. Exposure to 10000-30000 parts per million (1-3%) has been reported to cause narcosis and death.
<b>METHYL ETHYL KETONE</b>	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases.</p> <p>Methyl ethyl ketone is considered to have a low order of toxicity; however, methyl ethyl ketone is often used in combination with other solvents and the mixture may have greater toxicity than either solvent alone. Combinations of n-hexane with methyl ethyl ketone, and also methyl n-butyl ketone with methyl ethyl ketone may result in an increased in peripheral neuropathy, a progressive disorder of the nerves of the extremities. Combinations with chloroform also show an increase in toxicity.</p>
<b>PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE, ALPHA-ISOMER</b>	<p>For propylene glycol ethers (PGEs):</p> <p>Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA) and tripropylene glycol methyl ether (TPM).</p> <p>Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on the reproductive organs, the developing embryo and foetus, blood or thymus gland, are not seen with the commercial-grade propylene glycol ethers. In the ethylene series, metabolism of the terminal hydroxyl group produces and alkoxyacetic acid. The reproductive and developmental toxicities of the lower molecular weight homologues in the ethylene series are due specifically to the formation of methoxyacetic and ethoxyacetic acids.</p> <p>Longer chain homologues in the ethylene series are not associated with reproductive toxicity, but can cause haemolysis in sensitive species, also through formation of an alkoxyacetic acid.</p> <p>Animal testing shows that high concentrations (for example, 0.5%) are associated with birth defects but lower exposures have not been shown to cause adverse effects.</p> <p>The beta isomer of PGMEA comprises only 10% of the commercial material; the remaining 90% is alpha isomer. Hazard appears low, but emphasizes the need for care in handling this chemical.</p> <p>A BASF report (in ECETOC ) showed that inhalation exposure to 545 ppm PGMEA (beta isomer) was associated with a teratogenic response in rabbits; but exposure to 145 ppm and 36 ppm had no adverse effects. The beta isomer of PGMEA comprises only 10% of the commercial material, the remaining 90% is alpha isomer. Hazard appears low but emphasizes the need for care in handling this chemical. [I.C.I] *Shin-Etsu SDS</p>
<b>SILICA AMORPHOUS</b>	<p>For silica amorphous:</p> <p>When experimental animals inhale synthetic amorphous silica (SAS) dust, it dissolves in the lung fluid and is rapidly eliminated. If swallowed, the vast majority of SAS is excreted in the faeces and there is little accumulation in the body. Following absorption across the gut, SAS is eliminated via urine without modification in animals and humans. SAS is not expected to be broken down (metabolised) in mammals.</p> <p>After ingestion, there is limited accumulation of SAS in body tissues and rapid elimination occurs. Intestinal absorption has not been calculated, but appears to be insignificant in animals and humans.</p> <p>Reports indicate high/prolonged exposures to amorphous silicas induced lung fibrosis in experimental animals; in some experiments these effects were reversible. [PATTYS]</p>
<b>XYLENE</b>	Reproductive effector in rats
<b>CARBON BLACK</b>	No significant acute toxicological data identified in literature search. Inhalation (rat) TCLo: 50 mg/m <sup>3</sup> /6h/90D-I Nil reported
<b>ETHYLBENZENE</b>	<p>Ethylbenzene is readily absorbed when inhaled, swallowed or in contact with the skin. It is distributed throughout the body, and passed out through urine. It may irritate the skin, eyes and may cause hearing loss if exposed to high doses. Long Term exposure may cause damage to the kidney, liver and lungs, including a tendency to cancer formation, according to animal testing. There is no research on its effect on sex organs and unborn babies.</p> <p><b>NOTE:</b> Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.</p> <p>Liver changes, uterine tract, effects on fertility, foetotoxicity, specific developmental abnormalities (musculoskeletal system) recorded.</p>
<b>TOLUENE &amp; METHYL ETHYL KETONE &amp; XYLENE &amp; ETHYLBENZENE</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
<b>SILICA AMORPHOUS &amp; XYLENE</b>	<p>The substance is classified by IARC as Group 3:</p> <p><b>NOT</b> classifiable as to its carcinogenicity to humans.</p> <p>Evidence of carcinogenicity may be inadequate or limited in animal testing.</p>
<b>XYLENE &amp; ETHYLBENZENE</b>	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
<b>CARBON BLACK &amp; ETHYLBENZENE</b>	<b>WARNING:</b> This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

<b>Acute Toxicity</b>	✓	<b>Carcinogenicity</b>	⊘
<b>Skin Irritation/Corrosion</b>	✓	<b>Reproductivity</b>	✓
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT - Single Exposure</b>	✓
<b>Respiratory or Skin sensitisation</b>	⊘	<b>STOT - Repeated Exposure</b>	✓
<b>Mutagenicity</b>	⊘	<b>Aspiration Hazard</b>	✓

**Legend:** ✗ – Data available but does not fill the criteria for classification  
✓ – Data available to make classification  
⊘ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

### Toxicity

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
<b>Toro Black Bottle</b>	Not Available	Not Available	Not Available	Not Available	Not Available

**Toro Black Bottle**

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
toluene	LC50	96	Fish	0.0073mg/L	4
	EC50	48	Crustacea	3.78mg/L	5
	EC50	72	Algae or other aquatic plants	12.5mg/L	4
	BCF	24	Algae or other aquatic plants	10mg/L	4
	NOEC	168	Crustacea	0.74mg/L	5
methyl ethyl ketone	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>400mg/L	4
	EC50	48	Crustacea	308mg/L	2
	EC50	96	Algae or other aquatic plants	>500mg/L	4
propylene glycol monomethyl ether acetate, alpha-isomer	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	=100mg/L	1
	EC50	48	Crustacea	=408mg/L	1
	EC0	24	Crustacea	=500mg/L	1
silica amorphous	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	ca.2000mg/L	1
	EC50	48	Crustacea	ca.7600mg/L	1
	EC50	72	Algae or other aquatic plants	440mg/L	1
	EC10	72	Algae or other aquatic plants	140mg/L	1
xylene	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	2.6mg/L	2
	EC50	48	Crustacea	>3.4mg/L	2
	EC50	72	Algae or other aquatic plants	4.6mg/L	2
carbon black	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	=1000mg/L	1
ethylbenzene	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	NOEC	96	Fish	=1000mg/L	1
	LC50	96	Fish	0.0043mg/L	4
	EC50	48	Crustacea	1.184mg/L	4
	EC50	96	Algae or other aquatic plants	3.6mg/L	4
	NOEC	168	Crustacea	0.96mg/L	5

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

**Persistence and degradability**

Ingredient	Persistence: Water/Soil	Persistence: Air
toluene	LOW (Half-life = 28 days)	LOW (Half-life = 4.33 days)
methyl ethyl ketone	LOW (Half-life = 14 days)	LOW (Half-life = 26.75 days)
propylene glycol monomethyl ether acetate, alpha-isomer	LOW	LOW
silica amorphous	LOW	LOW
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)

**Bioaccumulative potential**

Ingredient	Bioaccumulation
toluene	LOW (BCF = 90)
methyl ethyl ketone	LOW (LogKOW = 0.29)

Continued...

propylene glycol monomethyl ether acetate, alpha-isomer	LOW (LogKOW = 0.56)
silica amorphous	LOW (LogKOW = 0.5294)
xylene	MEDIUM (BCF = 740)
ethylbenzene	LOW (BCF = 79.43)

**Mobility in soil**

Ingredient	Mobility
toluene	LOW (KOC = 268)
methyl ethyl ketone	MEDIUM (KOC = 3.827)
propylene glycol monomethyl ether acetate, alpha-isomer	HIGH (KOC = 1.838)
silica amorphous	LOW (KOC = 23.74)
ethylbenzene	LOW (KOC = 517.8)

**SECTION 13 DISPOSAL CONSIDERATIONS****Waste treatment methods**

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul>
-------------------------------------	--

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

<b>Marine Pollutant</b>	
	NO

**Land transport (DOT)**

<b>UN number</b>	1263				
<b>UN proper shipping name</b>	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base; Paint related material including paint thinning, drying, removing, or reducing compound				
<b>Transport hazard class(es)</b>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="border-right: 1px dashed black; padding-right: 5px;">Class</td> <td style="padding-left: 5px;">3</td> </tr> <tr> <td style="border-right: 1px dashed black; padding-right: 5px;">Subrisk</td> <td style="padding-left: 5px;">Not Applicable</td> </tr> </table>	Class	3	Subrisk	Not Applicable
Class	3				
Subrisk	Not Applicable				
<b>Packing group</b>	I				
<b>Environmental hazard</b>	Not Applicable				
<b>Special precautions for user</b>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="border-right: 1px dashed black; padding-right: 5px;">Hazard Label</td> <td style="padding-left: 5px;">3</td> </tr> <tr> <td style="border-right: 1px dashed black; padding-right: 5px;">Special provisions</td> <td style="padding-left: 5px;">367, T11, TP1, TP8, TP27</td> </tr> </table>	Hazard Label	3	Special provisions	367, T11, TP1, TP8, TP27
Hazard Label	3				
Special provisions	367, T11, TP1, TP8, TP27				

**Air transport (ICAO-IATA / DGR)**

<b>UN number</b>	1263
------------------	------

<b>UN proper shipping name</b>	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds)	
<b>Transport hazard class(es)</b>	ICAO/IATA Class	3
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	3L
<b>Packing group</b>	I	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	Special provisions	A3 A72 A192
	Cargo Only Packing Instructions	361
	Cargo Only Maximum Qty / Pack	30 L
	Passenger and Cargo Packing Instructions	351
	Passenger and Cargo Maximum Qty / Pack	1 L
	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden

**Sea transport (IMDG-Code / GGVSee)**

<b>UN number</b>	1263	
<b>UN proper shipping name</b>	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)	
<b>Transport hazard class(es)</b>	IMDG Class	3
	IMDG Subrisk	Not Applicable
<b>Packing group</b>	I	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	EMS Number	F-E , S-E
	Special provisions	163 367
	Limited Quantities	500 mL

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture****TOLUENE(108-88-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Washington Permissible exposure limits of air contaminants
US - Alaska Limits for Air Contaminants	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - California - Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration, Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)	US ACGIH Threshold Limit Values (TLV)
US - California Permissible Exposure Limits for Chemical Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - California Proposition 65 - Reproductive Toxicity	US Clean Air Act - Hazardous Air Pollutants
US - Hawaii Air Contaminant Limits	US CWA (Clean Water Act) - List of Hazardous Substances
US - Idaho - Acceptable Maximum Peak Concentrations	US CWA (Clean Water Act) - Priority Pollutants
US - Idaho - Limits for Air Contaminants	US CWA (Clean Water Act) - Toxic Pollutants
US - Massachusetts - Right To Know Listed Chemicals	US Drug Enforcement Administration (DEA) List I and II Regulated Chemicals
US - Michigan Exposure Limits for Air Contaminants	US EPA Carcinogens Listing
US - Minnesota Permissible Exposure Limits (PELs)	US EPCRA Section 313 Chemical List
US - Oregon Permissible Exposure Limits (Z-1)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-2)	US Office of Environmental Health Hazard Assessment Proposition 65 No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Rhode Island Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z2
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances

**METHYL ETHYL KETONE(78-93-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

US - Alaska Limits for Air Contaminants  
 US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELS)  
 US - California Permissible Exposure Limits for Chemical Contaminants  
 US - Hawaii Air Contaminant Limits  
 US - Idaho - Limits for Air Contaminants  
 US - Massachusetts - Right To Know Listed Chemicals  
 US - Michigan Exposure Limits for Air Contaminants  
 US - Pennsylvania - Hazardous Substance List  
 US - Rhode Island Hazardous Substance List  
 US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants  
 US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants  
 US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants

US - Washington Permissible exposure limits of air contaminants  
 US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values  
 US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants  
 US ACGIH Threshold Limit Values (TLV)  
 US Drug Enforcement Administration (DEA) List I and II Regulated Chemicals  
 US EPA Carcinogens Listing  
 US NIOSH Recommended Exposure Limits (RELS)  
 US OSHA Permissible Exposure Levels (PELs) - Table Z1  
 US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE, ALPHA-ISOMER(108-65-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELS)  
 US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)  
 US - California Permissible Exposure Limits for Chemical Contaminants  
 US - Pennsylvania - Hazardous Substance List  
 US AIHA Workplace Environmental Exposure Levels (WEELs)

US Clean Air Act - Hazardous Air Pollutants  
 US EPCRA Section 313 Chemical List  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### SILICA AMORPHOUS(7631-86-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 US - Alaska Limits for Air Contaminants  
 US - California Permissible Exposure Limits for Chemical Contaminants  
 US - Hawaii Air Contaminant Limits  
 US - Idaho - Limits for Air Contaminants  
 US - Idaho - Toxic and Hazardous Substances - Mineral Dust  
 US - Massachusetts - Right To Know Listed Chemicals  
 US - Michigan Exposure Limits for Air Contaminants  
 US - Minnesota Permissible Exposure Limits (PELs)  
 US - Oregon Permissible Exposure Limits (Z-1)  
 US - Oregon Permissible Exposure Limits (Z-3)  
 US - Pennsylvania - Hazardous Substance List  
 US - Rhode Island Hazardous Substance List

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants  
 US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants  
 US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants  
 US - Washington Permissible exposure limits of air contaminants  
 US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values  
 US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants  
 US - Wyoming Toxic and Hazardous Substances Table Z-3 Mineral Dusts  
 US NIOSH Recommended Exposure Limits (RELS)  
 US OSHA Permissible Exposure Levels (PELs) - Table Z1  
 US OSHA Permissible Exposure Levels (PELs) - Table Z3  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### XYLENE(1330-20-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 US - Alaska Limits for Air Contaminants  
 US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELS)  
 US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)  
 US - California Permissible Exposure Limits for Chemical Contaminants  
 US - Hawaii Air Contaminant Limits  
 US - Idaho - Limits for Air Contaminants  
 US - Massachusetts - Right To Know Listed Chemicals  
 US - Michigan Exposure Limits for Air Contaminants  
 US - Minnesota Permissible Exposure Limits (PELs)  
 US - Oregon Permissible Exposure Limits (Z-1)  
 US - Pennsylvania - Hazardous Substance List  
 US - Rhode Island Hazardous Substance List  
 US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants  
 US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants  
 US - Washington Permissible exposure limits of air contaminants  
 US ACGIH Threshold Limit Values (TLV)  
 US ACGIH Threshold Limit Values (TLV) - Carcinogens  
 US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)  
 US Clean Air Act - Hazardous Air Pollutants  
 US CWA (Clean Water Act) - List of Hazardous Substances  
 US EPA Carcinogens Listing  
 US EPCRA Section 313 Chemical List  
 US OSHA Permissible Exposure Levels (PELs) - Table Z1  
 US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### CARBON BLACK(1333-86-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 US - Alaska Limits for Air Contaminants  
 US - California Permissible Exposure Limits for Chemical Contaminants  
 US - California Proposition 65 - Carcinogens  
 US - Hawaii Air Contaminant Limits  
 US - Idaho - Limits for Air Contaminants  
 US - Massachusetts - Right To Know Listed Chemicals  
 US - Michigan Exposure Limits for Air Contaminants  
 US - Minnesota Permissible Exposure Limits (PELs)  
 US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Carcinogens  
 US - Oregon Permissible Exposure Limits (Z-1)  
 US - Pennsylvania - Hazardous Substance List

US - Rhode Island Hazardous Substance List  
 US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants  
 US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants  
 US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants  
 US - Washington Permissible exposure limits of air contaminants  
 US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants  
 US ACGIH Threshold Limit Values (TLV)  
 US ACGIH Threshold Limit Values (TLV) - Carcinogens  
 US NIOSH Recommended Exposure Limits (RELS)  
 US OSHA Permissible Exposure Levels (PELs) - Table Z1  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### ETHYLBENZENE(100-41-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Washington Permissible exposure limits of air contaminants
US - Alaska Limits for Air Contaminants	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - California - Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)	US ACGIH Threshold Limit Values (TLV)
US - California Permissible Exposure Limits for Chemical Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - California Proposition 65 - Carcinogens	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens	US Clean Air Act - Hazardous Air Pollutants
US - Hawaii Air Contaminant Limits	US CWA (Clean Water Act) - List of Hazardous Substances
US - Idaho - Limits for Air Contaminants	US CWA (Clean Water Act) - Priority Pollutants
US - Massachusetts - Right To Know Listed Chemicals	US CWA (Clean Water Act) - Toxic Pollutants
US - Michigan Exposure Limits for Air Contaminants	US EPA Carcinogens Listing
US - Minnesota Permissible Exposure Limits (PELs)	US EPCRA Section 313 Chemical List
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Carcinogens	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-1)	US Office of Environmental Health Hazard Assessment Proposition 65 No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Rhode Island Hazardous Substance List	US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	

## Federal Regulations

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	Yes
Reproductive toxicity	Yes
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	Yes
Germ cell mutagenicity	No
Simple Asphyxiant	No

#### US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Benzene, methyl-	1000	454
2-Butanone	5000	2270
Ethyl methyl ketone	5000	2270
Xylene (mixed)	100	45.4
Ethylbenzene	1000	454

## State Regulations

### US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

### US - CALIFORNIA PROPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Toluene, Carbon black (airborne, unbound particles of respirable size), Ethylbenzene Listed

## National Inventory Status

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (toluene; propylene glycol monomethyl ether acetate, alpha-isomer; xylene; ethylbenzene; carbon black; methyl ethyl ketone)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
<b>Legend:</b>	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

## SECTION 16 OTHER INFORMATION

<b>Revision Date</b>	02/12/2016
<b>Initial Date</b>	Not Available

### Other information

#### Ingredients with multiple cas numbers

Name	CAS No
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6, 84540-57-8, 142300-82-1
silica amorphous	7631-86-9, 112945-52-5, 67762-90-7, 68611-44-9, 68909-20-6, 112926-00-8, 61790-53-2, 60676-86-0, 91053-39-3, 69012-64-2, 844491-94-7

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average  
 PC – STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit,  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.