

Toro Premium ATF

The Toro Company

Chemwatch: 5198-50 Version No: 2.1.1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 16/12/2015 Print Date: 05/10/2018 S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Toro Premium ATF
Synonyms	Not Available
Other means of identification	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses

Transmission fluid.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	The Toro Company
Address	8111 Lyndale Avenue South, Bloomington MN 55420 United States
Telephone	+1-952-888-8801
Fax	+1-952-887-8258
Website	www.toro.com
Email	HealthAndSafety@toro.com


Emergency phone number

Association / Organisation	CHEMTEL
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	+1-813-248-0585

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

CHEMWATCH HAZARD RATINGS





Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Skin Sensitizer Category 1

0 = Minimum1 = Low 2 = Moderate 3 = High 4 = Extreme

Label elements

Hazard pictogram(s)



SIGNAL WORD

WARNING

Hazard statement(s)

H317

May cause an allergic skin reaction.

Hazard(s) not otherwise specified

Not Applicable

Chemwatch: **5198-50**Version No: **2.1.1.1**Toro Promium

Toro Premium ATF

Issue Date: **16/12/2015** Print Date: **05/10/2018**

Precautionary statement(s) Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P261	Avoid breathing mist/vapours/spray.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

P363	Wash contaminated clothing before reuse.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name		
64742-56-9.	70-<80	paraffinic distillate, light, solvent-dewaxed (severe)		
36878-20-3	1-<5	nonylated diphenylamines		
67124-09-8	1-2.5	1-(tert-dodecylthio)-2-propanol		
27136-73-8	0.1-<1	2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol		
122-39-4	0.1-<1	<u>diphenylamine</u>		
61791-44-4	0.1-<0.25	tallow alkyl-diethanolamine derivatives		

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If furnes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- ▶ High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

Page 3 of 10

Toro Premium ATF

Issue Date: **16/12/2015**Print Date: **05/10/2018**

- Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide
- ▶ Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ► Wear full body protective clothing with breathing apparatus.
- ▶ Prevent, by any means available, spillage from entering drains or water course
- ▶ Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- ▶ DO NOT approach containers suspected to be hot.

Combustible.

- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).
- Mav emit acrid smoke.
- ► Mists containing combustible materials may be explosive.

Fire/Explosion Hazard

Combustion products include:

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes

May emit corrosive fumes

CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills

Slippery when spilt.

- ▶ Remove all ignition sources
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
 - Control personal contact with the substance, by using protective equipment.
 - · Contain and absorb spill with sand, earth, inert material or vermiculite.
- ▶ Wipe up.

Maior Spills

Slippery when spilt. Moderate hazard.

- Clear area of personnel and move upwind.
- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course
- ▶ No smoking, naked lights or ignition sources.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- ► Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- ▶ DO NOT enter confined spaces until atmosphere has been checked
- Avoid smoking, naked lights or ignition sources.

Other information

- Store in original containers.Keep containers securely sealed.
- ▶ No smoking, naked lights or ignition sources.
- Store in a cool, drv. well-ventilated area.
- ► Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.

Conditions for safe storage, including any incompatibilities

Suitable container

- ► Metal can or drum
 - Packaging as recommended by manufacturer.
 - Check all containers are clearly labelled and free from leaks.

Storage incompatibility

- ► Avoid reaction with oxidising agents
- Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

Page 4 of 10

Toro Premium ATF

Issue Date: 16/12/2015 Print Date: 05/10/2018

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	paraffinic distillate, light, solvent-dewaxed (severe)	Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist	5 mg/m3	10 mg/m3	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	paraffinic distillate, light, solvent-dewaxed (severe)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT
US OSHA Permissible Exposure Levels (PELs) - Table Z1	paraffinic distillate, light, solvent-dewaxed (severe)	Oil mist, mineral	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	diphenylamine	Anilinobenzene, DPA, Phenylaniline, N-Phenylaniline, N-Phenylbenzenamine [Note: The carcinogen 4-Aminodiphenyl may be present as an impurity in the commercial product.]	10 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	diphenylamine	Diphenylamine	10 mg/m3	Not Available	Not Available	TLV® Basis: Liver & kidney dam; hematologic eff

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
diphenylamine	Diphenylamine	30 mg/m3	180 mg/m3	220 mg/m3

Ingredient	Original IDLH	Revised IDLH
paraffinic distillate, light, solvent- dewaxed (severe)	2,500 mg/m3	Not Available
nonylated diphenylamines	Not Available	Not Available
1-(tert-dodecylthio)-2-propanol	Not Available	Not Available
2-(heptadecenyl)-4,5-dihydro- 1H-imidazole-1-ethanol	Not Available	Not Available
diphenylamine	Not Available	Not Available
tallow alkyl-diethanolamine derivatives	Not Available	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Personal protection









- Safety glasses with side shields.
- Chemical goggles.
- Eye and face protection
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.

Skin protection

See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber NOTE:
- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

Body protection

Hands/feet protection

See Other protection below

Toro Premium ATF

Issue Date: **16/12/2015**Print Date: **05/10/2018**

Other protection

- Overalls.
- ▶ P.V.C. apron.
- ▶ Barrier cream.
- ▶ Skin cleansing cream.
- Eye wash unit.

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AK-AUS P2	-	AK-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AK-AUS / Class 1 P2	-
up to 100 x ES	-	AK-2 P2	AK-PAPR-2 P2 ^

^ - Full-face

 $A(All\ classes) = Organic\ vapours,\ B\ AUS\ or\ B1 = Acid\ gasses,\ B2 = Acid\ gas\ or\ hydrogen\ cyanide(HCN),\ B3 = Acid\ gas\ or\ hydrogen\ cyanide(HCN),\ E = Sulfur\ dioxide(SO2),\ G = Agricultural\ chemicals,\ K = Ammonia(NH3),\ Hg = Mercury,\ NO = Oxides\ of\ nitrogen,\ MB = Methyl\ bromide,\ AX = Low\ boiling\ point\ organic\ compounds(below\ 65\ degC)$

- · Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Red liquid with mild, oily odour, does not mix with water.		
Physical state	Liquid	Relative density (Water = 1)	0.863
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	34
Initial boiling point and boiling range (°C)	>316	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	177 (COC)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	<0.013 @ 20 deg C	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	>2	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models).

Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Inhalation bazard is increased at higher temperatures.

Inhaled Inhalation hazard is increased at higher temperatures.

Not normally a hazard due to non-volatile nature of product

Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.

Page 6 of 10 **Toro Premium ATF** Issue Date: 16/12/2015 Print Date: 05/10/2018

Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.		
Skin Contact	material is unlikely to produce an irritant dermatitis as described Open cuts, abraded or irritated skin should not be exposed to this The material may accentuate any pre-existing dermatitis condition	s material on s or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the	
Eye	Although the liquid is not thought to be an irritant (as classified b characterised by tearing or conjunctival redness (as with windbu	y EC Directives), direct contact with the eye may produce transient discomfort urn).	
Chronic	Substance accumulation, in the human body, may occur and may	ion reaction in some persons compared to the general population. To cause some concern following repeated or long-term occupational exposure. To add to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles	
	TOXICITY	IRRITATION	
Toro Premium ATF	Not Available	Not Available	
paraffinic distillate, light, solvent-dewaxed (severe)	TOXICITY Dermal (rabbit) LD50: >2000 mg/kg ^[1] Inhalation (rat) LC50: >3.9 mg/l4 h ^[1] Oral (rat) LD50: >2000 mg/kg ^[1]	IRRITATION Not Available	
nonylated diphenylamines	TOXICITY Oral (rat) LD50: >5000 mg/kg ^[2]	IRRITATION Not Available	
1-(tert-dodecylthio)-2-propanol	TOXICITY Dermal (rabbit) LD50: >2000 mg/kg ^[2] Oral (rat) LD50: >5000 mg/kg ^[2]	IRRITATION Not Available	
2-(heptadecenyl)-4,5-dihydro- 1H-imidazole-1-ethanol	TOXICITY Not Available	IRRITATION Not Available	
diphenylamine	TOXICITY Oral (hamster) LD50: ~600 mg/kg ^[1]	IRRITATION Not Available	
tallow alkyl-diethanolamine derivatives	TOXICITY Not Available	IRRITATION Not Available	
Legend:	Value obtained from Europe ECHA Registered Substances - data extracted from RTECS - Register of Toxic Effect of chemical controls.	Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified al Substances	

The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since:

- The adverse effects of these materials are associated with undesirable components, and
- The levels of the undesirable components are inversely related to the degree of processing;
- Distillate base oils receiving the same degree or extent of processing will have similar toxicities;
- The potential toxicity of residual base oils is independent of the degree of processing the oil receives.

The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing.

PARAFFINIC DISTILLATE, LIGHT, SOLVENT-DEWAXED (SEVERE)

Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Testing of residual oils for mutation-causing and cancer-causing potential has shown negative results, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size. For highly and severely refined distillate base oils:

In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal $concentration \ for \ inhalation \ is \ 2.18 \ to > 4 \ mg/L. \ The \ materials \ have \ varied \ from \ "non-irritating" \ to \ "moderately irritating" \ when \ tested \ for \ skin \ and \ eye$ irritation. Testing for sensitisation has been negative. The effects of repeated exposure vary by species; in animals, effects to the testes and lung have been observed, as well as the formation of granulomas. In animals, these substances have not been found to cause reproductive toxicity or significant increases in birth defects.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

NONYLATED DIPHENYLAMINES

Heating of substituted diphenylamines may generate vapours which can irritate the eyes and airways. Drying of skin and mucous membranes leading to irritation may occur with prolonged or repeated contact. Overexposure may cause skin and airway irritation with dizziness and flu-like symptoms. All show a slight to very low order of toxicity following oral or topical administration. There is very low potential to cause gene mutations.

1-(TERT-DODECYLTHIO)-2-PROPANOL

For alkyl sulfide lube additives:

Animal testing has shown that inhalation of high levels of these compounds can be lethal, and can cause changes in the kidney and liver. This does not seem to be relevant in humans. This group of substances does not seem to cause reproductive or developmental toxicity, or genetic damage.

*HPV Challenge Program Submission Group 1; 2005

Chemwatch: 5198-50 Page 7 of 10 Version No: 2.1.1.1

Toro Premium ATF

Issue Date: 16/12/2015 Print Date: 05/10/2018

The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's gedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the 2-(HEPTADECENYL)-4,5-DIHYDRO-1H-IMIDAZOLEopportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one 1-ETHANOL with stronger sensitising potential with which few individuals come into contact. Generally these amphoteric surfactants do not seem to irritate the skin, but they mildly irritate the eye. They also do not cause mutations. Information on effects on reproduction and ability to cause cancer is unavailable. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Diphenylamine and all its substituted derivatives show slight to moderate acute toxicity. Overall, it is not considered to cause mutations or genetic toxicity. In DIPHENYL AMINE animal testing, higher concentrations appear to reduce the number of viable offspring. ADI: 0.02 mg/kg/day NOEL: 1.5 mg/kg/day The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Laboratory testing shows that the fatty acid amide, cocoamide DEA, causes occupational allergic contact dermatitis, and that allergy to this substance is becoming more common. TALLOW ALKYL-Alkanolamides are manufactured by condensation of diethanolamine and the methyl ester of long chain fatty acids. **DIETHANOLAMINE** Tallow derivatives used in the manufacture of cosmetic products are safe for consumption when it undergoes- transesterification or hydrolysis at 200 ♥ C, **DERIVATIVES** under pressure for 20 minutes (for glycerol, fatty acids and esters); saponification with 12 M of NaOH (for glycerol and soap) at 95 � C for 3 hours; continuous process at 140 �C, for about 8 minutes or its equivalent. The chemicals in the Fatty Nitrogen Derived (FND) Amides are generally similar in terms of physical and chemical properties, environmental fate and toxicity. Its low acute oral toxicity is well established across all subcategories by the available data and show no apparent organ specific toxicity, mutation, reproductive or developmental defects. PARAFFINIC DISTILLATE. LIGHT, SOLVENT-DEWAXED (SEVERE) & 2-(HEPTADECENYL)-4,5-No significant acute toxicological data identified in literature search. DIHYDRO-1H-IMIDAZOI F-1-ETHANOL & TALLOW ALKYL-DIETHANOLAMINE DERIVATIVES Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as 2-(HEPTADECENYL)-4,5reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing DIHYDRO-1H-IMIDAZOLE-RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to 1-ETHANOL & **DIPHENYLAMINE & TALLOW** severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or ALKYL-DIETHANOLAMINE asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating **DERIVATIVES** substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. 2-(HEPTADECENYL)-4.5-DIHYDRO-1H-IMIDAZOLE-The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. 1-ETHANOL & TALLOW The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, ALKYL-DIETHANOLAMINE scaling and thickening of the skin. DERIVATIVES

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	~	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0
			Data available but dans unt fill the suite de fau dans ification

Legend:

X - Data available but does not fill the criteria for classification

Data available to make classification

Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE SOURCE
Toro Premium ATF	Not Available	Not Available	Not Available	Not Not Available Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE SOURCE
paraffinic distillate, light,	EC50	48	Crustacea	>1000mg/L 1
solvent-dewaxed (severe)	NOEC	504	Crustacea	>1mg/L 1
nonylated diphenylamines	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE SOURCE
	NOEC	96	Crustacea	<10mg/L 1
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE SOURCE
1-(tert-dodecylthio)-2-propanol	Not Available	Not Available	Not Available	Not Not Available Available
2-(heptadecenyl)-4,5-dihydro- 1H-imidazole-1-ethanol	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE SOURCE

Page 8 of 10 **Toro Premium ATF**

Issue Date: 16/12/2015 Print Date: 05/10/2018

	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	3.79mg/L	4
	EC50	48	Crustacea	0.31mg/L	4
diphenylamine	EC50	72	Algae or other aquatic plants	0.048mg/L	1
	BCF	768	Fish	0.0437mg/L	4
	NOEC	504	Crustacea	0.16mg/L	1
tallow alkyl-diethanolamine derivatives	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.1mg/L	2
	EC50	48	Crustacea	0.043mg/L	2
	EC50	72	Algae or other aquatic plants	0.004mg/L	2
	NOEC	72	Algae or other aquatic plants	0.0024mg/L	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
2-(heptadecenyl)-4,5-dihydro- 1H-imidazole-1-ethanol	LOW	LOW
diphenylamine	LOW (Half-life = 56 days)	Not Available

Bioaccumulative potential

Ingredient	Bioaccumulation
2-(heptadecenyl)-4,5-dihydro- 1H-imidazole-1-ethanol	LOW (LogKOW = 7.5137)
diphenylamine	LOW (BCF = 253)

Mobility in soil

Ingredient	Mobility
2-(heptadecenyl)-4,5-dihydro- 1H-imidazole-1-ethanol	LOW (KOC = 206300)
diphenylamine	LOW (KOC = 1887)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority. Product / Packaging disposal
 - ▶ Recycle wherever possible or consult manufacturer for recycling options.
 - ► Consult State Land Waste Authority for disposal.
 - ▶ Bury or incinerate residue at an approved site.
 - ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant

NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Toro Premium ATF

Safety, health and environmental regulations / legislation specific for the substance or mixture

PARAFFINIC DISTILLATE, LIGHT, SOLVENT-DEWAXED (SEVERE)(64742-56-9.) IS FOUND ON THE FOLLOWING REGULATORY LISTS International Agency for Research on Cancer (IARC) - Agents Classified by the IARC US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants Monographs US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air US - Alaska Limits for Air Contaminants Contaminants US - California Permissible Exposure Limits for Chemical Contaminants US - Washington Permissible exposure limits of air contaminants US - Hawaii Air Contaminant Limits US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants US - Idaho - Limits for Air Contaminants US ACGIH Threshold Limit Values (TLV) US - Massachusetts - Right To Know Listed Chemicals US ACGIH Threshold Limit Values (TLV) - Carcinogens US - Michigan Exposure Limits for Air Contaminants US NIOSH Recommended Exposure Limits (RELs) US - Minnesota Permissible Exposure Limits (PELs) US OSHA Permissible Exposure Levels (PELs) - Table Z1 US - Oregon Permissible Exposure Limits (Z-1) US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US - Pennsylvania - Hazardous Substance List US TSCA Chemical Substance Inventory - Interim List of Active Substances US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

NONYLATED DIPHENYLAMINES(36878-20-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

1-(TERT-DODECYLTHIO)-2-PROPANOL(67124-09-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

2-(HEPTADECENYL)-4,5-DIHYDRO-1H-IMIDAZOLE-1-ETHANOL(27136-73-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US TSCA Chemical Substance Inventory - Interim List of Active Substances

DIPHENYLAMINE(122-39-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Hawaii Air Contaminant Limits	Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US - Washington Permissible exposure limits of air contaminants
US - Michigan Exposure Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV)
US - Minnesota Permissible Exposure Limits (PELs)	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Oregon Permissible Exposure Limits (Z-1)	US EPCRA Section 313 Chemical List
US - Pennsylvania - Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances
	US TSCA Section 4/12 (b) - Sunset Dates/Status

TALLOW ALKYL-DIETHANOLAMINE DERIVATIVES(61791-44-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

Page **10** of **10**

Toro Premium ATF

Issue Date: **16/12/2015**Print Date: **05/10/2018**

State Regulations

US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory Status

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (tallow alkyl-diethanolamine derivatives; paraffinic distillate, light, solvent-dewaxed (severe); nonylated diphenylamines; 2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol; diphenylamine; 1-(tert-dodecylthio)-2-propanol)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	N (tallow alkyl-diethanolamine derivatives; paraffinic distillate, light, solvent-dewaxed (severe); 1-(tert-dodecylthio)-2-propanol)
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	16/12/2015
Initial Date	Not Available

Other information

Ingredients with multiple cas numbers

Name	CAS No
tallow alkyl-diethanolamine derivatives	61791-44-4, 1218787-32-6

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

 ${\sf PC-STEL} : {\sf Permissible \ Concentration-Short \ Term \ Exposure \ Limit}$

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection
OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.