
5000 SERIES	Z MASTER <sup>®</sup> 5000 SERIES					
	74904	74906	74915	74930	74918	
ENGINE* AT 3600 RPM	23 hp Kohler® Command Pro EFI 747cc	25 hp Kohler Command Pro EFI 747cc	25 hp Kohler Command Pro 747cc	25 hp Kohler Command Pro EFI 747cc	26.5 hp Kohler Command Pro EFI 747cc	
ELECTRIC START	Standard					
HEAVY-DUTY CANISTER AIR CLEANER	Standard					
DRIVE TIRES	23" x 9.5"- 12"		24" x 12" x 12"			
CASTER TIRES	13" x 5" - 6"Flat-free semi-pneumaticFlat-free semi-pneumatic					
FUEL CAPACITY	12 gallons, single-point fill					
DIGITAL FUEL GAUGE	Standard					
DIGITAL HOUR METER	Standard					
HYDRAULIC DRIVE SYSTEM	Unitized 12 cc pumps and wheel motors					
MAX GROUND SPEED (FWD)	10 mph					
SEAT	Deluxe suspension seat with 3-D isolation mounts for maximum comfort					
DECK WIDTH	48"	52"	60"	60"	72"	
CUTTING DECK	TURBO FORCE*					
DECK DEPTH	5.5"					
DECK CONSTRUCTION	7-gauge high-strength steel					
BULL-NOSE BUMPER	Standard					
ADJUSTABLE DISCHARGE BAFFLE	Standard					
RUBBER DISCHARGE CHUTE	Standard					
1" HEAVY-DUTY SPINDLE SHAFT	Standard					
SPINDLE BEARINGS		Maintenance Free Greaseable				
DECK LIFT ASSIST PEDAL		Standard				
CUTTING HEIGHT	1.0" - 5.5" in .25" increments					



**COMFORTABLE RIDE** The deluxe suspension seat features thick cushions, large bolsters and 3-D isolation mounts that absorb bumps and vibrations to reduce operator fatigue.



**TOUGH SPINDLE ASSEMBLIES** 

Toro's rugged cast-iron spindle assemblies survive impacts that would destroy lesser spindles. A stout cast iron housing with a massive base absorbs impact loads and distributes them across a broader area of the deck shell.



SMOOTH, POWERFUL RESPONSE The unitized pump and wheel motor uses proven commercial hydraulic components while eliminating hoses and other potential leak points. You'll get a smoother, faster response while enjoying an even more reliable machine.



490-9672 ©2017 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. \*The gross horsepower ratings of these engines were laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower. \*\*See retailer for warranty details.