6000 SERIES	Z MASTER® 6000 SERIES								
	<b>78922</b> CARB Model	74923	<b>78924</b> CARB Model	74960	74961	<b>74926 /</b> 78926 CARB Model	<b>74928 /</b> 78928 CARB Model	74946	74947
ENGINE* AT 3600 RPM	22 hp Kawasaki® FX 726cc	24.5 hp Kawasaki FX 852cc	23.5 hp Kawasaki FX 726cc	31 hp Kawasaki FX 999cc	31 hp Kawasaki FX 999cc	26.5 hp Kohler* Command Pro EFI 747cc	26.5 hp Kohler Command Pro EFI 747cc	34 hp Kohler Command Pro EFI 999cc w/Horizon™ Technology	34 hp Kohler Command Pro EFI 999cc w/Horizon Technology
ELECTRIC START	Standard								
HEAVY-DUTY CANISTER AIR CLEANER	Standard								
DRIVE TIRES	24" x 9.5" x 12" 24" x 12" x 12"								
CASTER TIRES	13" x 5" - 6" Flat-free semi-pneumatic  13" x 6.5" - 6" Flat-free semi-pneumatic								
FUEL CAPACITY	12 gallons, single-point fill								
DIGITAL FUEL GAUGE	Standard								
DIGITAL HOUR METER	Standard								
HYDRAULIC DRIVE SYSTEM	Unitized	I 12 cc pumps & whee	el motors	Unitized 16 cc pumps & wheel motors					
MAX GROUND SPEED (FWD)	10 mph			11.5 mph					
SEAT	Deluxe suspension seat with 3-D isolation mounts for maximum comfort								
DECK WIDTH	48"	52"	52"	60"	72"	60"	72"	60"	72"
CUTTING DECK	TURBO FORCE"								
DECK DEPTH	5.5"								
DECK CONSTRUCTION	7-gauge high-strength steel								
BULL-NOSE BUMPER	Standard								
ADJUSTABLE DISCHARGE BAFFLE	Standard, tools-free								
RUBBER DISCHARGE CHUTE					Standard				
1" HEAVY-DUTY SPINDLE SHAFT	 				Standard				
SPINDLE BEARINGS		Mainten	ance Free		Greaseable	Maintenance Free	Greaseable	Maintenance Free	Greaseable
DECK LIFT ASSIST PEDAL	Standard								
CUTTING HEIGHT	1.0" – 5.5" in .25" increments								

