

GRANDSTAND

STAND-ON MOWERS

Through increased operator comfort, outstanding traction and handling, and an incredible after-cut appearance, the Toro GrandStand takes stand-on mower performance to another level. Simply put, choosing a GrandStand is a decision you'll always be comfortable with.

MORE PRODUCTIVITY

Accomplish more with a top speed of 10 mph (16 km/h) allowing you to cover more ground. The large 10.5 gallon (39.7 liter) fuel tank helps you to run all day without refueling.

LESS MAINTENANCE

With hefty cast iron spindles including maintenance free bearings plus only annual grease points, there will be less need for routine maintenance. That means less time spent off your mower and more time generating profits with it.

EASY TO SERVICE

When service is needed, it's easier than ever before. The removable fuel tank means open access to both sides of the engine and everything in the tower. Turning the engine provides extra space for accessing the deck drive.

GRANDSTAND® STAND-ON MOWERS	GRANDSTAND STAND-ON MOWERS						
	74534 79534 CARB Model 7453	74536	74504 79504 CARB Model	74505 79505 CARB Model	74518 79518 CARB Model	74519	74513
DECK SIZE	36" (91 CM)	40" (102 CM)	48" (122 CM)	52" (132 CM)	48" (122 CM) EFI	52" (132 CM) EFI	60" (152 CM) EF
ENGINE* AT 3600 RPM	15 hp Kawasaki [®] FS 603cc		≫ 22 hp Kawasaki FX 726cc		23 hp Kohler [®] Command EFI 747cc	≫ 25 hp Kohler Command EFI 747cc	
STARTER				Electric			
AIR CLEANER	N/A		>> HeavyDuty Air Canister				
DRIVE TIRES	18" x 8.5" - 8" (45.7 cm x 21.6 cm –20.3 cm)	≫ 18" x 9.5" - 8" (45.7 cm x 24.1 cm -20.3 cm)	≫ 20" x 10.5" - 8" (50.8 cm x 26.7 cm - 20.5 cm)				
CASTER TIRES	11" x 4" - 5" Flat-Free Semi-Pneumatic (27.9 cm x 10.1 cm – 12.7 cm)						
FUEL CAPACITY	7.8 gallons (29.5 liters)		≫ 10.5 gallons (39.7 liters)				
DIGITAL HOUR METER				Standard			
HYDRAULIC DRIVE SYSTEM	Pumps & Wheel Motors		>> Unitized Pumps & Wheel Motors				
MAX GROUND SPEED (FWD)	8.0 mph (12.9 km/h)		>> 10.0 mph (16 km/h)				
CUTTING DECK				TURBO FORCE®			
DECK DEPTH	5.0" (12.7 cm)		≫ 5.5" (14 cm)				
DECK CONSTRUCTION	7-Gauge, High-Strength Steel						
BULL-NOSE BUMPER	Standard						
ADJUSTABLE DISCHARGE BAFFLE	Standard						
RUBBER DISCHARGE CHUTE	Standard						
1" (2.5 CM) HEAVY-DUTY SPINDLE SHAFT	Standard						
SPINDLE BEARINGS	Maintenance-Free						
CUTTING HEIGHT	1.0" - 5.0" (2.5 - 12.7 cm) 1.5" - 5.0" (3.8 - 12.7 cm)						

>> = Enhanced or Step-up feature



SMALLER FOOTPRINT

The GrandStand conserves space to get more machines on your trailer, or allows for a smaller trailer and lighter load. The foldable platform makes it even more compact for transport or storage.



PROPERTY OWNER ACCEPTANCE

Some property owners have negative reactions to larger, heavier-looking mowers and are concerned that their lawns may be damaged. The sleeker Toro GrandStand helps to overcome that problem.

BETTER VISIBILITY

The exceptional visibility from the GrandStand protects the operator, the mower and the property. The operator is better able to steer clear of obstacles, and easily pass beneath branches.

EFI – SUPERIOR FUEL ECONOMY

- Up to 25% better fuel economy than equivalent carbureted engines
- Lower operating cost
- Easy, no choke starting
- Reduced carbon footprint

FATIGUE-REDUCING SUSPENSION

The revolutionary Flex-Ride operator platform suspension results in less operator fatigue and higher productivity throughout the day. The suspension system is self-compensating for operators of different sizes.

2 IN 1 VERSATILITY

Toro's foldable operator platform instantly converts the GrandStand to a walk-behind. It easily lowers back down when its time to ride – saving time, money and trailer space by eliminating the need to switch mowers.

490-0023 ©2018 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

S

ΕS

EATUR

ш

DDITIONAL

∢