

5000 SERIES	Z MASTER® 5000 SERIES										
	74904	74906	75955 MyRIDE® Suspension System	74915	74930	75951 MyRIDE® Suspension System	74943 Rear Discharge	74945 Rear Discharge	74933 Propane	74934 Propane	74918
ENGINE* AT 3600 RPM	23 hp Kohler® Command Pro EFI 747cc	25 hp Kohler Command Pro EFI 747cc		25 hp Kohler Command Pro 747cc	25 hp Kohler Command Pro EFI 747cc			26.5 hp Kohler Command Pro EFI 747cc	Kohler® Command Pro EFI Propane		26.5 hp Kohler Command Pro EFI 747cc
ELECTRIC START	Standard										
HEAVY-DUTY CANISTER AIR CLEANER	Standard										
DRIVE TIRES	23" x 9.5" – 12" (58.4 cm x 24.1 cm – 30.5 cm)		24" x 12" x 12" (61 cm x 30.5 cm – 30.5 cm)								
CASTER TIRES	13" x 5" – 6" Flat-free semi-pneumatic (33 cm x 12.7 cm – 15.2 cm)	13" x 6.5" - 6" Flat-free semi-pneumatic (33 cm x 16.5 cm – 15.2 cm)									
FUEL CAPACITY	12 gallons (45.4 liters), single-point fill								43.5 lbs. (19.7 kg) Propane		12 gallons (45.4 liters), single-point fill
DIGITAL FUEL GAUGE	Standard										
HOUR METER	Smart Hour										
HYDRAULIC DRIVE SYSTEM	Unitized 12 cc pumps and wheel motors										
MAX GROUND SPEED (FWD)	10 mph (16.1 km/h)										
MyRIDE® SUSPENSION SYSTEM	-	-	Standard	-	-	Standard	-	-	-	-	-
SEAT	Deluxe suspension seat with 3-D isolation mounts for maximum comfort										
DECK WIDTH	48" (122 cm)	52" (132 cm)	52" (132 cm)	60" (152 cm)	60" (152 cm)	60" (152 cm)	60" (152 cm)	72" (183 cm)	60" (152 cm)	72" (183 cm)	72" (183 cm)
CUTTING DECK	TURBO FORCE®										
DECK DEPTH	5.5" (14 cm)										
DECK CONSTRUCTION	7-gauge (4.7 mm) high-strength steel										
BULL-NOSE BUMPER	Standard										
ADJUSTABLE DISCHARGE BAFFLE	Standard										
RUBBER DISCHARGE CHUTE	Standard										
1" (2.5 CM) HEAVY-DUTY SPINDLE SHAFT	Standard										
SPINDLE BEARINGS	Maintenance-Free										
DECK LIFT ASSIST PEDAL	Standard										
CUTTING HEIGHT	1.0" – 5.5" (2.5 - 14 cm) in .25" (6 mm) increments										

COMFORTABLE RIDE

The deluxe suspension seat features thick cushions, large bolsters and 3-D isolation mounts that absorb bumps and vibrations to reduce operator fatigue.

TOUGH SPINDLE ASSEMBLIES

Toro's rugged cast-iron spindle assemblies survive impacts that would destroy lesser spindles. A stout cast iron housing with a massive base absorbs impact loads and distributes them across a broader area of the deck shell.

SMOOTH, POWERFUL RESPONSE

The unitized pump and wheel motor uses proven commercial hydraulic components while eliminating hoses and other potential leak points. You'll get a smoother, faster response while enjoying an even more reliable machine.



490-0035 ©2018 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *The gross horsepower ratings of these engines were laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower.