

5000 SERIES	Z MASTER® 5000 SERIES											
	74904	74906	75955 MyRIDE™ Suspension System	74915	74930	75951 MyRIDE™ Suspension System	74943 Rear Discharge	74945 Rear Discharge	74933 Propane	74934 Propane	74918	
ENGINE* AT 3600 RPM	23 hp Kohler® Command Pro EFI 747cc		25 hp Kohler Command Pro EFI 747cc					26.5 hp Kohler Command Pro EFI 747cc		Kohler® Command Pro EFI Propane		26.5 hp Kohler Command Pro EFI 747cc
ELECTRIC START	Standard											
HEAVY-DUTY CANISTER AIR CLEANER	Standard											
DRIVE TIRES	23" x 9.5" - 12" (58.4 cm x 24.1 cm - 30.5 cm)			24" x 12" x 12" (61 cm x 30.5 cm - 30.5 cm)								
CASTER TIRES	13" x 5" - 6" Flat-free semi-pneumatic (33 cm x 12.7 cm - 15.2 cm)		13" x 6.5" - 6" Flat-free semi-pneumatic (33 cm x 16.5 cm - 15.2 cm)									
FUEL CAPACITY	12 gallons (45.4 liters), single-point fill								43.5 lbs. (19.7 kg) Propane		12 gallons (45.4 liters), single-point fill	
DIGITAL FUEL GAUGE	Standard											
HOUR METER	Smart Hour											
HYDRAULIC DRIVE SYSTEM	Unitized 12 cc pumps and wheel motors											
MAX GROUND SPEED (FWD)	10 mph (16.1 km/h)											
MyRIDE™ SUSPENSION SYSTEM	-	-	Standard	-	-	Standard	-	-	-	-	-	
SEAT	Deluxe suspension seat with 3-D isolation mounts for maximum comfort											
DECK WIDTH	48" (122 cm)	52" (132 cm)	52" (132 cm)	60" (152 cm)	60" (152 cm)	60" (152 cm)	60" (152 cm)	72" (183 cm)	60" (152 cm)	72" (183 cm)	72" (183 cm)	
CUTTING DECK	TURBO FORCE™											
DECK DEPTH	5.5" (14 cm)											
DECK CONSTRUCTION	7-gauge (4.7 mm) high-strength steel											
BULL-NOSE BUMPER	Standard											
ADJUSTABLE DISCHARGE BAFFLE	Standard											
RUBBER DISCHARGE CHUTE	Standard											
1" (2.5 CM) HEAVY-DUTY SPINDLE SHAFT	Standard											
SPINDLE BEARINGS	Maintenance Free						Greaseable		Maintenance Free		Greaseable	
DECK LIFT ASSIST PEDAL	Standard											
CUTTING HEIGHT	1.0" - 5.5" (2.5 - 14 cm) in .25" (6 mm) increments											

COMFORTABLE RIDE

The deluxe suspension seat features thick cushions, large bolsters and 3-D isolation mounts that absorb bumps and vibrations to reduce operator fatigue.

TOUGH SPINDLE ASSEMBLIES

Toro's rugged cast-iron spindle assemblies survive impacts that would destroy lesser spindles. A stout cast iron housing with a massive base absorbs impact loads and distributes them across a broader area of the deck shell.

SMOOTH, POWERFUL RESPONSE

The unitized pump and wheel motor uses proven commercial hydraulic components while eliminating hoses and other potential leak points. You'll get a smoother, faster response while enjoying an even more reliable machine.

