

ZERO TURN MOWERS WITH MyRIDE® SUSPENSION SYSTEM	TIMECUTTER® MX	TIMECUTTER® HD			TITAN® HD			Z MASTER®					
	74768	75211	75212	75213	74465	74466	74467	75932	75936	75955	75951	75967	75968
	2000 SERIES	2000 SERIES	2000 SERIES	2000 SERIES	3000 SERIES	3000 SERIES	3000 SERIES	5000 SERIES	5000 SERIES	5000 SERIES	5000 SERIES	6000 SERIES	6000 SERIES
ENGINE*	24.5 hp Toro® Commercial V-Twin 708cc	22.5 hp Toro Commercial V-Twin 708cc	24.5 hp Toro Commercial V-Twin 708cc		24.5 hp Toro Commercial V-Twin 708cc w/ Heavy Duty Air Canister			24.5 hp Kawasaki® FX 852cc	25.5 hp Kawasaki FX 852cc	25 hp Kohler® Command Pro EFI 747cc		31 hp Kawasaki FX 999cc	
DRIVE TIRES	20" x 10" (50.8 x 25.4 cm)	22" x 10" (55.9 x 25.4 cm)			23" x 9.5" x 12" (58.4 x 24.1 x 30.5cm)		23" x 10.5" x 12" (58.4 x 26.7 x 30.5cm)	23" x 9" x 12" (58.4 x 24.1 x 30.5cm)		24" x 12" x 12" (61.0 x 30.5 x 30.5cm)			
CASTER TIRES	13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)			13" x 6.5" - 6" (33.0 x 16.5 x 15.2cm)			13" x 6.5" - 6" (33.0 x 16.5 x 15.2cm) Pneumatic		13" x 6.5" - 6" (33.0 x 16.5 x 15.2cm) Semi-pneumatic			
FUEL CAPACITY	3 Gal (11.4 L)	5 Gal (18.9 L)			7 Gal (26.5 L)			8 Gal (30.3 L), Single-Point Fill		12 Gal (45.4 L), Single-Point Fill			
HOURLY METER	Optional	Standard			Standard			Standard					
MAX GROUND SPEED (FWD)	Up to 7 mph (11.3 km/h)	Up to 8.5 mph (13.7 km/h)			Up to 9 mph (14.5 km/h)			Up to 8.5 mph (13.7 km/h)		Up to 10 mph (16.1 km/h)		Up to 11.5 mph (18.5 km/h)	
MyRIDE® SUSPENSION SYSTEM													
COMFORT PLATFORM	Cast-Aluminum	Cast-Aluminum			Cast-Aluminum w/Cast-Aluminum Trailing Arm			Fabricated High-Strength Steel with Flip-Up Floor Pan					
PLATFORM TRAVEL	3.0" (7.6 cm)	3.0" (7.6 cm)			3.0" (7.6 cm)			3.6" (9.1 cm)					
SHOCKS	1 Front Center / 2 Rear	1 Front Center / 2 Rear			1 Front Center / 2 Rear			1 Front Center / 2 Rear					
ISO MOUNTS	N/A	N/A			N/A			Qty 4, 2" (5.1cm) 3-D Isolation Mounts					
SEAT	Premium	Premium Thickly Padded w/ Armrests			Deluxe High Back Adjustable Seat w/ Premium Armrests			Deluxe Seat w/ 3-D Isolation Mounts and Padded Armrests					
ADJUSTABILITY	4 Point Adjustment on Rear Shocks	4 Point, Infinite Adjustment on Rear Shocks			5 Point, Infinite Adjustment on Rear Shocks			5 Point, Infinite Adjustment on Rear Shocks					
DECK WIDTH	50" (127 cm)	48" (121.9 cm)	54" (137.2 cm)	60" (152.4 cm)	48" (121.9 cm)	52" (132.1 cm)	60" (152.4 cm)	52" (132.1 cm)	60" (152.4 cm)	52" (132.1 cm)	60" (152.4 cm)	60" (152.4 cm)	72" (182.9 cm)
CUTTING DECK	Fabricated 10-Gauge 3 Blades	Fabricated Grade 50 High Strength 10-Gauge Steel Shell			TURBO FORCE® 7/10-Gauge High-Strength Steel			TURBO FORCE® 7-Gauge High-Strength Steel					
DECK DEPTH	4.0" (10.6 cm)	5.0" (12.7 cm)			5.0" (12.7 cm)			5.5" (14.0 cm)					
FRAME	Heavy-Duty 10-Gauge Channel	Heavy-Duty 10-Gauge Channel			3" x 2" (7.6 x 5 cm) Tubular Steel			3" x 1.5" (7.6 x 3.8 cm) Tubular Steel					
BULL-NOSE BUMPER	N/A	N/A			Standard			Standard					
ADJUSTABLE DISCHARGE BAFFLE	N/A	N/A			N/A			Standard				Standard, Tools-Free	
RUBBER DISCHARGE CHUTE	N/A	N/A			Standard			Standard					
DECK LIFT ASSIST	Optional	Standard			Standard			Standard					
DECK MAINTENANCE	No-Tools Bulldog Jack Mount	No-Tools Bulldog Jack Mount			No-Tools Bulldog Jack Mount			Flip-Up Floor Pan for Servicing					
CUTTING HEIGHT	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm) 13 position			1.5" - 5" in 0.25" increments (3.8 - 12.7 cm in 0.6 cm increments)			1.0" - 5.5" in .25" increments (2.5 - 14.0 cm in 0.6 cm increments)					
LIMITED WARRANTY**	3 Year Unlimited Hours	3 Year 300 Hour Limited			4 Year 750 Hour Limited			5 Year 1200 Hour Limited No Hour Limit First Two Years				5 Year 1400 Hour Limited No Hour Limit First Two Years	



490-0038 ©2018 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *The gross horsepower ratings of these engines were laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower. **See retailer for warranty details.