5000 SERIES PROPANE	Z MASTER® 5000 SERIES PROPANE		
	74933		74934
ENGINE AT 3600 RPM	Kohler* Command Pro EFI Propane		Kohler Command Pro EFI Propane
ELECTRIC START	Standard		
HEAVY-DUTY CANISTER AIR CLEANER	Standard		
DRIVE TIRES	24" x 12"- 12" (61 cm x 30.5 cm – 30.5 cm)		
CASTER TIRES	13" x 6.5" - 6" Flat-free semi-pneumatic (33 cm x 16.5 cm – 15.2 cm)		
FUEL CAPACITY	43.5 lbs. (19.7 kg) Propane		
DIGITAL FUEL GAUGE	Standard		
DIGITAL HOUR METER	Standard		
HYDRAULIC DRIVE SYSTEM	Unitized 12 cc pumps and wheel motors		
MAX GROUND SPEED (FWD)	10 mph (16 km/h)		
SEAT	Deluxe suspension seat with 3-D isolation mounts for maximum comfort		
DECK WIDTH	60" (152 cm)		72" (183 cm)
CUTTING DECK	TURBO FORCE* Rear Discharge		
DECK DEPTH	5.5" (14 cm)		
DECK CONSTRUCTION	7-gauge high-strength steel		
BULL-NOSE BUMPER	Standard		
ADJUSTABLE DISCHARGE BAFFLE	Standard		
RUBBER DISCHARGE CHUTE	Standard		
1" (2.5 CM) HEAVY-DUTY SPINDLE SHAFT	Standard		
SPINDLE BEARINGS	Maintenance Free		Greaseable
DECK LIFT ASSIST PEDAL	Standard		
CUTTING HEIGHT	1.0" - 5.5" (2.5 - 14 cm) in .25" (6 mm) increments		



SINGLE-TANK DESIGN

Single vapor-draw propane tank mounted behind the seat allows for better deck and drive tire visibility. Larger tank positioned above the engine aids in performance by increasing vaporization capacity.



SMOOTH, POWERFUL RESPONSE

The 12cc unitized pump and wheel motor uses proven commercial hydraulic components while eliminating hoses and other potential leak points. You'll get a smoother, faster response while enjoying an even more reliable machine.



EXCEPTIONAL COMFORT

Deluxe suspension seat features thick cushions, large bolsters and 3-D isolator mounts that absorb bumps and vibrations to reduce operator fatigue.

