5000 SERIES REAR DISCHARGE	Z MASTER [®] 5000 SERIES WITH REAR DISCHARGE DECKS	
	74943	74945
ENGINE* AT 3600 RPM	25 hp Kohler Command Pro EFI 747cc	26.5 hp Kohler Command Pro EFI 747cc
ELECTRIC START	Standard	
HEAVY-DUTY CANISTER AIR CLEANER	Standard	
DRIVE TIRES	24" x 12" x 12" (61 cm x 30.5 cm – 30.5 cm)	
CASTER TIRES	13" x 6.5" - 6" Flat-free semi-pneumatic (33 cm x 16.5 cm – 15.2 cm)	
FUEL CAPACITY	12 gallons (45.4 liters), single-point fill	
DIGITAL FUEL GAUGE	Standard	
DIGITAL HOUR METER	Standard	
HYDRAULIC DRIVE SYSTEM	Unitized 12 cc pumps and wheel motors	
MAX GROUND SPEED (FWD)	10 mph (16 km/h)	
SEAT	Deluxe suspension seat with 3-D isolation mounts for maximum comfort	
DECK WIDTH	60" (152 cm)	72" (183 cm)
CUTTING DECK	TURBO FORCE" Rear Discharge	
DECK DEPTH	5.5" (14 cm)	
DECK CONSTRUCTION	7-gauge high-strength steel	
BULL-NOSE BUMPER	Standard	
ADJUSTABLE DISCHARGE BAFFLE	Standard	
RUBBER DISCHARGE CHUTE	Standard	
1" (2.5 CM) HEAVY-DUTY SPINDLE SHAFT	Standard	
SPINDLE BEARINGS	Greaseable Ball Bearings	
DECK LIFT ASSIST PEDAL	Standard	
CUTTING HEIGHT	1.0" - 5.5" (2.5 - 14 cm) in .25" (6 mm) increments	



Two blades rotate clockwise and one rotates counter-clockwise allowing for even distribution of clippings.



DUAL TRIMMING Trim around trees and landscaping obstacles with either side of the deck. Durable, adjustable side bumpers act as an anti-scalp system.



RUGGED PERFORMANCE Highly productive in taller grass and weed conditions.



490-0051 ©2018 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *The gross horsepower ratings of these engines were laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower.