



Z MASTER[®]

6000 SERIES ZERO TURN MOWERS

HORIZON[™] TECHNOLOGY



HORIZON[™] TECHNOLOGY

HORIZON[™] TECHNOLOGY, AN ONBOARD INTELLIGENCE PLATFORM THAT IMPROVES FUEL EFFICIENCY AND PRODUCTIVITY.

Horizon allows communication between key systems on the machine to enhance performance in a wide range of mowing conditions.

Horizon Technology protects your engine by monitoring engine oil temperature and pressure and will put the machine into "SAFE MODE" if critical thresholds are exceeded.

HORIZON TECHNOLOGY

Available On Select Models:

Models 74946, 74947 & 74969

- 29 hp Kawasaki[®] FX EFI 852cc or 34 hp Kohler[®] Command Pro EFI 999cc engines
- 60" or 72" TURBO FORCE[®] deck

www.toro.com/zmasterhorizon



DEFINED PERFORMANCE MODES:

Engine speed controlled by three-position rocker switch and existing PTO switch to provide defined performance modes:

MAX MODE

Maximum power for the most demanding conditions.

ECONOMY MODE

Excellent performance in typical conditions with reduced fuel consumption, emissions, noise and machine wear.

LOW MODE

Helps reduce deck packing and discharge clumping when cutting in wet conditions.

6000 SERIES	Z MASTER® 6000 SERIES FEATURING HORIZON™ TECHNOLOGY		
	74969	74946	74947
ENGINE* AT 3600 RPM	29 hp Kawasaki® FX EFI 852cc	34 hp Kohler Command Pro EFI 999cc	34 hp Kohler Command Pro EFI 999cc
ELECTRIC START	Standard		
HEAVY-DUTY CANISTER AIR CLEANER	Standard		
DRIVE TIRES	24" x 12" x 12" (61 cm x 30.5 cm – 30.5 cm)		
CASTER TIRES	13" x 6.5" – 6" Flat-free semi-pneumatic (33 cm x 16.5 cm – 15.2 cm)		
FUEL CAPACITY	12 gallons (45.4 l), single-point fill		
DIGITAL FUEL GAUGE	Standard		
HOUR METER	Horizon Technology		
HYDRAULIC DRIVE SYSTEM	Unitized 16 cc pumps & wheel motors		
MAX GROUND SPEED (FWD)	11.5 mph (18.5 km/h)		
SEAT	Deluxe suspension seat with 3-D isolation mounts for maximum comfort		
DECK WIDTH	60" (152 cm)	60" (152 cm)	72" (183 cm)
CUTTING DECK	TURBO FORCE*		
DECK DEPTH	5.5" (14.0 cm)		
DECK CONSTRUCTION	7-gauge (4.7 mm) high-strength steel		
BULL-NOSE BUMPER	Standard		
ADJUSTABLE DISCHARGE BAFFLE	Standard, tools-free		
RUBBER DISCHARGE CHUTE	Standard		
1" (2.5 CM) HEAVY-DUTY SPINDLE SHAFT	Standard		
SPINDLE BEARINGS	Maintenance Free	Maintenance Free	Greaseable
DECK LIFT ASSIST PEDAL	Standard		
CUTTING HEIGHT	1.0" – 5.5" (2.5 – 14 cm) in .25" (0.6 mm) increments		