ALL NEW TITAN [®] HD 2500 Series	TITAN [®] HD 2500 SERIES			
	74470	74471	74472	78472 (CARB)
ENGINE* AT 3600 RPM	20.5 hp* Kawasaki® FX 726cc	22 hp* Kawasaki FX 726cc	23.5 hp* Kawasaki FX 726cc	23.5 hp* Kawasaki FX 726cc
ELECTRIC START	Standard			
HEAVY-DUTY CANISTER AIR CLEANER	Standard			
DECK WIDTH	48" (122 cm)	52" (132 cm)	60" (152 cm)	60" (152 cm)
CUTTING DECK	TURBO FORCE*			
DECK DEPTH	5.5" (14 cm)			
DECK CONSTRUCTION	7/10-gauge high-strength steel			
BULL-NOSE BUMPER	Standard			
RUBBER DISCHARGE CHUTE	Standard			
DECK SPINDLES	8" (20.3 cm) Alum Sealed Ball Bearings, 1" (2.5 cm) Shaft			
HYDRAULIC DRIVE SYSTEM	ZT3400			
FUEL CAPACITY	7 gallons (26.5 liters)			
MAX GROUND SPEED (FWD)	Up to 10 mph (16 km/h)			
REAR TIRES	24" x 9.5" - 12" (60.96 cm x 24.13 cm - 30.48 cm) 24" x 12" - 12" (60.96 cm x 30.48 cm - 30.48 cm)			
FRONT TIRES	13" x 6.5" - 6" (33 cm x 16.51 cm - 15.24 cm) Taper Roller			
SEAT	Deluxe High-Back Adjustable Suspension Seat			
TOOL-MOUNTING CAPABILITY	Side Console / Rear Guard Ready			
DECK LIFT ASSIST PEDAL	Standard			
CUTTING HEIGHT	1.5" - 5" (3.8 - 12.7 cm) in 0.25" (6 mm) increments			
ROPS	No-tools Folding			
WARRANTY**	4 Year 1000 Hour Limited			



COMMERCIAL ENGINES

Powerful Kawasaki FX commercialgrade engines provide professional quality performance. Heavy-duty canister style air filtration system protects the engine from contaminants and prolongs product life.



SUPERIOR PRODUCTIVITY

Experience superior productivity with larger tires, a 7-gallon (26.5 liters) fuel tank, ground speeds up to 10 mph (16 km/h), and the innovative tool carrying capability of the TITAN HD. Toro has productivity in mind, on or off the mower.



EASY SERVICE

The flip-up floor panel and easy access to routine service points around the engine make service easy.



490-0001 ©2018 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted in this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940 or SAE J2723. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See retailer for warranty details. Engine warranty differs from product warranty.