

| ALL NEW TITAN® HD 2000 WITH MyRIDE® SUSPENSION SYSTEM | TITAN® HD 2000 SERIES WITH MyRIDE® SUSPENSION SYSTEM | | |
|--|--|-------|-------|
| | 74465 | 74466 | 74467 |

| | | | |
|----------------------------------|--|--------------|--------------|
| ENGINE* | Toro V-Twin 708cc 24.5 hp at 3600 rpm per SAE J1940 Gross | | |
| AIR FILTER | Heavy-duty Donaldson® canister style air filter | | |
| ELECTRIC START | Standard | | |
| DECK WIDTH | 48" (122 cm) | 52" (132 cm) | 60" (152 cm) |
| CUTTING DECK | TURBO FORCE* | | |
| DECK DEPTH | 5" (12.7 cm) | | |
| DECK CONSTRUCTION | 7/10-gauge high-strength steel | | |
| BULL-NOSE BUMPER | Standard | | |
| RUBBER DISCHARGE CHUTE | Standard | | |
| DECK SPINDLES | 8" (20.3 cm) Alum, Sealed Ball Bearings, 1" (2.5 cm) Shaft | | |
| HYDRAULIC DRIVE SYSTEM | ZT3100 | | |
| FUEL CAPACITY | 7 gallons (26.5 liters) | | |
| MAX GROUND SPEED (FWD) | Up to 9 mph (14.5 km/h) | | |
| MYRIDE® SUSPENSION SYSTEM | | | |
| COMFORT PLATFORM | MyRIDE® Suspension System | | |
| PLATFORM TRAVEL | 3.0" (7.62 cm) | | |
| SHOCKS | 1 center / 2 rear | | |
| SEAT | Deluxe seat with padded armrests | | |
| ADJUSTABILITY | 5 point adjustment on rear shocks | | |
| TOOL-MOUNTING CAPABILITY | Side Console / Rear Guard Ready | | |
| DECK LIFT ASSIST PEDAL | Standard | | |
| CUTTING HEIGHT | 1.5" - 5" (3.8 - 12.7 cm) in 0.25" (6 mm) increments | | |
| ROPS | No-tools Folding | | |
| WARRANTY** | 4 Year 750 Hour Limited | | |



COMMERCIAL ENGINES
Powerful Toro commercial-grade engines provide professional quality performance. Heavy-duty Donaldson® canister style air filtration system protects the engine from contaminants and prolongs product life.



COMMERCIAL-GRADE HYDRAULICS
The integrated pump and wheel motor uses proven commercial hydraulic components while eliminating hoses and other potential leak points. You'll get a smoother, faster response while enjoying an even more reliable machine.



MyRIDE® MAXIMUM COMFORT
The MyRIDE Suspension System features a suspended operator platform and adjustable rear shocks to provide a superior ride.



490-9999 ©2018 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted in this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940 or SAE J2723. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See retailer for warranty details. Engine warranty differs from product warranty.