

TITAN® HD

1500 SERIES

78450

2500 SERIES

78472

COMMERCIAL ENGINE AT 3600 RPM*	21 hp Kohler® 725cc	23.5 hp Kawasaki® FX 726cc
AIR FILTER	Heavy-duty Donaldson® canister style air filter	
STARTER	Electric	
DECK WIDTH	48" (121.9 cm)	60" (152 cm)
DRIVE TIRES	22" X 9.5" - 12" (55.9 X 24.1 - 30.5 cm)	24" x 12" - 12" (60.9 x 30.5 - 30.5 cm)
CASTER TIRES (CAGE BEARING)	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)	
CUTTING DECK	TURBO FORCE®	
DECK DEPTH	5" (12.7 cm)	5.5" (14 cm)
DECK CONSTRUCTION	7/10-gauge high-strength steel	
BULL-NOSE BUMPER	Standard	
RUBBER DISCHARGE CHUTE	Standard	
DECK SPINDLES	8" (20.3 cm) Alum, Sealed Ball Bearings, 1" (2.5 cm) Shaft	
HYDRAULIC DRIVE SYSTEM	ZT-3100 Integrated Pumps & Wheel Motors	ZT-3400 Integrated Pumps & Wheel Motors
FUEL CAPACITY	7 gallons (26.5 liters)	
MAX GROUND SPEED (FWD)	Up to 8 mph (12.9 km/h)	Up to 10 mph (16 km/h)
TOOL-MOUNTING CAPABILITY	Rear Guard Ready	Side Console / Rear Guard Ready
DECK LIFT ASSIST PEDAL	Standard	
CUTTING HEIGHT	1.5" - 5" (3.8 - 12.7 cm) in 0.25" (6 mm) increments	
ROPS	Standard	
WARRANTY**	4 Year 500 Hour Limited	4 Year 1000 Hour Limited



SPECIFICATIONS



COMMERCIAL ENGINES

Powerful commercial-grade engines provide professional quality performance. Heavy-duty Donaldson® canister style air filtration system protects the engine from contaminants and prolongs product life.



COMMERCIAL-GRADE HYDRAULICS

The integrated pump and wheel motor uses proven commercial hydraulic components while eliminating hoses and other potential leak points. You'll get a smoother, faster response while enjoying an even more reliable machine.



EASY SERVICE

The flip-up floor panel and easy access to routine service points around the engine make service easy.



490-0129 ©2018 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted in this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. *The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See retailer for warranty details. Engine warranty differs from product warranty.