



## 4.7–5.5 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



### VERSATILE ACCESSORIES

Enhance seasonal productivity with optional light kit, winter tires and flashers.



### POWER BROOM ATTACHMENT

Perfect for clearing snow down to the pavement on sidewalks and driveways, as well as clearing debris and dethatching grass. Designed for multi-season use.



### 2" SQUARE RECEIVER

Standard with the MULTI FORCE is the Power Arm with 2" receiver, providing a quick attachment point where attachments can be connected to the unit.



### BOSS® PLOW

The available 5-foot BOSS plow is designed with productivity, durability and operator safety in mind.

	74529	74523	74527 (Snow-Only Model)			
<b>POWER SYSTEM</b>						
Commercial Engines at 3600 RPM*	26.5 hp Kohler® Command PRO® EFI 747cc	26.5 hp Kohler Command PRO EFI 747cc	26.5 hp Kohler Command PRO EFI 747cc			
Starter	Electric	Electric	Electric			
Heavy-Duty Canister Air Cleaner	Standard	Standard	Standard			
Drive Tires	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	20" x 10" – 8" Snow Tires (50.8 x 25.4 – 20.3 cm)			
Caster Tires	11" x 4" – 5" (27.9 x 10.1 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.1 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.1 – 12.7 cm) Flat-Free Semi-Pneumatic			
Fuel/Capacity	Gas/10.5 Gal (39.7 L)	Gas/10.5 Gal (39.7 L)	Gas/10.5 Gal (39.7 L)			
Digital Hour Meter	Standard	Standard	Standard			
Hydraulic Drive System	Unitized Pumps & Wheel Motors (no hoses)	Unitized Pumps & Wheel Motors (no hoses)	Unitized Pumps & Wheel Motors (no hoses)			
Pump	10cc/rev	10cc/rev	10cc/rev			
Wheel Motor	10 cir	10 cir	10 cir			
Maximum Forward Speed	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)			
Clutch	Electromagnetic	Electromagnetic	N/A			
<b>MOWING DECKS</b>						
Deck Size	52" (132.1 cm)	60" (152.4 cm)	N/A			
Cutting Deck	7-Gauge TURBO FORCE®	7-Gauge TURBO FORCE	N/A			
Bull-Nose Bumper	Standard	Standard	N/A			
Adjustable Discharge Baffle	Standard	Standard	N/A			
Rubber Discharge Chute	Standard	Standard	N/A			
Deck Lift Design	Extension Spring	Extension Spring	N/A			
Spindle Housings	9 3/8" (23.8 cm) Diameter Cast Iron	9 3/8" (23.8 cm) Diameter Cast Iron	N/A			
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard	Standard	N/A			
Spindle Bearings	Maintenance-Free	Maintenance-Free	N/A			
Cutting Height	1.5" – 5.0" (3.8 – 12.7 cm)	1.5" – 5.0" (3.8 – 12.7 cm)	N/A			
Blades	.25" (.6 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel	N/A			
Blade Tip Speed	18,500+ ft/min	18,500+ ft/min	N/A			
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt	N/A			
Anti-Scalp Rollers	N/A	Standard	N/A			
Carrier Frame Construction	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	N/A			
<b>FEATURES</b>						
Steering Controls	Twin Lever	Twin Lever	Twin Lever			
Operator Platform	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension			
<b>WEIGHTS AND MEASUREMENTS</b>						
Weight	908 lbs.	411.9 kg	941 lbs.	426.8 kg	680 lbs.	308.4 kg
Height	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm
Deck Width	54"	137.2 cm	62"	157.5 cm	N/A	N/A
Deflector Width	68"	172.7 cm	76"	193 cm	N/A	N/A
Length (Platform Up)	61"	154.9 cm	65"	165.1 cm	61"	154.9 cm
Length (Platform Down)	75"	190.5 cm	79"	200.7 cm	75"	190.5 cm

\* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.