



1.8–2.9 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



FLAT-FREE CASTER TIRES

Semi-pneumatic caster tires eliminate time-consuming flats so mowers can spend more time in the field and less time in the shop.



COMMERCIAL-GRADE ENGINES

High-horsepower commercial engines deliver many hours of trouble-free life. Twin-cylinder design runs smooth and delivers excellent load response.



RUBBER DISCHARGE CHUTE

Patented flexible rubber discharge chute allows close trimming without damaging the chute or landscaping structures.



PATENTED TRU-TRAK® SULKY

Large, independently pivoting foot plates reduce operator fatigue. The two-point connection eliminates jack-knifing in turns or reverse.

FLOATING DECK GEAR DRIVE		FLOATING DECK HYDRO DRIVE		FIXED DECK GEAR DRIVE				FIXED DECK HYDRO DRIVE			
39074† 14.5 hp Kawasaki® FS (603cc)	39078† 15 hp Kawasaki (603cc)	30488 18.5 hp Kawasaki (603cc)	30489 18.5 hp Kawasaki (603cc)	30632 14.5 hp Kawasaki (603cc)	39634† 14.5 hp Kawasaki (603cc)	39638† 14.5 hp Kawasaki (603cc)	30672† 14.5 hp Kawasaki (603cc)	39674† 14.5 hp Kawasaki (603cc)	39678† 14.5 hp Kawasaki (603cc)	39934† 14.5 hp Kawasaki (603cc)	39938† 14.5 hp Kawasaki (603cc)

POWER SYSTEM Commercial Engines at 3600 RPM*

Starter	Recoil	Electric	Recoil							
Drive Tires	16" x 7.5" – 8" (40.6 x 19.1 – 20.3 cm)		13" x 5" – 6" (33 x 12.7 – 15.2 cm)	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm)	13" x 5" – 6" (33 x 12.7 – 15.2 cm)	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm)	9" x 3.5" – 4" (22.9 x 8.9 – 10.2 cm) Flat-Free Semi-Pneumatic		16" x 7.5" – 8" (40 x 19 – 20.3 cm)	
Caster Tires	9" x 3.5" – 4" (22.9 x 8.9 – 10.2 cm) Flat-Free Semi-Pneumatic		9" x 3.5" – 4" (22.9 x 8.9 – 10.2 cm) Flat-Free Semi-Pneumatic							
Fuel/Capacity	Gas/5 Gal (18.9 L)		Gas/5 Gal (18.9 L)							
Control System	T-Bar	Twin Lever	Pistol Grips				T-Bar		Pistol Grips	
Transmission	5-Speed Gearbox with 9 Spline Coupler	Hydro-Gear 10cc Pumps and Parker Motors	5-Speed Gearbox with 9 Spline Coupler				Hydro-Gear 10cc Pumps and Parker Motors		Hydro-Gear 10cc Pumps and Parker Motors	
Hour Meter	—		—		—		—		—	
Maximum Forward Speed	6.2 mph (10 km/h)		6.2 mph (10 km/h)							
Brake System	6" (15.2 cm) Band Brakes; Manual Parking brake	Hydraulic Service Brakes; Manual Parking Brake	6" (15.2 mm) Band Brakes				Hydraulic Service Brakes; Manual Parking Brake		Hydraulic Service Brakes; Manual Parking Brake	

MOWING DECKS

Deck Size	36" (91.4 cm)	48" (121.9 cm)	48" (121.9 cm)	52" (132.1 cm)	32" (81.3 cm)	36" (91.4 cm)	48" (121.9 cm)	32" (81.3 cm)	36" (91.4 cm)	48" (121.9 cm)	36" (91.4 cm)	48" (121.9 cm)
Cutting Deck	TURBO FORCE [†]				TURBO FORCE ¹							
Bull-Nose Bumper	Standard				Standard ¹							
Adjustable Discharge Baffle	Standard				Standard							
Rubber Discharge Chute	Standard				Standard							
Spindle Housings	9 3/8" (23.8 cm) Diameter Cast Iron				Cast Aluminum	9 3/8" (23.8 cm) Diameter Cast Iron		Cast Aluminum	9 3/8" (23.8 cm) Diameter Cast Iron			
Spindle Bearings	Sealed Ball Bearings				Sealed Ball Bearings							
Cutting Height	1.0" – 4.5" (2.5 – 11.4 cm) Quick Change				1.0" – 4.25" (2.5 – 10.8 cm)							
Blades	(2) 1/4" (.6 cm) Heat-Treated Steel (3) 1/4" (.6 cm) Heat-Treated Steel				(2) .204" (.5 cm) Steel	(2) 1/4" (.6 cm) Heat-Treated Steel (3) 1/4" (.6 cm) Heat-Treated Steel		(2) .204" (.5 cm) Steel	(2) 1/4" (.6 cm) Heat-Treated Steel (3) 1/4" (.6 cm) Heat-Treated Steel			
Blade Tip Speed	18,000+ ft/min				18,000+ ft/min							
Belt Construction	Aramid Fiber V-Belt				Aramid Fiber V-Belt							
Anti-Scalp Rollers	2 Front	3 Front, Optional 2 Rear		4 Front, 2 Rear	N/A							

WEIGHTS AND MEASUREMENTS

Weight	588 lbs. (266.7 kg)	649 lbs. (294.4 kg)	682 lbs. (309.3 cm)	721 lbs. (327 kg)	402 lbs. (182.3 kg)	462 lbs. (209.6 kg)	500 lbs. (226.7 kg)	400 lbs. (181.4 kg)	460 lbs. (208.6 kg)	498 lbs. (225.8 kg)	460 lbs. (208.6 kg)	498 lbs. (225.8 kg)
Height	41" (104.1 cm)	41" (104.1 cm)	46" (116.8 cm)	46" (116.8 cm)	41" (104.1 cm)	41" (104.1 cm) [†]	41" (104.1 cm)	41" (104.1 cm)	41" (104.1 cm)	41" (104.1 cm)	41" (104.1 cm)	41" (104.1 cm)
Deck Clearance Width	37.2" (94.5 cm)	49.6" (126 cm)	49.6" (126 cm)	53.7" (136.4 cm)	32.8" (83.3 cm)	37.1" (94.2 cm)	49.6" (126 cm)	32.8" (83.3 cm)	37.1" (94.2 cm)	49.6" (126 cm)	37.1" (94.2 cm)	49.6" (126 cm)
Deflector Width	51.1" (129.8 cm)	63.5" (161.3 cm)	63.5" (161.3 cm)	67.6" (171.7 cm)	45.8" (116.3 cm)	46.6" (118.4 cm)	63.5" (161.3 cm)	45.8" (116.3 cm)	46.6" (118.4 cm)	63.5" (161.3 cm)	46.6" (118.4 cm)	63.5" (161.3 cm)
Length	82.7" (210.1 cm)	82" (208.3 cm)	77.8" (197.6 cm)	77.8" (197.6 cm)	78" (198.1 cm)	80" (203.2 cm)	78.3" (198.9 cm)	72" (182.9 cm)	74" (188 cm)	72.3" (183.6 cm)	74" (188 cm)	72.3" (183.6 cm)

¹ 32" Fixed Deck Type: 7/10 Fixed Deck Deck Construction: Fabricated Steel, 10-gauge top, 7-gauge skirt

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

[†]CARB compliant model.