



## 3.9–4.9 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



### INNOVATIVE TOOL CARRYING

Save time and improve efficiency with TITAN HD's unique ability to easily attach tools and accessories directly to the mower with the innovative tool-mounting brackets.



### TORO V-TWIN ENGINES

The powerful commercial-grade engines deliver professional quality performance, and the heavy-duty Donaldson® canister air filtration system prolongs product life.



### ENHANCED MYRIDE® COMFORT

The MyRIDE Suspension System includes a suspended operator platform and adjustable rear shocks to provide a superior ride.



### COMMERCIAL-GRADE HYDRAULICS

Get the ideal blend of smooth response and long-term reliability. Integrated pump and wheel motor with proven commercial hydraulic components eliminates hoses and other potential leak points.

|  | 74465<br>MyRIDE® Suspension System                              | 74466<br>MyRIDE Suspension System                               | 74467<br>MyRIDE Suspension System                               | 74463<br>Rear Discharge   | 74480<br>Special Edition  |          |            |          |            |          |
|--|---|---|---|---|---|----------|------------|----------|------------|----------|
| <b>POWER SYSTEM</b>                              |   |   |   |   |   |          |            |          |            |          |
| Commercial Engines at 3600 RPM*                  | 24.5 hp* Toro® V-Twin (708cc)                                   | 24.5 hp* Toro V-Twin (708cc)                                    | 24.5 hp* Toro V-Twin (708cc)                                    | 25 hp Kohler (747cc)  | 23.5 hp* Kawasaki FX (726cc)                                    |          |            |          |            |          |
| Starter  | Electric  | Electric  | Electric  | Electric  | Electric  |          |            |          |            |          |
| Heavy-Duty Donaldson® Canister-Style Air Cleaner | Standard  | Standard  | Standard  | Standard  | Standard  |          |            |          |            |          |
| Drive Tires                                      | 23" x 9.5" - 12" (58.4 x 24.1 - 30.5 cm)                        | 23" x 9.5" - 12" (58.4 x 24.1 - 30.5 cm)                        | 23" x 10.5" - 12" (58.4 x 26.7 - 30.5 cm)                       | 23" x 10.5" - 12" (58.4 x 26.7 - 30.5 cm)                       | 24" x 12" - 12" (61 x 30.5 - 30.5 cm)                           |          |            |          |            |          |
| Caster Tires (Cage Bearing)                      | 13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)                           | 13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)                           | 13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)                           | 13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)                           | 13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)                           |          |            |          |            |          |
| Fuel/Capacity                                    | Gas/7 Gal (26.5 L)  | Gas/7 Gal (26.5 L)  | Gas/7 Gal (26.5 L)  | Gas/7 Gal (26.5 L)  | Gas/7 Gal (26.5 L)  |          |            |          |            |          |
| Digital Hour Meter                               | Standard  | Standard  | Standard  | Standard  | Standard  |          |            |          |            |          |
| Hydraulic Drive System                           | ZT-3100 Integrated Pumps & Wheel Motors                         | ZT-3100 Integrated Pumps & Wheel Motors                         | ZT-3100 Integrated Pumps & Wheel Motors                         | ZT-3400 Integrated Pumps & Wheel Motors                         | ZT-3400 Integrated Pumps & Wheel Motors                         |          |            |          |            |          |
| Maximum Forward Speed                            | 9 mph (14.5 km/h)   | 9 mph (14.5 km/h)   | 9 mph (14.5 km/h)   | 9 mph (14.5 km/h)   | 9 mph (14.5 km/h)   |          |            |          |            |          |
| Clutch   | Electromagnetic   | Electromagnetic   | Electromagnetic   | Electromagnetic   | Electromagnetic   |          |            |          |            |          |
| <b>MOWING DECKS</b>                              |   |   |   |   |   |          |            |          |            |          |
| Deck Size  | 48" (121.9 cm)  | 52" (132.1 cm)  | 60" (152.4 cm)  | 60" (152.4 cm)  | 60" (152.4 cm)  |          |            |          |            |          |
| Cutting Deck                                     | 7/10-Gauge High-Strength Steel TURBO FORCE®                     | 7/10-Gauge High-Strength Steel TURBO FORCE                      | 7/10-Gauge High-Strength Steel TURBO FORCE                      | 7/10-Gauge High-Strength Steel TURBO FORCE (Rear Discharge)     | 7/10-Gauge High-Strength Steel TURBO FORCE (Rear Discharge)     |          |            |          |            |          |
| Bull-Nose Bumper                                 | Standard  | Standard  | Standard  | Standard  | Standard  |          |            |          |            |          |
| Rubber Discharge Chute                           | Standard  | Standard  | Standard  | Standard  | Standard  |          |            |          |            |          |
| Deck Lift Design                                 | Extension Spring  | Extension Spring  | Extension Spring  | Extension Spring  | Extension Spring  |          |            |          |            |          |
| Spindle Housings                                 | 8" (20.3 cm) Diameter Aluminum                                  | 8" (20.3 cm) Diameter Aluminum                                  | 8" (20.3 cm) Diameter Aluminum                                  | 8" (20.3 cm) Diameter Aluminum                                  | 8" (20.3 cm) Diameter Aluminum                                  |          |            |          |            |          |
| 1" (2.5 cm) Spindle Shaft                        | Standard  | Standard  | Standard  | Standard  | Standard  |          |            |          |            |          |
| Spindle Bearings                                 | Maintenance-Free  | Maintenance-Free  | Maintenance-Free  | Maintenance-Free  | Maintenance-Free  |          |            |          |            |          |
| Cutting Height                                   | 1.5" - 5" (.25" increments)<br>3.8 - 12.7 cm (.6 cm increments) | 1.5" - 5" (.25" increments)<br>3.8 - 12.7 cm (.6 cm increments) | 1.5" - 5" (.25" increments)<br>3.8 - 12.7 cm (.6 cm increments) | 1.5" - 5" (.25" increments)<br>3.8 - 12.7 cm (.6 cm increments) | 1.5" - 5" (.25" increments)<br>3.8 - 12.7 cm (.6 cm increments) |          |            |          |            |          |
| Deck Depth                                       | 5" (12.7 cm)  | 5" (12.7 cm)  | 5" (12.7 cm)  | 5" (12.7 cm)  | 5.5" (14 cm)  |          |            |          |            |          |
| Blades   | .204" (.5 cm)<br>Heat-Treated Steel                             | .204" (.5 cm)<br>Heat-Treated Steel                             | .204" (.5 cm)<br>Heat-Treated Steel                             | .204" (.5 cm)<br>Heat-Treated Steel                             | .204" (.5 cm)<br>Heat-Treated Steel                             |          |            |          |            |          |
| Blade Tip Speed                                  | 18,500+ ft/min  | 18,500+ ft/min  | 18,500+ ft/min  | 18,500+ ft/min  | 18,500+ ft/min  |          |            |          |            |          |
| Belt Construction                                | Aramid Fiber V-Belt   | Aramid Fiber V-Belt   | Aramid Fiber V-Belt   | Aramid Fiber V-Belt   | Aramid Fiber V-Belt   |          |            |          |            |          |
| <b>FEATURES</b>                                  |   |   |   |   |   |          |            |          |            |          |
| <b>MyRIDE® Suspension System</b>                 |   |   |   |   |   |          |            |          |            |          |
| Comfort Platform                                 | MyRIDE Suspension System  | MyRIDE Suspension System  | MyRIDE Suspension System  | N/A   | MyRIDE Suspension System  |          |            |          |            |          |
| Platform Travel                                  | 3.0" (7.62 cm)  | 3.0" (7.62 cm)  | 3.0" (7.62 cm)  | N/A   | 3.0" (7.62 cm)  |          |            |          |            |          |
| Shocks   | 1 center / 2 rear   | 1 center / 2 rear   | 1 center / 2 rear   | N/A   | 1 center / 2 rear   |          |            |          |            |          |
| Seat   | Deluxe Seat with Armrests                                       | Deluxe Seat with Armrests                                       | Deluxe Seat with Padded Armrests                                | N/A   | High-Back Adjustable w/ Armrests                                |          |            |          |            |          |
| Adjustability                                    | 5 Detents, Infinite Adjustability                               | 5 Detents, Infinite Adjustability                               | 5 Detents, Infinite Adjustability                               | N/A   | 5 Detents, Infinite Adjustability                               |          |            |          |            |          |
| Steering Controls                                | 1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened              | 1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened              | 1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened              | 1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened              | 1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened              |          |            |          |            |          |
| Operator Seat                                    | N/A   | N/A   | N/A   | High-Back Adjustable Suspension Seat                            | High-Back Adjustable Suspension Seat                            |          |            |          |            |          |
| Folding ROPS                                     | Standard  | Standard  | Standard  | Standard  | Standard  |          |            |          |            |          |
| Tool-Mounting Capability                         | Side Console / Rear Guard Ready                                 | Side Console / Rear Guard Ready                                 | Side Console / Rear Guard Ready                                 | Side Console / Rear Guard Ready                                 | Side Console / Rear Guard Ready                                 |          |            |          |            |          |
| Lift Mechanism                                   | Quick-Attach Jack Ready   | Quick-Attach Jack Ready   | Quick-Attach Jack Ready   | Quick-Attach Jack Ready   | Quick-Attach Jack Ready   |          |            |          |            |          |
| Warranty**                                       | 4 Year 750 Hour Limited   | 4 Year 750 Hour Limited   | 4 Year 750 Hour Limited   | 4 Year 750 Hour Limited   | 4 Year 750 Hour Limited   |          |            |          |            |          |
| <b>WEIGHTS AND MEASUREMENTS</b>                  |   |   |   |   |   |          |            |          |            |          |
| Weight   | 870 lbs.  | 394.6 kg  | 890 lbs.  | 403.7 kg  | 920 lbs.  | 417.3 kg | 1,012 lbs. | 459 kg   | 1,036 lbs. | 470 kg   |
| ROPS Height (Folded)                             | 49"   | 124.5 cm  | 49"   | 124.5 cm  | 49"   | 124.5 cm | 49"        | 124.5 cm | 49"        | 124.5 cm |
| ROPS Height (Upright)                            | 70.5"   | 179.1 cm  | 70.5"   | 179.1 cm  | 70.5"   | 179.1 cm | 70.5"      | 179.1 cm | 70.5"      | 179.1 cm |
| Deck Clearance Width                             | 53"   | 134.6 cm  | 56.75"  | 144.1 cm  | 63.5"   | 161.3 cm | 66"        | 167.6 cm | 53"        | 134.6 cm |
| Deflector Width                                  | 63.25"  | 160.7 cm  | 67.25"  | 170.8 cm  | 75.25"  | 191.1 cm | 75.25"     | 191.1 cm | 63.25"     | 160.7 cm |
| Length   | 82"   | 208.3 cm  | 82"   | 208.3 cm  | 83"   | 210.8 cm | 84.25"     | 214 cm   | 82"        | 208.3 cm |

\* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. \*\*See your local Toro dealer or consult owners manual for complete warranty details