



4.7–5.5 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



ENHANCED COMFORT

From the standard suspension seat and isolated floor pan design to the deck step guide and easy-to-use controls, TITAN HD is designed with all-day comfort in mind.




SUPERIOR PRODUCTIVITY

Larger tires, faster ground speeds up to 10 mph, a 4-year/1,000-hour limited warranty and commercial ZT3400 transmissions make the 2500 Series our most productive.



KAWASAKI® ENGINES

Professional-quality engines feature a heavy-duty canister-style air filtration system that protects the engine from contaminants and prolongs product life.



COMMERCIAL-GRADE HYDRAULICS

Integrated pump and wheel motor eliminates hoses and other potential leak points for reliability and a smoother, faster response.

	74471		74472	
POWER SYSTEM				
Commercial Engines at 3600 RPM*	22 hp* Kawasaki FX (726cc)		23.5 hp* Kawasaki FX (726cc)	
Starter	Electric		Electric	
Heavy-Duty Canister Air Cleaner	Standard		Standard	
Drive Tires	24" x 9.5" – 12" (60.9 x 24.1 – 30.5 cm)		24" x 12" – 12" (60.9 x 30.5 – 30.5 cm)	
Caster Tires	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Taper Roller		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Taper Roller	
Fuel/Capacity	Gas/7 Gal (26.5 L)		Gas/7 Gal (26.5 L)	
Digital Hour Meter	Standard		Standard	
Hydraulic Drive System	ZT-3400 Integrated Pumps & Wheel Motors		ZT-3400 Integrated Pumps & Wheel Motors	
Maximum Forward Speed	10 mph (16.1 km/h)		10 mph (16.1 km/h)	
Clutch	Electromagnetic		Electromagnetic	
MOWING DECKS				
Deck Size	52" (132.1 cm)		60" (152.4 cm)	
Cutting Deck	7/10-Gauge High-Strength Steel TURBO FORCE		7/10-Gauge High-Strength Steel TURBO FORCE	
Bull-Nose Bumper	Standard		Standard	
Rubber Discharge Chute	Standard		Standard	
Deck Lift Design	Extension Spring		Extension Spring	
Spindle Housings	8" (20.3 cm) Diameter Aluminum		8" (20.3 cm) Diameter Aluminum	
1" (2.5 cm) Spindle Shaft	Standard		Standard	
Spindle Bearings	Maintenance-Free		Maintenance-Free	
Cutting Height	1.5" - 5" (.25" increments) 3.8 – 12.7 cm (.6 cm increments)		1.5" - 5" (.25" increments) 3.8 – 12.7 cm (.6 cm increments)	
Deck Depth	5.5 (13.9 cm)"		5.5 (13.9 cm)"	
Blades	.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel	
Blade Tip Speed	18,500+ ft/min		18,500+ ft/min	
Belt Construction	Aramid Fiber V-Belt		Aramid Fiber V-Belt	
FEATURES				
Steering Controls	1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened		1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened	
Operator Seat	High-Back Adjustable Suspension Seat		High-Back Adjustable Suspension Seat	
Arm Rests	Standard		Standard	
Folding ROPS	Standard		Standard	
Tool-Mounting Capability	Side Console / Rear Guard Ready		Side Console / Rear Guard Ready	
Lift Mechanism	Quick-Attach Jack Ready		Quick-Attach Jack Ready	
Floor Pan	Iso-Mount Flip-Up		Iso-Mount Flip-Up	
Warranty**	4 Year 1,000 Hour Limited		4 Year 1,000 Hour Limited	
WEIGHTS AND MEASUREMENTS				
Weight	957 lbs.	434.1 kg	1,006 lbs.	456.3 kg
ROPS Height (Folded)	49"	124.5 cm	49"	124.5 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	56.75"	144.1 cm	63.5"	161.3 cm
Deflector Width	67.25"	170.8 cm	75.25"	191.1 cm
Length	82"	208.3 cm	83"	210.8 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See your local Toro dealer or consult owners manual for complete warranty details