

1.1 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



	22210	22215
POWER SYSTEM		
Commercial Engines at 3600 RPM*	Kawasaki® 179cc FJ180V Commercial	Kawasaki® 179cc FJ180V Commercial
Starter	Recoil	Recoil
Tires	Front: 9" x 2" (22.8 cm x 5.0 cm) Rubber Tire w/ Co-Polymer Wheels Rear: 10.5" x 3" (26.6 cm x 7.6 cm) Rubber Tire w/ Co-Polymer Wheels	Front: 9" x 2" (22.8 cm x 5.0 cm) Rubber Tire w/ Co-Polymer Wheels Rear: 10.5" x 3" (26.6 cm x 7.6 cm) Rubber Tire w/ Co-Polymer Wheels
Fuel/Capacity	Gas/1 Gal (3.8 L)	Gas/1 Gal (3.8 L)
Transmission	Variable Speed RWD	Heavy Duty Variable Speed RWD
Control System	Two Bail Control System	Two Bail Control System
Maximum Forward Speed	Variable up to 4.1 mph (6.6 km/h)	Variable up to 4.0 mph (6.4 km/h)
MOWING DECK		
Deck Size	30" (76.2 cm)	30" (76.2 cm)
Deck Type	Mulch/Rear Bag/Side Discharge	Mulch/Rear Bag/Side Discharge
Deck Construction	13-Gauge Steel Deck / Cast Aluminum Frame	13-Gauge Steel Deck / Cast Aluminum Frame
Spindle Assemblies	Die Cast Spindle, 17 mm Cold Formed Spindle Shafts	Die Cast Spindle, 17 mm Cold Formed Spindle Shafts
Cutting Height	1.5" – 5.0" in 1/2" increments (3.8 – 12.7 cm in .6 cm increments)	1.5" – 5.0" in 1/2" increments (3.8 – 12.7 cm in .6 cm increments)
Blades	(2) .135" (.3 cm) Thick Steel	(2) .135" (.3 cm) Thick Steel
Blade Engagement	Blade Brake Clutch (BBC)	Blade Brake Clutch (BBC)
Blade Tip Speed	18,000+ ft/min	18,000+ ft/min
WEIGHT AND MEASUREMENTS		
Weight	170 lbs. (77.1 kg) Dry Mulch Mode	173 lbs. (78.4 kg) Dry Mulch Mode
Height**	41" (104.1 cm)	41" (104.1 cm)
Width	32" (81.3 cm)	32" (81.3 cm)
Length**	66" (167.6 cm)	66" (167.6 cm)

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

** Height-of-Cut in position 3, handle assembled and in the highest position.



TWO-BAIL CONTROL SYSTEM

Provides excellent control and is easy to operate.



BLADE BRAKE CLUTCH (BBC)

Allows operator to disengage the blades without shutting off the engine.



COMMERCIAL-GRADE WHEELS

Rubber tires with co-polymer wheels feature precision ball bearings for long life with less downtime and lower replacement costs.



2-POINT HEIGHT OF CUT

Heavy-duty 2-point Height of Cut (HOC) system makes it easy to adjust deck height. No need to walk around the mower to adjust four different levers.



HIGHLY PRODUCTIVE 30" DECK

3-in-1 deck design provides mulching, bagging or side-discharge and helps you finish the job faster.