

	74952		74949		75932		74950		74958		75936		74959	
					MyRIDE® Suspension System						MyRIDE Suspension System			
POWER SYSTEM														
Commercial Engines at 3600 RPM*	20.5 hp Kawasaki® FX (726cc)		24.5 hp Kawasaki FX (852cc)		24.5 hp Kawasaki FX (852cc)		25.5 hp Kawasaki FX (852cc)		25 hp Kohler Command PRO EFI (747cc)		25.5 hp Kawasaki FX (852cc)		25 hp Kohler® Command PRO (747cc)	
Starter	Electric		Electric		Electric		Electric		Electric		Electric		Electric	
Heavy-Duty Canister Air Cleaner	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Drive Tires	23" x 9.5" – 12" (58.4 x 24.1 – 30.5 cm)		23" x 9.5" – 12" (58.4 x 24.1 – 30.5 cm)		23" x 9.5" – 12" (58.4 x 24.1 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)	
Caster Tires	13" x 5" – 6" (33 x 12.7 – 15.2 cm) Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic		13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic	
Fuel/Capacity	Gas/8 Gal (30.3 L)		Gas/8 Gal (30.3 L)		Gas/8 Gal (30.3 L)		Gas/8 Gal (30.3 L)		Gas/8 Gal (30.3 L)		Gas/8 Gal (30.3 L)		Gas/8 Gal (30.3 L)	
Digital Hour Meter	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Hydraulic Drive System	Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors		Unitized Pumps & Wheel Motors	
Pump	12cc/rev		12cc/rev		12cc/rev		12cc/rev		12cc/rev		12cc/rev		12cc/rev	
Wheel Motor	14.6 cir		14.6 cir		14.6 cir		14.6 cir		14.6 cir		14.6 cir		14.6 cir	
Maximum Forward Speed	8.5 mph (13.7 km/h)		8.5 mph (13.7 km/h)		8.5 mph (13.7 km/h)		10 mph (16.1 km/h)		10 mph (16.1 km/h)		10 mph (16.1 km/h)		10 mph (16.1 km/h)	
Clutch	Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic	
MOWING DECKS														
Deck Size	48" (121.9 cm)		52" (132.1 cm)		52" (132.1 cm)		60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		72" (182.9 cm)	
Cutting Deck	7-Gauge TURBO FORCE†		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE	
Bull-Nose Bumper	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Adjustable Discharge Baffle	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Rubber Discharge Chute	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Deck Lift Design	Extension Spring		Extension Spring		Extension Spring		Extension Spring		Extension Spring		Extension Spring		Extension Spring	
Spindle Housings	9" (22.9 cm) Diameter Cast Iron		9" (22.9 cm) Diameter Cast Iron		9" (22.9 cm) Diameter Cast Iron		9" (22.9 cm) Diameter Cast Iron		9" (22.9 cm) Diameter Cast Iron		9" (22.9 cm) Diameter Cast Iron		9" (22.9 cm) Diameter Cast Iron	
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Spindle Bearings	Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free	
Cutting Height	1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)		1.0" – 5.5" (2.5 – 14 cm)	
Deck Depth	5.5" (14 cm)		5.5" (14 cm)		5.5" (14 cm)		5.5" (14 cm)		5.5" (14 cm)		5.5" (14 cm)		5.5" (14 cm)	
Blades	.25" (.6 cm) Heat-Treated Steel		.25" (.6 cm) Heat-Treated Steel		.25" (.6 cm) Heat-Treated Steel		.25" (.6 cm) Heat-Treated Steel		.25" (.6 cm) Heat-Treated Steel		.25" (.6 cm) Heat-Treated Steel		.25" (.6 cm) Heat-Treated Steel	
Blade Tip Speed	18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min	
Belt Construction	Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt	
Anti-Scalp Rollers	3 Standard, 1 Optional		3 Standard, 1 Optional		4 Standard, 1 Optional		4 Standard, 1 Optional		4 Standard, 1 Optional		4 Standard, 1 Optional		4 Standard, 1 Optional	
Carrier Frame Construction	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)	
FEATURES														
Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened	
Operator Seat	Deluxe Suspension with 3-D Isolation Mounts		Deluxe Suspension with 3-D Isolation Mounts		MyRIDE Suspension System		Deluxe Suspension with 3-D Isolation Mounts		Deluxe Suspension with 3-D Isolation Mounts		MyRIDE Suspension System		Deluxe Suspension with 3-D Isolation Mounts	
Arm Rests	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Seat Suspension System	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Folding ROPS	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Storage Compartment	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Foot Pedal Deck Lift	Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Z Stand	Optional		Optional		Optional		Optional		Optional		Optional		Optional	
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access		Pierced, Extruded Tread; No-Tools Deck Access	
WEIGHTS AND MEASUREMENTS														
Weight	1,048 lbs.	475.4 kg	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,165 lbs.	528.4 kg	1,185 lbs.	537.5 kg	1,185 lbs.	537.5 kg	1,255 lbs.	569.3 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	49.7"	126.2 cm	53.7"	136.4 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm
Deflector Width	63.6"	161.5 cm	67.6"	171.7 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm
Length	79.2"	201.2 cm	79.2"	201.2 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

†CARB compliant model or model available.