

74933†

74934†

POWER SYSTEM

Commercial Engines at 3600 RPM*	Kohler® Command PRO EFI Propane (725cc)	Kohler Command PRO EFI Propane (725cc)
Starter	Electric	Electric
Heavy-Duty Canister Air Cleaner	Standard	Standard
Drive Tires	24" x 12" – 12" (61 x 30.5 – 30.5 cm)	24" x 12" – 12" (61 x 30.5 – 30.5 cm)
Caster Tires	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic
Fuel/Capacity	Liquid Propane/43.5 lbs	Liquid Propane/43.5 lbs
Hour Meter	Smart Hour Meter	Smart Hour Meter
Hydraulic Drive System	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors
Pump	12cc/rev (shock valves)	12cc/rev (shock valves)
Wheel Motor	14.6 cir	14.6 cir
Maximum Forward Speed	10 mph (16.1 km/h)	10 mph (16.1 km/h)
Clutch	Electromagnetic	Electromagnetic

MOWING DECKS

Deck Size	60" (152.4 cm)	72" (182.9 cm)
Cutting Deck	7-Gauge TURBO FORCE*	7-Gauge TURBO FORCE
Bull-Nose Bumper	Standard	Standard
Adjustable Discharge Baffle	Standard	Standard
Rubber Discharge Chute	Standard	Standard
Deck Lift Design	Extension Spring	Extension Spring
Spindle Housings	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard	Standard
Spindle Bearings	Maintenance-Free	Maintenance-Free
Cutting Height	1.0" – 5.5" (2.5 – 14 cm)	1.0" – 5.5" (2.5 – 14 cm)
Blades	.25" (.6 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel
Blade Tip Speed	18,500+ ft/min	18,500+ ft/min
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt
Anti-Scalp Rollers	4 Standard, 1 Optional	6 Standard, 1 Optional
Carrier Frame Construction	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)

FEATURES

Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened
Operator Seat	Deluxe Suspension with 3-D Isolation Mounts	Deluxe Suspension with 3-D Isolation Mounts
Arm Rests	Standard	Standard
Seat Suspension System	Standard	Standard
Folding ROPS	Standard	Standard
Storage Compartment	Standard	Standard
Foot Pedal Deck Lift	Standard	Standard
Z Stand	Optional	Optional
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access

WEIGHTS AND MEASUREMENTS

Weight	1,397 lbs.	633.7 kg	1,467 lbs.	665.4 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	61.7"	156.7 cm	73.6"	186.9 cm
Deflector Width	75.7"	192.3 cm	87.6"	222.5 cm
Length	83.1"	211.1 cm	87.3"	221.7 cm

* The gross horsepower of these propane engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

†CARB compliant model or model available.



Z MASTER®

5000 SERIES PROPANE MOWERS

**OPERATOR COMFORT**

Deluxe suspension seat features thick cushions, large bolsters and 3-D isolator mounts that absorb bumps and vibrations to reduce operator fatigue.

**SMOOTH, POWERFUL RESPONSE**

The 12cc unitized pump and wheel motor eliminates hoses and potential leak points for a smoother, faster response.

GET THE ADVANTAGES OF PROPANE without sacrificing power and features. These models help reduce emissions and fuel costs while extending engine life.

INCREASE VISIBILITY AND STABILITY and vaporization capacity with the single 43.5 lb. tank mounted behind the seat.

ELIMINATE EVAPORATIVE EMISSIONS and fuel contamination, theft and spillage with the full sealed system.

5.5–6.5 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.