

	74926	74960	75967 MyRIDE [™] Suspension System	74969 Horizon [™] Technology	74946 Horizon Technology	74928	74961	75968 MyRIDE Suspension System	74947 Horizon Technology
POWER SYSTEM									
Commercial Engines at 3600 RPM*	26.5 hp Kohler [™] Command PRO EFI (747cc)	31 hp Kawasaki [™] FX (999cc)	31 hp Kawasaki FX (999cc)	29.5 hp Kawasaki FX EFI (852cc)	34 hp Kohler Command PRO EFI (999cc)	26.5 hp Kohler Command PRO EFI (747cc)	31 hp Kawasaki FX (999cc)	31 hp Kawasaki FX (999cc)	34 hp Kohler Command PRO EFI (999cc)
Electric Start	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Heavy-Duty Canister Air Cleaner	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Drive Tires	24" x 12" – 12" (61 x 30.5 – 30.5 cm)	24" x 12" – 12" (61 x 30.5 – 30.5 cm)	24" x 12" – 12" (61 x 30.5 – 30.5 cm)	24" x 12" – 12" (61 x 30.5 – 30.5 cm)	24" x 12" – 12" (61 x 30.5 – 30.5 cm)	24" x 12" – 12" (61 x 30.5 – 30.5 cm)	24" x 12" – 12" (61 x 30.5 – 30.5 cm)	24" x 12" – 12" (61 x 30.5 – 30.5 cm)	24" x 12" – 12" (61 x 30.5 – 30.5 cm)
Caster Tires	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic
Fuel/Capacity	Gas/12 Gal (45.4 L)	Gas/12 Gal (45.4 L)	Gas/12 Gal (45.4 L)	Gas/12 Gal (45.4 L)	Gas/12 Gal (45.4 L)	Gas/12 Gal (45.4 L)	Gas/12 Gal (45.4 L)	Gas/12 Gal (45.4 L)	Gas/12 Gal (45.4 L)
Hour Meter	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Hydraulic Drive System	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors
Pump	16cc/rev	16cc/rev	16cc/rev	16cc/rev	16cc/rev	16cc/rev	16cc/rev	16cc/rev	16cc/rev
Wheel Motor	17.1 cir	17.1 cir	17.1 cir	17.1 cir	17.1 cir	17.1 cir	17.1 cir	17.1 cir	17.1 cir
Maximum Forward Speed	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)
Clutch	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic
MOWING DECKS									
Deck Size	60" (152.4 cm)	60" (152.4 cm)	60" (152.4 cm)	60" (152.4 cm)	60" (152.4 cm)	72" (182.9 cm)	72" (182.9 cm)	72" (182.9 cm)	72" (182.9 cm)
Cutting Deck	7-Gauge TURBO FORCE [™]	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE
Bull-Nose Bumper	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Adjustable Discharge Baffle	Standard, Tools-Free	Standard, Tools-Free	Standard, Tools-Free	Standard, Tools-Free	Standard, Tools-Free	Standard, Tools-Free	Standard, Tools-Free	Standard, Tools-Free	Standard, Tools-Free
Rubber Discharge Chute	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Deck Lift Design	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring
Spindle Housings	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Spindle Bearings	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free
Cutting Height	1.0" – 5.5" (2.5 cm – 14 cm)	1.0" – 5.5" (2.5 cm – 14 cm)	1.0" – 5.5" (2.5 cm – 14 cm)	1.0" – 5.5" (2.5 cm – 14 cm)	1.0" – 5.5" (2.5 cm x 14 cm)	1.0" – 5.5" (2.5 cm – 14 cm)	1.0" – 5.5" (2.5 cm – 14 cm)	1.0" – 5.5" (2.5 cm – 14 cm)	1.0" – 5.5" (2.5 cm – 14 cm)
Blades	.25" (.6 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel
Blade Tip Speed	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt
Anti-Scalp Rollers	4 Standard, 1 Optional	4 Standard, 1 Optional	4 Standard, 1 Optional	4 Standard, 1 Optional	4 Standard, 1 Optional	4 Standard, 1 Optional	4 Standard, 1 Optional	4 Standard, 1 Optional	4 Standard, 1 Optional
Carrier Frame Construction	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm – 10-Gauge)	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm – 10-Gauge)	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm – 10-Gauge)	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm – 10-Gauge)	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm – 10-Gauge)	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm – 10-Gauge)	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm – 10-Gauge)	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm – 10-Gauge)	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm – 10-Gauge)
FEATURES									
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened
Operator Seat	Deluxe Suspension with 3-D Isolation Mounts	Deluxe Suspension with 3-D Isolation Mounts	MyRIDE [™] Suspension System	Deluxe Suspension with 3-D Isolation Mounts	Deluxe Suspension with 3-D Isolation Mounts	Deluxe Suspension with 3-D Isolation Mounts	Deluxe Suspension with 3-D Isolation Mounts	MyRIDE [™] Suspension System	Deluxe Suspension with 3-D Isolation Mounts
Arm Rests	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Seat Suspension System	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Folding ROPS	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Storage Compartment	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Foot Pedal Deck Lift	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Z Stand	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access
WEIGHTS AND MEASUREMENTS									
Weight	1,254 lbs. / 568.8 kg	1,254 lbs. / 568.8 kg	1,370 lbs. / 621.4 kg	1,290 lbs. / 585.2 kg	1,289 lbs. / 584.7 kg	1,350 lbs. / 612.3 kg	1,334 lbs. / 605.1 kg	1,440 lbs. / 653.2 kg	1,369 lbs. / 621 kg
ROPS Height (Folded)	46.8" / 118.9 cm	46.8" / 118.9 cm	46.8" / 118.9 cm	46.8" / 118.9 cm	46.8" / 118.9 cm	46.8" / 118.9 cm	46.8" / 118.9 cm	46.8" / 118.9 cm	46.8" / 118.9 cm
ROPS Height (Upright)	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm
Deck Clearance Width	61.7" / 156.7 cm	61.7" / 156.7 cm	61.7" / 156.7 cm	61.7" / 156.7 cm	61.7" / 156.7 cm	73.6" / 186.9 cm	73.6" / 186.9 cm	73.6" / 186.9 cm	73.6" / 186.9 cm
Deflector Width	75.7" / 192.3 cm	75.7" / 192.3 cm	75.7" / 192.3 cm	75.7" / 192.3 cm	75.7" / 192.3 cm	87.6" / 222.5 cm	87.6" / 222.5 cm	87.6" / 222.5 cm	87.6" / 222.5 cm
Length	83.1" / 211.1 cm	83.1" / 211.1 cm	83.1" / 211.1 cm	83.1" / 211.1 cm	83.1" / 211.1 cm	86.1" / 218.7 cm	86.1" / 218.7 cm	86.1" / 218.7 cm	86.1" / 218.7 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.