



CONTOUR-FOLLOWING WING DECKS

Wing decks on the 96" model flex up 20 degrees and down 15 degrees to follow the terrain, hugging the ground for the smoothest possible cut. Folds to 72.5" to fit in trailer.



EXTENDED SERVICE INTERVALS

Save on maintenance with extended service intervals and a deck design that uses up to four matching blades. The mower is also backed by a 5-year, 2,000-hour limited warranty (first two years no-hour-limit).

THE NEW STANDARD IN COMFORT

The floor pan and deluxe suspension seat are iso-mounted to reduce vibration. That results in a better operator experience and more productivity.



SUPERIOR PERFORMANCE

Powered by (an optional) Tier 4-compliant, three-cylinder, 1.6 liter, 37 hp Yanmar diesel engine, this mower is packed with power to tackle the toughest mowing jobs.

	74028	74029	74072	74074	74096					
POWER SYSTEM										
Commercial Engines at 3600 RPM*	25 hp Yanmar Diesel 1267cc	25 hp Yanmar Diesel 1267cc	37 hp Yanmar Diesel 1642cc	37 hp Yanmar Diesel 1642cc	37 hp Yanmar Diesel 1642cc					
Heavy-Duty Canister Air Cleaner	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor					
Drive Tires	26" x 12" - 12" (66.0 x 30.5 x 30.5 cm)	26" x 12" - 12" (66.0 x 30.5 x 30.5 cm)	26" x 12" - 12" (66.0 x 30.5 x 30.5 cm)	26" x 12" - 12" (66.0 x 30.5 x 30.5 cm)	26" x 12" - 12" (66.0 x 30.5 x 30.5 cm)					
Caster Tires	15" x 6" - 6" (38.1 x 15.2 x 15.2 cm)	15" x 6" - 6" (38.1 x 15.2 x 15.2 cm)	15" x 6" - 6" (38.1 x 15.2 x 15.2 cm)	15" x 6" - 6" (38.1 x 15.2 x 15.2 cm)	15" x 6" - 6" (38.1 x 15.2 x 15.2 cm)					
Fuel/Capacity	Flat-Free Semi-Pneumatic Diesel/12.5 Gal (45.4 L)	Flat-Free Semi-Pneumatic Diesel/12.5 Gal (45.4 L)	Flat-Free Semi-Pneumatic Diesel/12.5 Gal (45.4 L)	Flat-Free Semi-Pneumatic Diesel/12.5 Gal (45.4 L)	Flat-Free Semi-Pneumatic Diesel/12.5 Gal (45.4 L)					
Hour Meter	Horizon™ Technology	Horizon Technology	Horizon Technology	Horizon Technology	Horizon Technology					
Hydraulic Drive System	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump					
Max Ground Speed (Fwd)	12.5 mph (20.1 km/h)	12.5 mph (20.1 km/h)	12.5 mph (20.1 km/h)	12.5 mph (20.1 km/h)	12.5 mph (20.1 km/h)					
Clutch	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc					
MOWING DECKS										
Deck Size	60" (152.4 cm) (Rear Discharge)	72" (182.9 cm) (Rear Discharge)	72" (182.9 cm)	72" (182.9 cm) (Rear Discharge)	96" (243.8 cm) (Rear Discharge)					
Cutting Deck	7-Gauge TURBO FORCE™	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE					
Bull-Nose Bumper	Standard	Standard	Standard	Standard	Standard					
Deck Depth	5.5" (14.0 cm)	5.5" (14.0 cm)	5.5" (14.0 cm)	5.5" (14.0 cm)	5.5" (14.0 cm)					
Adjustable Discharge Baffle	Standard	N/A	Standard	N/A	N/A					
Rubber Discharge Chute	Standard	N/A	Standard	N/A	N/A					
Deck Lift Design	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch					
Spindle Housings	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron	9" (22.9 cm) Diameter Cast Iron					
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard	Standard	Standard	Standard	Standard					
Spindle Bearings	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free					
Cutting Height	1.0" - 5.5" (2.5 - 14.0 cm)	1.0" - 5.5" (2.5 - 14.0 cm)	1.0" - 5.5" (2.5 - 14.0 cm)	1.0" - 5.5" (2.5 - 14.0 cm)	1.0" - 5.5" (2.5 - 14.0 cm)					
Blades	3 blades at 20.5" length	3 blades at 24.5" length	3 blades at 24.5" length	3 blades at 24.5" length	4 blades at 24.5" length					
Blade Tip Speed	18,200+ ft/min	14,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,100+ ft/min					
Shaft Drive	Standard	Standard	Standard	Standard	Standard					
Anti-Scalp Rollers	4 Standard, 2 Side Skids	4 Standard, 2 Side Skids	6 Standard	4 Standard, 2 Side Skids	13 Standard					
FEATURES										
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened					
Operator Seat	Deluxe Suspension (Iso-Mount, Flip-Up)	Deluxe Suspension (Iso-Mount, Flip-Up)	Deluxe Suspension (Iso-Mount, Flip-Up)	Deluxe Suspension (Iso-Mount, Flip-Up)	Deluxe Suspension (Iso-Mount, Flip-Up)					
Arm Rests	Standard	Standard	Standard	Standard	Standard					
Seat Suspension System	Standard	Standard	Standard	Standard	Standard					
Folding ROPS	Standard	Standard	Standard	Standard	Standard					
Storage Compartment	Standard	Standard	Standard	Standard	Standard					
Z Stand	N/A	N/A	N/A	N/A	N/A					
Floor Pan	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount					
WEIGHTS AND MEASUREMENTS										
Weight	1,957 lbs.	887.7 kg	1,964 lbs.	890.9 kg	2,067 lbs.	937.5 kg	2,143 lbs.	972 kg	2,650 lbs.	1,202 kg
ROPS Height (Folded)	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm
ROPS Height (Upright)	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm
Deck Clearance Width	66.3"	186.4 cm	78.3"	198.9 cm	73.6"	186.9 cm	78.3"	198.9 cm	102.3"	259.8 cm
Deflector Width	N/A	N/A	N/A	N/A	87.6"	222.5 cm	N/A	N/A	N/A	N/A
Length	96.48"	245.1 cm	100.68"	255.7 cm	99.68"	245.1 cm	100.68"	255.7 cm	97.38"	247.3 cm

* The gross horsepower of these diesel engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.