

GRANDSTAND®

STAND-ON MOWERS

STAND UP TO ANY TERRAIN.

#1

NUMBER ONE
ZERO-TURN
STAND-ON¹

BUMPY PATCHES AND CHALLENGING TERRAIN ARE ALL IN A DAY'S WORK—but feeling them doesn't need to be. GrandStand® combines the speed and comfort of a zero-turn rider with the on-and-off ease of a walk-behind for speed and maneuverability. And now the GrandStand is even better with all-new next-generation upgrades that enhance productivity, lower maintenance and make service a breeze.

IMPROVE PRODUCTIVITY with easy access on and off the machine—up to 10.5 gallons of fuel capacity on 48", 52" and 60" models—to mow longer with fewer stops.

GAIN SPEED AND PERFORMANCE with a new 10 mph max forward ground speed and responsive solid drive linkage. (Select models only.)

SAVE MAINTENANCE AND TIME with no hydraulic hoses, no daily/weekly grease points and a new engine design that allows extra room for service access. The fuel tank can also be removed without draining for easy service access to the transmission and controls.

2.6–5.5 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



TRACTION AND HANDLING

A wide stance and optimal balance enhance hillside stability and control. Operators can shift weight as needed to further enhance performance.



2-IN-1 VERSATILITY

Foldable operator platform instantly converts the machine to a walk-behind. It easily lowers back down when it's time to ride, saving time and trailer space.



CUSHIONED SUSPENSION

Flex-Ride operator platform suspension self-compensates for operators of all sizes, resulting in less fatigue and higher productivity throughout the day.



POWERED BAGGER

Compact side-mounted soft twin bagger and vertically mounted blower allow maneuverability in tight spaces and maximum visibility.

	74534 79534 CARB Model	74536	72504 71504 CARB Model	72518 [†]	72505 71505 CARB Model	72519	72513	
POWER SYSTEM								
Commercial Engines at 3600 RPM*	15 hp Kawasaki [†] FS (603cc)	15 hp Kawasaki FS (603cc)	22 hp Kawasaki FX (726cc)	23 hp Kohler [†] Command PRO [®] EFI (747cc)	22 hp Kawasaki FX (726cc)	25 hp Kohler Command PRO EFI (747cc)	25 hp Kohler Command PRO EFI (747cc)	
Starter	Electric	Electric	Electric	Electric	Electric	Electric	Electric	
Heavy-Duty Canister Air Cleaner	N/A	Standard	Standard	Standard	Standard	Standard	Standard	
Drive Tires	18" x 8.5" – 8" (45.7 x 21.6 – 20.3 cm)	18" x 9.5" – 8" (45.7 x 24.1 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	
Caster Tires	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	
Fuel/Capacity	Gas/7.8-Gal (29.5 L)	Gas/7.8-Gal (29.5 L)	Gas/10.5-Gal (39.7 L)	Gas/10.5-Gal (39.7 L)	Gas/10.5-Gal (39.7 L)	Gas/10.5-Gal (39.7 L)	Gas/10.5-Gal (39.7 L)	
Digital Hour Meter	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Hydraulic Drive System	Pumps & Wheel Motors	Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	
Pump	10cc/rev	10cc/rev	10cc/rev	10cc/rev	10cc/rev	10cc/rev	10cc/rev	
Wheel Motor	10 cir	10 cir	10 cir	10 cir	10 cir	10 cir	10 cir	
Maximum Forward Speed	8 mph (12.9 km/h)	8 mph (12.9 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	
Clutch	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	
MOWING DECKS								
Deck Size	36" (91.4 cm)	40" (101.6 cm)	48" (121.9 cm)	48" (121.9 cm)	52" (132.1 cm)	52" (132.1 cm)	60" (152.4 cm)	
Cutting Deck	7-Gauge TURBO FORCE [®]	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	
Bullnose Bumper	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Adjustable Discharge Baffle	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Rubber Discharge Chute	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Deck Lift Design	Compression Spring	Compression Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	
Spindle Housings	9 3/8" (23.8 cm) Diameter Cast Aluminum	9 3/8" (23.8 cm) Diameter Cast Aluminum	9 3/8" (23.8 cm) Diameter Cast Aluminum	9 3/8" (23.8 cm) Diameter Cast Aluminum	9 3/8" (23.8 cm) Diameter Cast Aluminum	9 3/8" (23.8 cm) Diameter Cast Aluminum	9 3/8" (23.8 cm) Diameter Cast Aluminum	
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Spindle Bearings	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	
Cutting Height	1.0" – 5.0" (2.5 – 12.7 cm) .204" (.5 cm) Heat-Treated Steel	1.0" – 5.0" (2.5 – 12.7 cm) .204" (.5 cm) Heat-Treated Steel	1.5" – 5.0" (3.8 – 12.7 cm) .204" (.5 cm) Heat-Treated Steel	1.5" – 5.0" (3.8 – 12.7 cm) .204" (.5 cm) Heat-Treated Steel	1.5" – 5.0" (3.8 – 12.7 cm) .204" (.5 cm) Heat-Treated Steel	1.5" – 5.0" (3.8 – 12.7 cm) .204" (.5 cm) Heat-Treated Steel	1.5" – 5.0" (3.8 – 12.7 cm) .204" (.5 cm) Heat-Treated Steel	
Blades	Heat-Treated Steel	Heat-Treated Steel	Heat-Treated Steel	Heat-Treated Steel	Heat-Treated Steel	Heat-Treated Steel	Heat-Treated Steel	
Blade Tip Speed	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	
Anti-Scalp Rollers	N/A	N/A	Optional	Optional	Optional	Optional	Standard	
Carrier Frame Construction	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	
FEATURES								
Steering Controls	Twin Lever	Twin Lever	Twin Lever	Twin Lever	Twin Lever	Twin Lever	Twin Lever	
Operator Platform	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	
WEIGHTS AND MEASUREMENTS								
Weight	833 lbs.	377.8 kg	844 lbs.	382.8 kg	890 lbs.	403.7 kg	881 lbs.	399.6 kg
Height	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm
Deck Clearance Width	37.6"	95.5 cm	41.8"	106.2 cm	49.5"	125.7 cm	49.5"	125.7 cm
Deflector Width	51.6"	131.1 cm	55.8"	141.7 cm	63.5"	161.3 cm	63.5"	161.3 cm
Length (Platform Up)	61"	154.9 cm	57"	144.8 cm	61"	154.9 cm	61"	154.9 cm
Length (Platform Down)	74"	188 cm	70"	177.8 cm	75"	190.5 cm	75"	190.5 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995.

As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

[†]CARB compliant model or model available.