

PROLINE™ SERIES

MID-SIZE MOWERS

NEW

**TIME SAVER.
MONEY MAKER.**



Contractors know every second not mowing is a lost opportunity, and training your crew on new equipment can cause unnecessary setbacks in time and money.

MAXIMIZE YOUR EFFICIENCY with the Toro PROLINE mid-size mowers. Not only will your crew be mowing in no time with easy-to-learn controls, but you'll also enjoy top-line reliability and professional cutting performance.

YOU'LL LOVE THE CONVENIENCE of the 2-wheel sulky, which rotates 360° and simply folds away when not in use; no more attaching and removing when trailering! Sold separately.

AND YOU CAN REST EASY knowing that Toro stands behind its mowers with a 3-year, 750-hour warranty.

	44410	44409 [†]	44424	44423 [†]	44427	44430	44448 [†] HDX	44454 [†] HDX								
POWER SYSTEM																
Commercial Engines at 3600 RPM*	14.5 hp Kawasaki® FS	14.5 hp Kawasaki FS	15 hp Kawasaki FS	15 hp Kawasaki FS	18.5 hp Kawasaki FS	22 hp Kawasaki FS	22 hp Kawasaki FX	22 hp Kawasaki FX								
Starter	Electric	Electric														
Drive Tires	18"	18"	20"	20"	20"	20"	20"	20"								
Caster Tires	9"	9"	11"	11"	11"	11"	11"	11"								
Fuel/Capacity	Gas / 5 Gal (18.9 L)	Gas / 5 Gal (18.9 L)														
Control System	Twin Lever	Twin Lever														
Transmission	ZT-2800	ZT-2800	ZT-2800	ZT-2800	ZT-2800	ZT-2800	ZT-3100	ZT-3100								
Hour Meter	Standard	Standard														
Maximum Forward Speed	7 mph (11.3 km/h)	7 mph (11.3 km/h)														
Brake System	Integrated Parking Brake	Integrated Parking Brake														
MOWING DECKS																
Deck Size	36" (91.4 cm)	36" (91.4 cm)	48" (121.9 cm)	48" (121.9 cm)	54" (137.2 cm)	60" (152.4 cm)	48" (121.9 cm)	54" (137.2 cm)								
Cutting Deck	10 Gauge High-Strength Steel	7/10 Gauge High-Strength Steel	7/10 Gauge High-Strength Steel													
Bullnose Bumper	Standard	Standard														
Adjustable Discharge Baffle	N/A	N/A														
Rubber Discharge Chute	-	-	-	-	-	-	Standard	Standard								
Deck Lift Assist	Standard	Standard														
Spindle Housings	8" Cast Aluminum	8" Cast Aluminum														
Spindle Bearings	Maintenance Free	Maintenance Free														
Cutting Height	1.5" – 4.5" (3.8 – 11.4 cm)	1.5" – 4.5" (3.8 – 11.4 cm)														
Blades	.204" Heat-Treated Steel	.204" Heat-Treated Steel														
Blade Tip Speed	18,500+ ft./min.	18,500+ ft./min.														
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt														
Anti-Scalp Rollers	Standard	Standard														
WEIGHTS AND MEASUREMENTS																
Weight	580 lbs.	263.1 kg	585 lbs.	265.4 kg	639 lbs.	289.8 kg	644 lbs.	292.1 kg	648 lbs.	294.9 kg	693 lbs.	314.3 kg	669 lbs.	303.5 kg	695 lbs.	315.2 kg
Height	45"	114.3 cm	45"	114.3 cm	46"	116.8 cm	46"	116.8 cm	46"	116.8 cm	46"	116.8 cm	46"	116.8 cm	46"	116.8 cm
Deck Clearance Width	37"	94.0 cm	37"	94.0 cm	49"	124.5 cm	49"	124.5 cm	55"	139.7 cm	61"	154.9 cm	49"	124.5 cm	55"	139.7 cm
Deflector Width	51"	129.5 cm	51"	129.5 cm	63"	160.0 cm	63"	160.0 cm	69"	175.3 cm	75"	190.5 cm	63"	160.0 cm	69"	175.3 cm
Length	77"	195.6 cm	77"	195.6 cm	80"	203.2 cm	80"	203.2 cm	80"	203.2 cm	83"	210.8 cm	80"	203.2 cm	80"	203.2 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

[†]CARB compliant model or model available.



DRIVE WITH EASE

Shred grass in no time with the easy-to-learn twin-lever controls and drive assist with three settings.



MOWING MUSCLE

Ensure you never lose a job because of broken equipment with a reliable Kawasaki engine that drives .204" blades for a gorgeous, professional cut.



MADE TO LAST

Your Toro is also built to take on years of rough rides with a bull nose bumper and 20" wheels with curb clearance.



QUICK ADJUSTMENT

Changing cut lengths on the go is a snap with a single-point height of cut adjustment.



NO-HASSLE SULKY

The 2-wheel sulky simply folds away, meaning no need to attach and remove it when trailering. Sold separately.