

Z MASTER[®]

2000 SERIES

NEW

MEET YOUR NEW WORKHORSE.



Heads will definitely turn when you're towing one of the coolest bulls in our pen around town. But the Z Master 2000 really shines once it's off the trailer, as it's bulging at the seams with commercial performance, reliability and efficiency at an unbeatable value.

FINISH MORE JOBS FASTER THAN EVER

with the powerful engines and upgraded hydros, and it's built to take on the toughest hits with a fully tubular frame, large 24" rear tires and 7/10-gauge steel deck with bullnose bumper.

WORLD-CLASS COMFORT, built-in lights and your customers will love the beautiful cut of the TURBO FORCE[®] deck.

REST EASY knowing that Toro stands behind its mowers with a 4-year, 750-hour warranty.



QUICK CARRY SYSTEM



TRIPLE THREAT UTILITY KIT

Attach tools and accessories directly to the mower with innovative tool-mounting brackets. Includes Bucket Holder Kit, Universal Mount and Trimmer Mount.

Sold separately.

4.6-6.1

Maximum Acres/Hour

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



NO MORE ROCKY RIDES

You shouldn't feel like you've gone 12 rounds with your lawn after mowing it. Save your body from the toughest terrain and avoid slow mowing speeds with the MyRIDE suspension system. *Select models.*



PRO DNA

Commercial DNA courses through these machines' veins with the same technology professionals depend on. Get a beautiful, professional-looking lawn.



LIGHT THE WAY

Built-in LED lights give you a superb panoramic view in dark conditions.

Select models.



MADE TO LAST

Enjoy years of reliable performance with a fully tubular frame and 7/10-gauge steel deck.

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See your local Toro dealer or consult owners manual for complete warranty details.

[†]CARB compliant model or model available.

	74490	74491	74492	74493 HDX MyRIDE [®] Suspension System	74494 HDX MyRIDE Suspension System	74495†	74496†	74497 HDX† MyRIDE Suspension System
POWER SYSTEM								
Commercial Engines at 3600 RPM*	Toro 24.5 hp w/ HDAC	Toro 24.5 hp w/ HDAC	Toro 24.5 hp w/ HDAC	Toro 24.5 hp w/ HDAC	Toro 24.5 hp w/ HDAC	23.5 hp* Kawasaki FX (726cc)	23.5 hp* Kawasaki FX (726cc)	23.5 hp* Kawasaki FX (726cc)
Starter	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Heavy-Duty Donaldson [®] Canister-Style Air Cleaner	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Drive Tires	24" x 9.5" - 12" (61 x 24.1 - 30.5 cm)	24" x 9.5" - 12" (61 x 24.1 - 30.5 cm)	24" x 12" - 12" (61 x 30.5 - 30.5 cm)	24" x 9.5" - 12" (61 x 24.1 - 30.5 cm)	24" x 12" - 12" (61 x 30.5 - 30.5 cm)	24" x 9.5" - 12" (61 x 24.1 - 30.5 cm)	24" x 12" - 12" (61 x 30.5 - 30.5 cm)	Tweels 24" x 12" - 12" (61 x 30.5 - 30.5 cm)
Caster Tires (Cage Bearing)	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm)	13" x 6.5" - 6" (33 x 16.5 - 15.2 cm) Flat-Free Semi-Pneumatic
Fuel/Capacity	Gas/7-Gal (26.5 L)	Gas/7-Gal (26.5 L)	Gas/7-Gal (26.5 L)	Gas/7-Gal (26.5 L)	Gas/7-Gal (26.5 L)	Gas/7-Gal (26.5 L)	Gas/7-Gal (26.5 L)	Gas/7-Gal (26.5 L)
Digital Hour Meter	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Hydraulic Drive System	ZT-3400 Integrated Pumps & Wheel Motors	ZT-3400 Integrated Pumps & Wheel Motors	ZT-3400 Integrated Pumps & Wheel Motors	ZT-3800 Integrated Pumps & Wheel Motors	ZT-3800 Integrated Pumps & Wheel Motors	ZT-3400 Integrated Pumps & Wheel Motors	ZT-3400 Integrated Pumps & Wheel Motors	ZT-3800 Integrated Pumps & Wheel Motors
Maximum Forward Speed	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	11 mph (17.7 km/h)	11 mph (17.7 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	11 mph (17.7 km/h)
Clutch	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic
MOWING DECKS								
Deck Size	48" (121.9 cm)	52" (132.1 cm)	60" (152.4 cm)	52" (132.1 cm)	60" (152.4 cm)	48" (121.9 cm)	60" (152.4 cm)	60" (152.4 cm)
Cutting Deck	7/10-Gauge High-Strength Steel TURBO FORCE [™]	7/10-Gauge High-Strength Steel TURBO FORCE [™]	7/10-Gauge High-Strength Steel TURBO FORCE [™]	7/10-Gauge High-Strength Steel TURBO FORCE [™]	7/10-Gauge High-Strength Steel TURBO FORCE [™]	7/10-Gauge High-Strength Steel TURBO FORCE [™]	7/10-Gauge High-Strength Steel TURBO FORCE [™]	7/10-Gauge High-Strength Steel TURBO FORCE [™]
Bullnose Bumper	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Rubber Discharge Chute	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Deck Lift Design	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring
Spindle Housings	8" (20.3 cm) Diameter Aluminum	8" (20.3 cm) Diameter Aluminum	8" (20.3 cm) Diameter Aluminum	8" (20.3 cm) Diameter Aluminum	8" (20.3 cm) Diameter Aluminum	8" (20.3 cm) Diameter Aluminum	8" (20.3 cm) Diameter Aluminum	8" (20.3 cm) Diameter Aluminum
1" (2.5 cm) Spindle Shaft	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Spindle Bearings	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free
Cutting Height	1.5" - 5" (25" increments) 3.8 - 12.7 cm (6 cm increments)	1.5" - 5" (25" increments) 3.8 - 12.7 cm (6 cm increments)	1.5" - 5" (25" increments) 3.8 - 12.7 cm (6 cm increments)	1.5" - 5" (25" increments) 3.8 - 12.7 cm (6 cm increments)	1.5" - 5" (25" increments) 3.8 - 12.7 cm (6 cm increments)	1.5" - 5" (25" increments) 3.8 - 12.7 cm (6 cm increments)	1.5" - 5" (25" increments) 3.8 - 12.7 cm (6 cm increments)	1.5" - 5" (25" increments) 3.8 - 12.7 cm (6 cm increments)
Deck Depth	5" (12.7 cm)	5" (12.7 cm)	5" (12.7 cm)	5" (12.7 cm)	5" (12.7 cm)	5" (12.7 cm)	5" (12.7 cm)	5.5" (14 cm)
Blades	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel
Blade Tip Speed	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt

FEATURES

MyRIDE [®] Suspension System								
	N/A	N/A	N/A	MyRIDE Suspension System	MyRIDE Suspension System	N/A	N/A	MyRIDE Suspension System
Comfort Platform	N/A	N/A	N/A	3.0" (7.62 cm)	3.0" (7.62 cm)	N/A	N/A	3.0" (7.62 cm)
Platform Travel	N/A	N/A	N/A	1 center / 2 rear	1 center / 2 rear	N/A	N/A	1 center / 2 rear
Shocks	N/A	N/A	N/A	Deluxe w/ Armrests	Deluxe w/ Armrests	N/A	N/A	Deluxe w/ Armrests
Seat	N/A	N/A	N/A	5 Detents, Infinite Adjustability	5 Detents, Infinite Adjustability	N/A	N/A	5 Detents, Infinite Adjustability
Adjustability	N/A	N/A	N/A	1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened	1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened	1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened	1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened	1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened
Steering Controls	High-Back Suspension w/Armrests	High-Back Suspension w/Armrests	High-Back Suspension w/Armrests	Deluxe w/ Armrests	Deluxe w/ Armrests	High-Back Suspension w/Armrests	High-Back Suspension w/Armrests	Deluxe w/ Armrests and Hard Top Sun Canopy
Operator Seat	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Folding ROPS	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Tool-Mounting Capability	Side Console / Rear Guard Ready	Side Console / Rear Guard Ready	Side Console / Rear Guard Ready	Side Console / Rear Guard Ready	Side Console / Rear Guard Ready	Side Console / Rear Guard Ready	Side Console / Rear Guard Ready	Side Console / Rear Guard Ready
Lift Mechanism	Quick-Attach Jack Ready	Quick-Attach Jack Ready	Quick-Attach Jack Ready	Quick-Attach Jack Ready	Quick-Attach Jack Ready	Quick-Attach Jack Ready	Quick-Attach Jack Ready	Quick-Attach Jack Ready
Warranty**	4 Year 750 Hour Limited	4 Year 750 Hour Limited	4 Year 750 Hour Limited	4 Year 750 Hour Limited	4 Year 750 Hour Limited	4 Year 750 Hour Limited	4 Year 750 Hour Limited	4 Year 750 Hour Limited

WEIGHTS AND MEASUREMENTS

Weight	870 lbs. / 394.6 kg	890 lbs. / 403.7 kg	920 lbs. / 417.3 kg	1,012 lbs. / 459 kg	1,036 lbs. / 470 kg	870 lbs. / 394.6 kg	920 lbs. / 417.3 kg	1,036 lbs. / 470 kg
ROPS Height (Folded)	49" / 124.5 cm	49" / 124.5 cm	49" / 124.5 cm	49" / 124.5 cm	49" / 124.5 cm	49" / 124.5 cm	49" / 124.5 cm	49" / 124.5 cm
ROPS Height (Upright)	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm	70.5" / 179.1 cm
Deck Clearance Width	53" / 134.6 cm	56.75" / 144.1 cm	63.5" / 161.3 cm	66" / 167.6 cm	53" / 134.6 cm	53" / 134.6 cm	63.5" / 161.3 cm	53" / 134.6 cm
Deflector Width	63.25" / 160.7 cm	67.25" / 170.8 cm	75.25" / 191.1 cm	75.25" / 191.1 cm	63.25" / 160.7 cm	63.25" / 160.7 cm	75.25" / 191.1 cm	63.25" / 160.7 cm
Length	82" / 208.3 cm	82" / 208.3 cm	83" / 210.8 cm	84.25" / 214 cm	82" / 208.3 cm	82" / 208.3 cm	83" / 210.8 cm	82" / 208.3 cm