

Z MASTER[®]

5000 SERIES
REAR DISCHARGE
MOWERS

NEW



NEED A PRODUCTIVITY EDGE?
Our rear discharge models let operators trim on either side of the deck while keeping sidewalks and flowerbeds clipping-free.

SAVE TIME AND CLEANUP with the rear discharge deck design that drops clippings within the path of the mower.

GAIN FUEL EFFICIENCY with Kohler[®] Command PRO[®] engines featuring electronic fuel injection (EFI).

TORO[®]



5.5–6.5 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



REAR DISCHARGE

Two blades rotate clockwise and one blade rotates counter-clockwise to spread clippings evenly through the rear discharge tunnel, saving time and cleanup.



ANTI-SCALPING SYSTEM

Durable, adjustable side bumpers protect the mower while enhancing deck flotation over uneven surfaces.



RUGGED PERFORMANCE

Highly productive in taller grass and weed conditions.

	72921†	72922†		
POWER SYSTEM				
Commercial Engines at 3600 RPM*	26.5 hp Kohler Command PRO EFI (747cc)	26.5 hp Kohler Command PRO EFI (747cc)		
Starter	Electric	Electric		
Heavy-Duty Canister Air Cleaner	Standard	Standard		
Drive Tires	▶ • 24" x 12" – 12" Tweels • (61 x 30.5 – 30.5 cm)	• 24" x 12" – 12" Tweels • (61 x 30.5 – 30.5 cm)		
Caster Tires	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic	13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Flat-Free Semi-Pneumatic		
Fuel/Capacity	Gas/12-Gal (45.4 L)	Gas/12-Gal (45.4 L)		
Hour Meter	Smart Hour Meter	Smart Hour Meter		
Hydraulic Drive System	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors		
Pump	12cc/rev (shock valves)	12cc/rev (shock valves)		
Wheel Motor	14.6 cir	14.6 cir		
Maximum Forward Speed	10 mph (16.1 km/h)	10 mph (16.1 km/h)		
Clutch	Electromagnetic	Electromagnetic		
MOWING DECKS				
Deck Size	60" (152.4 cm)	▶ 72" (182.9 cm)		
Cutting Deck	7-Gauge TURBO FORCE Rear Discharge	7-Gauge TURBO FORCE Rear Discharge		
Bullnose Bumper	Standard	Standard		
Adjustable Discharge Baffle	-	-		
Rubber Discharge Chute	-	-		
Deck Lift Design	Extension Spring	Extension Spring		
Spindle Housings	9" (22.9 cm) Dia. Cast Aluminum	9" (22.9 cm) Dia. Cast Aluminum		
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard	Standard		
Spindle Bearings	Greaseable	Greaseable		
Cutting Height	1.0" – 5.5" (2.5 – 14 cm)	1.0" – 5.5" (2.5 – 14 cm)		
Blades	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel		
Blade Tip Speed	18,500+ ft/min	18,500+ ft/min		
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt		
Anti-Scalp Rollers	2 Side Bumpers/4 Rollers	2 Side Bumpers/4 Rollers		
Carrier Frame Construction	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		
FEATURES				
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		
Operator Seat	Deluxe Suspension with 3-D Isolation Mounts	Deluxe Suspension with 3-D Isolation Mounts		
Arm Rests	Standard	Standard		
Seat Suspension System	Standard	Standard		
Folding ROPS	Standard	Standard		
Storage Compartment	Standard	Standard		
Foot Pedal Deck Lift	Standard	Standard		
Z Stand	Optional	Optional		
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access		
WEIGHTS AND MEASUREMENTS				
Weight	1,335 lbs.	605.5 kg	1,335 lbs.	605.5 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	78.3"	198.9 cm	78.3"	198.9 cm
Deflector Width	N/A	N/A	N/A	N/A
Length	87.3"	221.7 cm	87.3"	221.7 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

†CARB compliant model or model available.

